



其它電池

其它電池/充電器



- Wide Temperature Range from -55°C to +85°C
- Superior Shelf Life and Reliability: over 10 year at room temperature and self-discharge rate is less than 1% of its nominal capacity per year
- Energy type is bobbin structure and best suit for low current discharges. It may require depassivation before medium currents can be delivered

Part No.	Product No.	說明	Volt.	Capacity mAh	尺寸(mm)	Weight (g)
51862	ER13170	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	450mAh	13*17.5mm	6g
51864	ER14250	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	1200mAh	1/2AA 14.5*25.2mm	11g
51865	ER14505	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	2400mAh	AA 14.5*50.5mm	22g
51805	ER14505-AX	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	2400mAh	AA 14.5*50.5mm	22g
51866	ER17335	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	2100mAh	2/3A 17.5*33.5mm	21g
51867	ER26500	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	8500mAh	C 26.2*50mm	53g
51868	ER34615	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	19000mAh	D 34*61.5mm	115.0
51869	ER9V	EEMB_10.8V 錳-亞硫酸氯電池 Li-SOCL2 Battery	10.8V	1200mAh	16.9*26*48.8mm	29g
51861	ER2450	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery Button	3.6V	500mAh	24.5*5.5mm	9g
48238	ER34070	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery Button	3.6V	1000mAh	32.9*7mm	17.0g
48239	ER34100	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery Button	3.6V	1700mAh	1/6D 32.9*10mm	25.0g



- Wide Temperature Range from -55°C to +85°C
- Superior Shelf life and Reliability: over 10 years at room temperature and self discharge rate is less than 1% of its nominal capacity per year
- High Power type is spiral structure and best suit for high current discharge for both continuous and pulse current. It may require depassivation before medium current can be delivered

Part No.	Product No.	說明	Volt.	Capacity mAh	尺寸(mm)	Weight (g)
51859	ER14250M	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	750mAh	1/2AA 14.5*25.2mm	10g
51856	ER14505M	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	1800mAh	AA 14.5*50.5mm	22g
51858	ER26500M	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	6500mAh	C 26.2*50mm	53g
51860	ER34615M	EEMB_3.6V 錳-亞硫酸氯電池 Li-SOCL2 Battery	3.6V	14000mAh	D 34*61.5mm	118g



- 9V鋰電微電腦快速充電器，可同時提供2顆9V鋰電池充電
- 輸入：AC100~240V, 50~60Hz
- 輸出：DC9V
- 充電電流：300mAh

- 紅燈亮：充電中
- 綠燈亮：充電時或等待充電
- 充電時間：約2小時

Part No.	Product No.	說明	Volt.	尺寸(mm)	Weight (g)
57810	GN-9VCL	2 槽交換式電源鋰電池充電器組(Include GN-LI9V*1PC)	Input:AC100~240V,50/60Hz	70*74.8mm	127.2g



- 保護功能：短路，過充，過放，過電流等保護
- 充電電流：300mA

Part No.	Product No.	說明	Volt.	Capacity mAh	尺寸(mm)	Weight (g)
17308	HH095	TeKWell_行動式電力銀行	3.7V	1A	54*54*20mm	78g



- 輸出電壓：1.65VDC
- 輸入電流：4*125mA
- 可同時充電AA與AAA電池1~4顆
- 長時間將電池置於充電器裡面充電，並不會導致電池過度充電

Part No.	Product No.	說明	Volt.	Weight (g)
54356	PH-PP2-3X4	4 槽交換式鹼電池充電器組(內含 XL-AA*4PCS)	Input:90~240VAC,5W,50/60Hz	238.4g



- 四組獨立充電回路，4個獨立的雙色LED指示燈
- 充電後自動斷電功能，長期將電池放置充電器內，不會造成電池過充現象
- 自動檢知老舊死亡與不可充電之電池，操作簡單方便
- 充電槽防呆設計，避免將電池極性放反

Part No.	Product No.	說明	Volt.	Weight (g)
54358	SC-SA1-3X4	4 槽交換式電源萬用充電器組(內含 XL-AA*4PCS)	Input:100~240VAC/Output:3VDC	0.4kg



Part No.	Product No.	製造廠商	說明	Volt.	Capacity mAh	尺寸(mm)	Weight (g)
28264	THS7BAT	Tektronix	Tektronix_High-capacity	4.8V	2800mAh	Φ: 13mm L: 195mm	250g
54775	THS7CHG	Tektronix	Tektronix_充電器	4.8V	2800mAh	Φ: 13mm L: 195mm	250g



Part No.	Product No.	說明	Volt.	Weight (g)
54347	UL-PP2-3R4	2 槽交換式電源鹼電池充電器組(內含 Reg-AA*4PCS)	Input:90~240VAC,5W,50/60Hz	210.5g
60228	UL-PP2-4R4	2 槽交換式電源鹼電池充電器組(內含 Reg-AAA*4PCS)	Input:90~240VAC,5W,50/60Hz	210.5g

