



26-30AWG 紅灰綠扁平排線



- Average tensile strength; 1500lb/inch²
- Percent of original: 70% at least
- Average elongation: 200%
- Percent of original: 65% at least


USAGE: car, elevator, communication (switch machine), digital control facilities, apparatus and clock, inspection machine and so on

Part No.	Product No.	說明	Num. Of Cores	Length/Reel	Temp°C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
40669	HRG-034L02000FT	紅灰綠扁平排線	34P	200Ft/R(3.59Kg)	105	28AWG	UL2651	300V	1.27mm



Part No.	Product No.	說明	Num. Of Cores	Length/Reel	Temp. °C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
49212	I79-34P	紅灰綠扁平排線(RoSH)	24Pins	100M/R	105	28AWG	UL2651/E129583	300V	1.27mm


3M_28-30AWG 灰色扁平排線



- 28 AWG wire on .050 inch centers permits mass termination to a broad line of IDC connectors
- Stranded wire provides flexibility and extended product life
- Zippable for branching or discrete termination
- Available in Gray or Black

詳細產品規格請點擊www.100y.com.tw

Part No.	Product No.	製造廠商	說明	Num. Of Cores	Length/Reel	Temp°C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
43351	C3365/06	3M	3M 28 AWG 灰色扁平排線	06	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43340	C3365/08	3M	3M 28 AWG 灰色扁平排線	08	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43341	C3365/09	3M	3M 28 AWG 灰色扁平排線	09P	100Ft/30.5M	105	28	UL2651/ E42769	300V	1.27
9935	C3365/10	3M	3M 28 AWG 灰色扁平排線	10P	100Ft/30.5M	105	28	UL2651/ E42769	300V	1.27
43342	C3365/12	3M	3M 28 AWG 灰色扁平排線	12	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43343	C3365/14	3M	3M 28 AWG 灰色扁平排線	14	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43344	C3365/15	3M	3M 28 AWG 灰色扁平排線	15P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43345	C3365/16	3M	3M 28 AWG 灰色扁平排線	16P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43346	C3365/20	3M	3M 28 AWG 灰色扁平排線	20P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43347	C3365/24	3M	3M 28 AWG 灰色扁平排線	24P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43348	C3365/25	3M	3M 28 AWG 灰色扁平排線	25P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
9934	C3365/26	3M	3M 28 AWG 灰色扁平排線	26P	100Ft/30.5M	105	28	UL2651/ E42769	300V	1.27
43349	C3365/30	3M	3M 28 AWG 灰色扁平排線	30P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
3003	C3365/34	3M	3M 28 AWG 灰色扁平排線	34P	100Ft/30.5M	105	28	UL2651/ E42769	300V	1.27
43360	C3365/36	3M	3M 28 AWG 灰色扁平排線	36P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
43361	C3365/37	3M	3M 28 AWG 灰色扁平排線	37P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
3004	C3365/40	3M	3M 28 AWG 灰色扁平排線	40P	100Ft/30.5M	105	28	UL2651/ E42769	300V	1.27
43362	C3365/44	3M	3M 28 AWG 灰色扁平排線	44P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
3005	C3365/50	3M	3M 28 AWG 灰色扁平排線	50P	100Ft/30.5M	105	28	UL2651/ E42769	300V	1.27
43364	C3365/60	3M	3M 28 AWG 灰色扁平排線	60P	100Ft/30.5M	-20°C to +105°C	28	UL2651/ E42769	300V	1.27
8533	C3365/64	3M	3M 28 AWG 灰色扁平排線	64P	100Ft/30.5M	105	28	UL2651/ E42769	300V	1.27



- Meets external wiring requirements of National Electrical Code, Article 725(CL2)
- UL listed for USA and Canadian markets
- 28 AWG stranded wire on .050 inch centers permits mass termination to broad line of IDC connectors
- 360 degree expanded copper shielding provides 20 db average shielding effectiveness
- Primary cable is zippable for branching or discrete terminations

Part No.	Product No.	製造廠商	說明	Num. Of Cores	Length/Reel	Temp°C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
43421	3517/09	3M	3M_有遮蔽灰排線 #28 09P	09P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43422	3517/10	3M	3M_有遮蔽灰排線 #28 10P	10P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43423	3517/14	3M	3M_有遮蔽灰排線 #28 14P	14P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43424	3517/15	3M	3M_有遮蔽灰排線 #28 15P	15P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43433	3517/16	3M	3M_有遮蔽灰排線 #28 16P	16P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43434	3517/20	3M	3M_有遮蔽灰排線 #28 20P	20P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43435	3517/24	3M	3M_有遮蔽灰排線 #28 24P	24P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43436	3517/25	3M	3M_有遮蔽灰排線 #28 25P	25P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
28929	3517/26	3M	3M_有遮蔽灰排線	26P	100Ft/30.5M	80	28	E118773	300V	1.27
43437	3517/30	3M	3M_有遮蔽灰排線 #28 30P	30P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43438	3517/34	3M	3M_有遮蔽灰排線 #28 34P	34P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43439	3517/36	3M	3M_有遮蔽灰排線 #28 36P	36P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
43440	3517/37	3M	3M_有遮蔽灰排線 #28 37P	37P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45433	3517/40	3M	3M_有遮蔽灰排線 #28 40P	40P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
28928	3517/50	3M	3M_有遮蔽排線	50P	100Ft/30.5M	80	28	E118773	300V	1.27
45437	3517/60	3M	3M_有遮蔽灰排線 #28 60P	60P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45440	3517/64	3M	3M_有遮蔽灰排線 #28 64P	64P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27



電話：台灣：886-3-5753170
傳真：台灣：886-3-5753172
郵箱：台灣：sale@100y.com.tw

深圳：86-755-83298787
深圳：86-755-83640655
深圳：100y@vip.163.com

上海：86-21-34970699
上海：86-21-64605107
上海：100y-1@vip.163.com

3-16