




3M_28-30AWG 灰色扁平排線

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


- Round construction permits easier routing
- 28 AWG wire on .050 inch pitch permits mass termination to broad line of IDC connectors
- Continuous split/bond repeat allows for mass termination on 2.4 inch centers (approximate)
- Primary cable is zippable for branching or discrete terminations
- Meets external wiring requirements of National Electrical Code, Article 725(CL2)
- UL listed for USA and Canadian markets
- Dual shielding provides 35 db average shielding effectiveness

3M


Part No.	Product No.	製造廠商	說明	Num. Of Cores	Length/Reel	Temp°C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
45468	3659/09	3M	3M_有遮蔽灰排線 #28 09P	09P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45492	3659/10	3M	3M_有遮蔽灰排線 #28 10P	10P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45493	3659/14	3M	3M_有遮蔽灰排線 #28 14P	14P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45494	3659/15	3M	3M_有遮蔽灰排線 #28 15P	15P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45495	3659/16	3M	3M_有遮蔽灰排線 #28 16P	16P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45497	3659/20	3M	3M_有遮蔽灰排線 #28 20P	20P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45500	3659/24	3M	3M_有遮蔽灰排線 #28 24P	24P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45502	3659/25	3M	3M_有遮蔽灰排線 #28 25P	25P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45504	3659/26	3M	3M_有遮蔽灰排線 #28 26P	26P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45505	3659/34	3M	3M_有遮蔽灰排線 #28 34P	34P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45506	3659/36	3M	3M_有遮蔽灰排線 #28 36P	36P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45511	3659/37	3M	3M_有遮蔽灰排線 #28 37P	37P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45512	3659/40	3M	3M_有遮蔽灰排線 #28 40P	40P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45513	3659/50	3M	3M_有遮蔽灰排線 #28 50P	50P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45514	3659/60	3M	3M_有遮蔽灰排線 #28 60P	60P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27
45515	3659/64	3M	3M_有遮蔽灰排線 #28 64P	64P	100Ft/30.5M	-20°C to +80°C	28	E118773	300V	1.27



- Flex life of 100 million cycles at 1 3/4 inch diameter
- 19 strands of high strength copper alloy provide the longest flex life available for dynamic applications
- 28 AWG wire on .050 inch wire spacing permits mass termination to a broad line of IDC connectors
- Zippable for branching or discrete termination

3M

Part No.	Product No.	製造廠商	說明	Num. Of Cores	Length/Reel	Temp°C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
45086	C3319/09	3M	3M_28AWG 黑色排線	09P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45089	C3319/10	3M	3M_28AWG 黑色排線	10P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45091	C3319/14	3M	3M_28AWG 黑色排線	14P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45094	C3319/15	3M	3M_28AWG 黑色排線	15	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45095	C3319/16	3M	3M_28AWG 黑色排線	16P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45096	C3319/20	3M	3M_28AWG 黑色排線	20P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45243	C3319/24	3M	3M_28AWG 黑色排線	24P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45269	C3319/25	3M	3M_黑色排線 .050" 28AWG 25P (100Ft/R)	25P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45300	C3319/26	3M	3M_黑色排線 .050" 28AWG 26P (100Ft/R)	26P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
45303	C3319/30	3M	3M_黑色排線 .050" 28AWG 30P (100Ft/R)	30P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
43419	C3319/34	3M	3M_黑色排線 .050" 28AWG 25P (100Ft/R)	34P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
43420	C3319/36	3M	3M_黑色排線 .050" 28AWG 36P (100Ft/R)	36P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27
49870	C3319/40	3M	3M_黑色排線 .050" 28AWG 40P (100Ft/R)	40P	100Ft/R	-20°C to +105°C	28	Style2651/E42769	300V	1.27



- 28 AWG wire on .050 inch centers permits mass termination to a broad line of IDC connectors
- Ground plane construction for increased signal density or improved transmission properties
- Stranded wire provides flexibility and extended product life
- Ground plane can be stripped by hand for easy termination
- The drain wire terminates the ground plane into the first connector contact

3M

Part No.	Product No.	製造廠商	說明	Num. Of Cores	Length/Reel	Temp°C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
45450	C3476/10	3M	3M_灰色排線 .050" 28AWG 10P (100Ft/R)	10P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45455	C3476/14	3M	3M_灰色排線 .050" 28AWG 10P (100Ft/R)	14P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45456	C3476/15	3M	3M_灰色排線 .050" 28AWG 15P (100Ft/R)	15P	100Ft/R	-20°C to +105°C	28	AWM 2682/E42769	300V	1.27
45457	C3476/16	3M	3M_灰色排線 .050" 28AWG 16P (100Ft/R)	16P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45458	C3476/20	3M	3M_灰色排線 .050" 28AWG 20P (100Ft/R)	20P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45459	C3476/24	3M	3M_灰色排線 .050" 28AWG 24P (100Ft/R)	24P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45460	C3476/25	3M	3M_灰色排線 .050" 28AWG 25P (100Ft/R)	25P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45461	C3476/26	3M	3M_灰色排線 .050" 28AWG 26P (100Ft/R)	26P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45462	C3476/34	3M	3M_灰色排線 .050" 28AWG 34P (100Ft/R)	34P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45463	C3476/37	3M	3M_灰色排線 .050" 28AWG 37P (100Ft/R)	37P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45464	C3476/40	3M	3M_灰色排線 .050" 28AWG 40P (100Ft/R)	40P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45465	C3476/50	3M	3M_灰色排線 .050" 28AWG 50P (100Ft/R)	50P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45466	C3476/60	3M	3M_灰色排線 .050" 28AWG 60P (100Ft/R)	60P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27
45467	C3476/64	3M	3M_灰色排線 .050" 28AWG 64P (100Ft/R)	64P	100Ft/R	-20°C to +105°C	28	Style2682/E42769	300V	1.27

