




3M_28-30AWG 灰色扁平排線

詳細產品規格請點擊www.100y.com.tw



- .025 inch wire spacing increases signal density
- TPE insulation provides excellent transmission properties
- 30 AWG stranded conductors on .025 inch wire spacing is designed for mass termination and flexibility
- Meets the SCSI-3 characteristic impedance requirements



| Part No. | Product No. | 製造廠商 | 說明 | Num. Of Cores | Length/Reel | Temp°C | Cond. Size AWG | UL Style/Flame Class | Volt. | Pitch(mm) |
|----------|-------------|------|---------------------|---------------|-------------|-----------------|----------------|----------------------|-------|-----------|
| 43350 | C3756/100 | 3M | 3M_灰色排線 .025" C3756 | 100 | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 45033 | C3756/20 | 3M | 3M_灰色排線 .025" C3756 | 20P | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150v | 0.635 |
| 45037 | C3756/26 | 3M | 3M_灰色排線 .025" C3756 | 26P | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 43334 | C3756/36 | 3M | 3M_灰色排線 .025" C3756 | 36p | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 43335 | C3756/40 | 3M | 3M_灰色排線 .025" C3756 | 40P | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 43336 | C3756/50 | 3M | 3M_灰色排線 .025" C3756 | 50 | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 43337 | C3756/60 | 3M | 3M_灰色排線 .025" C3756 | 60 | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 43338 | C3756/68 | 3M | 3M_灰色排線 .025" C3756 | 68P | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 43339 | C3756/80 | 3M | 3M_灰色排線 .025" C3756 | 80 | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |
| 45039 | C3756/34 | 3M | 3M_灰色排線 .025" C3756 | 34P | 100Ft/R | -40°C to +105°C | 30 | Style20297/E42769 | 150V | 0.635 |

3M_28-30AWG 彩色排線

詳細產品規格請點擊www.100y.com.tw



- Wires are color coded for easy identification
- Twist and flat repeat has variable length option
- Can be mass terminated to a broad line of IDC connectors
- Provides reduced crosstalk in balanced drive applications
- 28 AWG stranded wire provides flexibility and extended product life
- 10 color repeat



| Part No. | Product No. | 製造廠商 | 說明 | Num. Of Cores | Length/Reel | Temp°C | Cond. Size AWG | UL Style/Flame Class | Volt. | Pitch(mm) |
|----------|-------------|------|-------------------|---------------|-------------|-------------------------|----------------|----------------------|------------------|-----------|
| 25782 | 1700/26 | 3M | 3M_彩色排線 | 26P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | 20462 | UL:300V CSA:150V | 1.27 |
| 45516 | C1700/10 | 3M | 3M_彩色排線 28AWG 10P | 10P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45517 | C1700/14 | 3M | 3M_彩色排線 28AWG 14P | 14P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45518 | C1700/16 | 3M | 3M_彩色排線 28AWG 16P | 16P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45531 | C1700/20 | 3M | 3M_彩色排線 28AWG 20P | 20P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45532 | C1700/26 | 3M | 3M_彩色排線 28AWG 26P | 26P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45533 | C1700/34 | 3M | 3M_彩色排線 28AWG 34P | 34P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45535 | C1700/36 | 3M | 3M_彩色排線 28AWG 36P | 36P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45537 | C1700/40 | 3M | 3M_彩色排線 28AWG 40P | 40P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45538 | C1700/50 | 3M | 3M_彩色排線 28AWG 50P | 50P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45539 | C1700/60 | 3M | 3M_彩色排線 28AWG 60P | 60P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |
| 45541 | C1700/64 | 3M | 3M_彩色排線 28AWG 64P | 64P | 100FT/R | UL-20+105°C CSA-20+80°C | 28 | E42769/20462 | UL:300V CSA:150V | 1.27 |



- 28AWG wire on .050 inch centers permits mass termination to a broad line of IDC connectors
- Stranded wire provides flexibility and extended product life
- Zippable for branching or discrete termination
- Color coded for wire identification
- RoHS Compliant



| Part No. | Product No. | 製造廠商 | 說明 | Num. Of Cores | Length/Reel | Temp°C | Cond. Size AWG | UL Style/Flame Class | Volt. | Pitch(mm) |
|----------|-------------|------|-------------------|---------------|-------------|-------------------------|----------------|-----------------------|------------------|-----------|
| 28637 | 3302/10 | 3M | 3M_28AWG 彩色排線 | 10P | 100Ft/R | -20°C to +105°C | 28 | UL E42769/Style 20462 | 300V | 1.27 |
| 41011 | 3302/14 | 3M | 3M_28AWG 彩色排線 | 14P | 100Ft/R | -20°C to +105°C | 28 | UL E42769/Style 20462 | 300V | 1.27 |
| 28638 | 3302/26 | 3M | 3M_28AWG 彩色排線 | 26P | 100Ft/R | -20°C to +105°C | 28 | UL E42769/Style 20462 | 300V | 1.27 |
| 28639 | 3302/34 | 3M | 3M_28AWG 彩色排線 | 34P | 100Ft/R | -20°C to +105°C | 28 | UL E42769/Style 20462 | 300V | 1.27 |
| 41012 | 3302/60 | 3M | 3M_28AWG 彩色排線 | 60P | 100Ft/R | -20°C to +105°C | 28 | UL E42769/Style 20462 | 300V | 1.27 |
| 45543 | C3302/09 | 3M | 3M_彩色排線 28AWG 09P | 09P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45562 | C3302/15 | 3M | 3M_彩色排線 28AWG 15P | 15P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45563 | C3302/16 | 3M | 3M_彩色排線 28AWG 16P | 16P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45567 | C3302/18 | 3M | 3M_彩色排線 28AWG 18P | 18P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45568 | C3302/20 | 3M | 3M_彩色排線 28AWG 20P | 20P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45570 | C3302/24 | 3M | 3M_彩色排線 28AWG 24P | 24P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45572 | C3302/25 | 3M | 3M_彩色排線 28AWG 25P | 25P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45573 | C3302/30 | 3M | 3M_彩色排線 28AWG 30P | 30P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45575 | C3302/36 | 3M | 3M_彩色排線 28AWG 36P | 36P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45577 | C3302/37 | 3M | 3M_彩色排線 28AWG 37P | 37P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45579 | C3302/40 | 3M | 3M_彩色排線 28AWG 40P | 40P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45580 | C3302/50 | 3M | 3M_彩色排線 28AWG 50P | 50P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |
| 45581 | C3302/64 | 3M | 3M_彩色排線 28AWG 64P | 64P | 100Ft/R | UL-20+105°C CSA-20+80°C | 28 | UL E42769/Style 20462 | UL:300V CSA:150V | 1.27 |

