




3M_26AWG 灰色扁平排線

詳細產品規格-請點擊www.100y.com.tw

- 26 AWG wire allows for higher power levels
- Stranded wire provides flexibility and extended product life
- .050 inch centers permits mass termination to a broad line of IDC connectors
- Zippable for branching or discrete termination
- Available in Gray and Black
- RoHS compliant

3M

Part No.	Product No.	製造廠商	說明	Num. Of Cores	Length/Reel	Temp°C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
43366	C3801/09	3M	3M 灰色排線 .050" C3801	09P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43367	C3801/10	3M	3M 灰色排線 .050" C3801	10P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43369	C3801/14	3M	3M 灰色排線 .050" C3801	14P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43380	C3801/15	3M	3M 灰色排線 .050" C3801	15P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43381	C3801/16	3M	3M 灰色排線 .050" C3801	16P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43382	C3801/18	3M	3M 灰色排線 .050" C3801	18P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43383	C3801/20	3M	3M 灰色排線 .050" C3801	20P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43384	C3801/24	3M	3M 灰色排線 .050" C3801	24P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43385	C3801/25	3M	3M 灰色排線 .050" C3801	25P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43386	C3801/26	3M	3M 灰色排線 .050" C3801	26P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
43387	C3801/30	3M	3M 灰色排線 .050" C3801	30P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
45078	C3801/37	3M	3M 灰色排線 .050" C3801	37P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
45079	C3801/40	3M	3M 灰色排線 .050" C3801	40P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
45080	C3801/44	3M	3M 灰色排線 .050" C3801	44P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
45081	C3801/50	3M	3M 灰色排線 .050" C3801	50P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
45082	C3801/60	3M	3M 灰色排線 .050" C3801	60P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27
45083	C3801/64	3M	3M 灰色排線 .050" C3801	64P	100Ft/R	-20°C to +105°C	26	Style2651/E42769	300V	1.27

Temp-Flex_24-28AWG 耐高溫排線

詳細產品規格-請點擊www.100y.com.tw

- Multi-flex cable is designed for harsh environments. To achieve increased flexibility in a fluoropolymer construction, 19 strand alloy conductors are used with self-lubricating FEP insulation material.

TEMP-FLEX

Part No.	Product No.	製造廠商	說明	Num. Of Cores	Ft./Reel	Temp. °C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
51888	F2607S-14-050-4	Temp-Flex	Temp-Flex_耐高溫 FEP 排線-Silver Plated Copper	14P	100Ft/30.5M	200°C	26AWG	20424	300V	0.05"
62431	F2607S-16-050-4	Temp-Flex	Temp-Flex_耐高溫 FEP 排線-Silver Plated Copper	16P	100Ft/30.5M	200°C	26AWG	20424	300V	0.05"
62432	F2607S-20-050-4	Temp-Flex	Temp-Flex_耐高溫 FEP 排線-Silver Plated Copper	20P	100Ft/30.5M	200°C	26AWG	20424	300V	0.05"
62433	F2607S-26-050-4	Temp-Flex	Temp-Flex_耐高溫 FEP 排線-Silver Plated Copper	26P	100Ft/30.5M	200°C	26AWG	20424	300V	0.05"
62434	F2607S-40-050-4	Temp-Flex	Temp-Flex_耐高溫 FEP 排線-Silver Plated Copper	40P	100Ft/30.5M	200°C	26AWG	20424	300V	0.05"



- Multi-flex cable is designed for harsh environments. To achieve increased flexibility in a fluoropolymer construction, 19 strand alloy conductors are used with self-lubricating FEP insulation material.

TEMP-FLEX

Part No.	Product No.	製造廠商	說明	Num. Of Cores	Ft./Reel	Temp. °C	Cond. Size AWG	UL Style/Flame Class	Volt.	Pitch(mm)
57991	F2807S-10-0394-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	10P	100Ft/R	200°C	28AWG	20424	300V	0.0394"
30436	F2807S-10-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	10P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
54258	F2807S-10-100-5	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	10P	100Ft/30.5M	200°C	28AWG		300V	2.54mm
54259	F2807S-14-100-5	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	14P		200°C	28AWG		300V	2.54mm
48583	F2807S-16-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	16P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
23651	F2807S-20-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	20P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
28390	F2807S-26-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	26P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
38156	F2807S-30-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	30P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
17306	F2807S-34-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	34P	100Ft/30.5M	200°C	/28AWG	#20424	300V	0.05"
54256	F2807S-4-100-5	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	4P	100Ft/30.5M	200°C	28AWG		300V	2.54mm
16800	F2807S-40-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	40P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
57990	F2807S-44-0394-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	44P	100Ft/R	200°C	28AWG	20424	300V	0.0394"
30439	F2807S-50-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	50P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
54257	F2807S-6-100-5	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	6P	100Ft/30.5M	200°C	28AWG		300V	2.54mm
30441	F2807S-60-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	60P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
55726	F2807S-64-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	64P	100Ft/R	200°C	28AWG	20424	300V	0.05"
55727	F2807S-68-050-55	Temp-Flex	耐高溫 FEP 排線-Silver Plated Copper	68P	100Ft/R	200°C	28AWG	20424	300V	0.05"

● 假如您需要適合特殊用途的產品或更詳細的技術資料，我們的業務專員將會透過電話，傳真，E-mail,幫助您



電話：台灣：886-3-5753170
 傳真：台灣：886-3-5753172
 郵箱：台灣：sale@100y.com.tw

深圳：86-755-83298787
 深圳：86-755-83640655
 深圳：100y@vip.163.com

上海：86-21-34970699
 上海：86-21-64605107
 上海：100y-1@vip.163.com