



Belden_同軸電纜線

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


29 AWG solid .011" silver-coated copper-covered steel conductor, TFE Teflon® insulation, copper-tin composite shield(100% coverage) unjacketed



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.	Temp.
60061	Belden 1672A	Belden	Belden_75Ohm 同軸電纜線	1672A Coax Cable	500Ft/捲	29AWG	19.5pF/Ft	75Ω	200° C



29 AWG solid .011" silver-coated copper-covered steel conductor, TFE Teflon® insulation, copper-tin composite shield(100% coverage), PVC jacket



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.	Temp.
60062	Belden 1672J	Belden	Belden_75Ohm 同軸電纜線	1672J Coax Cable	500Ft/捲	29AWG	19.5pF/Ft	75Ω	105° C



18 AWG solid bare copper-covered steel conductor, foam polyethylene insulation, Duobound® IV Quad Shield(100% coverage), PVC Jacket



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.	Temp.
54486	Belden 3092A	Belden	Belden_ControlNet 數據電纜	3092	152m	18	16.2pF/ft	75Ω	-30°C to 75°C



RG-174/U Type 50 ohm coax, 26 AWG stranded bare copper-covered steel, polyethylene core, 90% tinned copper braid



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.
2975	Belden 8216	Belden	Belden RG-174/U 高頻細同軸電纜線	8216	1000Ft(305M)/R	26	101pF/m	50Ω



50 ohm M17/169-00001(RG-178B/U)coax, 30AWG stranded(7x38) .012" silver-coated copper-covered steel, TFE core, braid shield 96% coverage, FEP jacketed



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.	Temp.	重量
2986	Belden 83265	Belden	Belden_RG-178B/U 同軸電纜線	83265	1000Ft(305M)/R	30	95.8pF/m	50Ω	200° C	2.73KG



18 AWG solid .037" silver-coated copper-covered steel conductor, plenum, TFE Teflon® insulation, double silver-coated copper braid shield(96% coverage), FEP jacket



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.	Temp.
49796	RG-142B/U Belden 83242	Belden	Belden_RG-142B/U 同軸電纜線	83242	1000Ft/R	19	29pF/ft	50Ω	200° C



30 AWG (7x38) silver coated copper covered steel, TFE insulated, shielded, FEP jacketed, RG-179 high Temp. Coaxial cable, MIL-C-17 M17/94-RG179



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.	Temp.
40459	RG-179/U Belden 83264	Belden	Belden_RG-179/U 同軸電纜線	83264	1000Ft(305M)/R	30	19.5 pF/ft	75 Ohms	200° C



95ohm 30 AWG Stranded(7x38) .012" silver-plated copper-covered steel conductor, TFE Teflon® insulation, silver-plated copper braid shield(91% coverage),FEP jacket



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.	Temp.
54166	RG-180/U Belden 83266	Belden	Belden_RG-180B/U 同軸電纜線	MIL-C-17G QPL Cable(83266)	1000Ft(305M)/R	30AWG	15.0pF/Ft , 49.2pF/m	95 Ω	200° C



RG-58A/U Type 53.5 ohm coax, 20 AWG stranded(19x32) tin copper, foam polyethylene core, 96% tinned copper braid



Part No.	Product No.	製造廠商	說明	Trade No.	Lengths/Reel	AWG	Nom. Cap.	Nom. Imp.
8592	RG-58A/U Belden 8219	Belden	Belden_區域網路-同軸電纜線	8219	1000Ft(305M)/R	20	86.9pF/m	53.5Ω

