




UL1061 PVC電子線 UL1061 (絞線)半硬質聚氯乙烯絕緣電子線

詳細產品規格-請點擊www.100y.com.tw



- Solid or stranded, tinned or bare copper conductor, 30-16AWG
- Color-coded semi-rigid PVC insulation
- Rated temperature: 80°C
- Rated voltage: 300V
- Uniform thickness of wire to ensure easy stripping and cutting
- Passes UL VW-1 & CSA Ft1 vertical flame test

Part No.	Product No.	說明	Length/Reel	AWG	Color	No./mm 線數/mm
52105	1061-26-紅	多芯電子線 UL1061-26AWG 紅色(兩端鍍錫)	條/90mm	26	紅色	7/0.160
52106	1061-26-紅	多芯電子線 UL1061-26AWG 紅色(兩端鍍錫)	條/300mm	26	紅色	7/0.160
52103	1061-26-黑	多芯電子線 UL1061-26AWG 黑色(兩端鍍錫)	條/90mm	26	黑色	7/0.160
52104	1061-26-黑	多芯電子線 UL1061-26AWG 黑色(兩端鍍錫)	條/300mm	26	黑色	7/0.160



- Solid or stranded, tinned or bare copper conductor, 30-16AWG
- Color-coded semi-rigid PVC insulation
- Rated temperature: 80°C
- Rated voltage: 300V
- Uniform thickness of wire to ensure easy stripping and cutting
- Passes UL VW-1 & CSA Ft1 vertical flame test

Part No.	Product No.	說明	Length/Reel	AWG	Color	No./mm 線數/mm
32005	1061-26-紅	多芯電子線 UL1061-26AWG 紅色(2000Ft/R)	610M/R	26	紅色	7/0.160
32007	1061-26-棕	多芯電子線 UL1061-26AWG 棕色(2000Ft/R)	610M/R	26	棕色	7/0.160
32006	1061-26-黑	多芯電子線 UL1061-26AWG 黑色(2000Ft/R)	610M/R	26	黑色	7/0.160

UL1028 PVC電子線 UL1028 (絞線)聚氯乙烯絕緣電子線

詳細產品規格-請點擊www.100y.com.tw



- Stranded, tinned or bare copper conductor
- Color-coded PVC insulation
- UL1028: Rated temp. 105°C, Rated voltage: 600 Volts
- Uniform thickness of wire to ensure easy stripping and cutting
- Resistant to acids, oils, alkalis, moisture and fungus
- Passes UL VW-1 vertical flame test

Part No.	Product No.	說明	線號 AWG	顏色	耐溫 °C	電壓(Volt.)	長度(M)/捲	導體線數/線徑(mm)
41389	UL1028-22AWG-Red	Stranded, tinned copper conductor .PVC insulation.	#22	紅色	105°C	600v	(305M/R)	17/0.160

UL1015 PVC電子線 UL1015 (單條)聚氯乙烯絕緣電子線

詳細產品規格-請點擊www.100y.com.tw



- Solid or stranded, tinned or bare copper conductor 28-4/0AWG
- Color-coded PVC insulation
- Rated temperature: 105°C
- Rated voltage: 600V
- Uniform thickness of wire to ensure easy stripping and cutting
- Resistant to acids, oils, alkalis, moisture and fungus
- Passed UL VW-1 & CSA FT1 vertical flame test

Part No.	Product No.	說明	No./mm 線數/mm	Length/Reel	AWG	Color
32173	1015-16-黑	UL1015 單芯電子線	1C/1.29	1000Ft/R	16	黑色

UL1015 (絞線)聚氯乙烯絕緣電子線

詳細產品規格-請點擊www.100y.com.tw



- 參考規範：CNS-3199
- 電壓：300V以下/60°C

Part No.	Product No.	說明	No./mm 線數/mm	Length/Reel	AWG	Color
14649	MPVC1218106261	PVC 花線	12/0.18	3280Ft/R	20	藍色

