



其他_SMD電解電容

詳細產品規格請點擊www.100y.com.tw



Type AEB capacitors are it for high voltage applications like input bus capacitors in board mounted miniature AC/DC supplies. The AEB's low impedance in rating up to 450Vdc, and long life, make it ideal for power supply input and other high voltage applications. The vertical, cylindrical cases make easy automatic mounting and reflow soldering.

+105°C, Up to 5000 Hour Load Life
Capacitance Range: 2.2µF to 100µF
Voltage Range: 160Vdc to 450Vdc

Part No.	Product No.	製造廠商	說明	Type	Capacitance (uF)	Tolerance(±)	Voltage (Vdc)	Temp. range°C	Size Dia.*L.(mm)
62538	AEB475M2GK32T-F	CDE	SMD E/C 電解電容	AEB	10uF	±20%	400V	105°C	10*17.5



STG 85°C表面粘著標準型制品系列
Vertical chip type miniaturized for 5.5mm

技術參數

工作溫度範圍: -40°C to +85°C
 電容容差: ±20% (at 120Hz, 20°C)

Part No.	Product No.	說明	Type	Capacitance (uF)	Tolerance(±)	Voltage (Vdc)	Temp. range°C	Size Dia.*L.(mm)
11903	GV-E/C-1000UF/10V	SMD 鋁質電解電容	GV	1000uF	±20	10V	85°C	10*10.2



- Chip type higher capacitance in larger case size
- Designed for surface mounting on high density PC board
- Applicable to automatic insertion machine using carrier tape
- Complied to the RoHS directive

技術參數

工作溫度範圍: -40°C to +85°C
 電容容差: ±20% (at 120Hz, 20°C)

Part No.	Product No.	說明	Capacitance (uF)	Tolerance(±)	Voltage (Vdc)	Temp. range°C	Size Dia.*L.(mm)
26999	SC1H106M05005VR100	SAMWHA-SMD 電解電容	10uF	±20%	50V	85°C	Φ5*5.4



Part No.	Product No.	製造廠商	說明	Type	Capacitance (uF)	Tolerance(±)	Voltage (Vdc)	Temp. range°C	Size Dia.*L.(mm)
45072	STK100010G-G	JACKCON	SMD 鋁質電解電容	STK	1000uF	±20%	10V	105°C	10*10.2
45069	STK10016D1-G	JACKCON	SMD 鋁質電解電容	STK	100uF	±20%	16V	105°C	6.3*5.4
45070	STK10050F-L	JACKCON	SMD 鋁質電解電容	STK	100uF	±20%	50V	105°C	8*10.2
40880	STK1050D1-S	JACKCON	SMD 鋁質電解電容	STK	10uF	±20%	50V	105°C	6.3*5.4
45068	STK4750D1-S	JACKCON	SMD 鋁質電解電容	STK	47uF	±20%	50V	105°C	6.3*7.7



Part No.	Product No.	說明	Capacitance (uF)	Tolerance(±)	Voltage (Vdc)	Size Dia.*L.(mm)
35186	GVV106M050S0ANE010	SMD E/C 電解電容	4.7uF	±20%	400V	10D*16.5L*12H mm

ELNA_電解電容

詳細產品規格請點擊www.100y.com.tw

ELNA-徑向鋁電容



- ELNA SILMIC II RFS系列Silk fiber迷你鋁電解電容, 音響用
- 使用Oxygen-free copper無酸素銅導線, 極低的失真

技術參數

工作溫度範圍: -40°C to +85°C
 電容容差: ±20% (at 120Hz, 20°C)



Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range	Size Dia.*L.(mm)
63187	RFS-10V101M	ELNA	ELNA_SILMIC II RFS 100uF/10V 音頻發燒級電容 For Audio	RFS(SILMIC II)	100uF	±20%	10V	85°C	8*11.5mm
63123	RFS-10V470ME3	ELNA	ELNA_SILMIC II RFS 47uF/10V 音頻發燒級電容 For Audio	RFS(SILMIC II)	47uF	±20%	10V	85°C	5*11mm
63119	RFS-16V100ME3	ELNA	ELNA_SILMIC II RFS 10uF/16V 音頻發燒級電容 For Audio	RFS(SILMIC II)	10uF	±20%	16V	85°C	5*11mm
63120	RFS-16V220ME3	ELNA	ELNA_SILMIC II RFS 22uF/16V 音頻發燒級電容 For Audio	RFS(SILMIC II)	22uF	±20%	16V	85°C	5*11mm
62592	RFS-16V222MK8	ELNA	ELNA_SILMIC II RFS 2200uF 16V 音頻發燒級電容 For Audio	RFS(SILMIC II)	2200uF	±20%	16V	85°C	18*35.5
63121	RFS-16V330MF3	ELNA	ELNA_SILMIC II RFS 33uF/16V 音頻發燒級電容 For Audio	RFS(SILMIC II)	33uF	±20%	16V	85°C	6.3*11mm
63122	RFS-16V470MG3	ELNA	ELNA_SILMIC II RFS 47uF/16V 音頻發燒級電容 For Audio	RFS(SILMIC II)	47uF	±20%	16V	85°C	8*11.5mm
61249	RFS-25V101MH4	ELNA	ELNA_SILMIC II RFS 100uF 25V 音頻發燒級電容 For Audio	RFS(SILMIC II)	100uF	±20%	25V	85°C	10*16mm
62222	RFS-35V100ME3#5	ELNA	ELNA_SILMIC II RFS 10uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	10uF	±20%	35V	85°C	5*11mm
62226	RFS-35V101MH5	ELNA	ELNA_SILMIC II RFS 100uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	100uF	±20%	35V	85°C	10*20mm
62230	RFS-35V102MK8	ELNA	ELNA_SILMIC II RFS 1000uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	1000uF	±20%	35V	85°C	18*35.5mm
62223	RFS-35V220MG3#5	ELNA	ELNA_SILMIC II RFS 22uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	22uF	±20%	35V	85°C	8*11.5mm
62227	RFS-35V221MI6	ELNA	ELNA_SILMIC II RFS 220uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	220uF	±20%	35V	85°C	12.5*25mm
62224	RFS-35V330MH3	ELNA	ELNA_SILMIC II RFS 33uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	33uF	±20%	35V	85°C	10*12.5mm
62228	RFS-35V331MJ6	ELNA	ELNA_SILMIC II RFS 330uF/35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	330uF	±20%	35V	85°C	16*25mm
62225	RFS-35V470MH3	ELNA	ELNA_SILMIC II RFS 47uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	47uF	±20%	35V	85°C	10*12.5mm
62229	RFS-35V471MJ7	ELNA	ELNA_SILMIC II RFS 330uF/35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	470uF	±20%	35V	85°C	16*31.5mm
62221	RFS-35V4R7ME3#5	ELNA	ELNA_SILMIC II RFS 4.7uF 35V 音頻發燒級電容 For Audio	RFS(SILMIC II)	4.7uF	±20%	35V	85°C	5*11mm
63146	RFS-50V470MH4	ELNA	ELNA_SILMIC II RFS 47uF/50V 音頻發燒級電容 For Audio	RFS(SILMIC II)	47uF	±20%	50V	85°C	10*16mm
63185	RFS-50V4R7ME3	ELNA	ELNA_SILMIC II RFS 4.7uF/50V 音頻發燒級電容 For Audio	RFS(SILMIC II)	4.7uF	±20%	50V	85°C	5*11mm

