



Vishay Bccomponents_臥式 鋁電容

詳細產品規格-請點擊www.100y.com.tw



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Axial leads, cylindrical aluminum case, insulated with a blue sleeve
- Mounting ring version not available in insulated form
- Taped versions up to case $\Phi 15\text{mm} \times 30\text{mm}$ available for automatic insertion
- Charge and discharge proof
- Long useful life: up to 10 000 hours to 15 000 hours at 85°C, high reliability
- Compliant to RoHS directive 2002/95/EC

VISHAY

Part No.	Product No.	製造廠商	說明	Capacitance(μF)	Tolerance(\pm)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)	Type
62732	132-10uF/100V	BC components	Bccomponents - 10uF/100VDC Long-Life.軸向鋁電容	10uF	-10~+50%	100VDC	85°C	8*18mm	132
61828	132-2200uF/25V	BC components	Bccomponents - 2200uF/25V Long-Life.軸向鋁電容	2200uF	-10~+50%	25VDC	85°C	21*38mm	132
62733	132-220uF/16V	BC components	BCcomponents - 220uF/16Vdc Long-Life.軸向鋁電容	220uF	-10~+50%	16VDC	85°C	10*18mm	132
63109	132-22uF/100V	BC components	BCcomponents - 22uF/100Vdc Long-Life.軸向鋁電容	22uF	-10+50%	100Vdc	85°C	10*18mm	132



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Axial leads, cylindrical aluminum case, insulated with a blue sleeve(case $\Phi 6.3 \times 12.7$ and $7.7 \times 12.7\text{mm}$ are moulded with flame retardant plastic material)
- Mounting ring version not available in insulated form
- Taped version up to case $\Phi 15 \times 30\text{mm}$ available for automatic insertion
- Charge and discharge proof
- Long useful life:2000 to 10 000 hours at 105°C, high reliability
- High ripple current capability
- Miniaturized, high CV-product per unit volume
- Lead(Pb)-free version are RoHS compliant

VISHAY

Part No.	Product No.	製造廠商	說明	Capacitance(μF)	Tolerance(\pm)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)	Type
61158	138-1000uF/50V	BC components	BCcomponents -138 1000uF/50V 軸向鋁電容	1000uF	$\pm 20\%$	50VDC	105°C	18*30mm	138



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Axial leads, cylindrical aluminum case, insulated with a blue sleeve
- Mounting ring version not available in insulated form
- Taped version up to case $\Phi 15 \times 30\text{mm}$ available for automatic insertion
- Charge and discharge proof
- Miniaturized, high CV-product per unit volume
- Compliant to RoHS directive 2002/95/EC

VISHAY

Part No.	Product No.	製造廠商	說明	Capacitance(μF)	Tolerance(\pm)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)	Type
64501	MAL202115472E3	VISHAY	ASM 021 臥式鋁電容	4700uF	$\pm 20\%$	16V	105°C	$\varphi 18 \times 30\text{mm}$	ASM 021

Vishay Bccomponents_ Snap-In鋁電容

詳細產品規格-請點擊www.100y.com.tw



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Large types, minimized dimensions, cylindrical aluminum case, insulated with a blue sleeve
- Pressure relief on the top of the aluminum case
- Charge and discharge proof
- Long useful life:12 000 hours at 85°C
- High ripple current capability
- Keyed polarity version available

VISHAY

Part No.	Product No.	製造廠商	說明	Capacitance(μF)	Tolerance(\pm)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)	Type
63229	056-1500uF/63V	BC components	BCcomponents_1500uF/63V 長壽命鋁電容	1500uF	$\pm 20\%$	63V	85°C	22*30mm	056 PSM-SI
63887	056-2200uF/63V	BC components	BCcomponents_2200uF/63V 長壽命鋁電容	2200uF	$\pm 20\%$	63V	85°C	25*30mm	056 PSM-SI
64523	056-6800uF/40V	BC components	BCcomponents_2200uF 40V 長壽命鋁電容	2200uF	$\pm 20\%$	40V	85°C	30*30mm	056 PSM-SI
63538	057-330uF/400V	BC components	Bccomponents_330uF/400V 長壽命鋁電容	330uF	$\pm 20\%$	400V	85°C	30*50mm	057 PSM-SI



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Large types, minimized dimensions, cylindrical aluminum case, insulated with a blue sleeve
- Very long useful life: up to 10 000 hours at 105°C
- Extended temperature range:105°C
- Low ESR, high ripple current capability
- Keyed polarity version available

VISHAY

Part No.	Product No.	製造廠商	說明	Capacitance(μF)	Tolerance(\pm)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)	Type
23559	058-10000uF/40V	BC components	BCcomponents_10000uF/40V 長壽命鋁電容	10000uF	$\pm 20\%$	40V	105°C	30*50mm	058 PLL-SI
61184	058-2200uF/100V	BC components	BCcomponents_2200uF/100V 長壽命鋁電容	2200uF	$\pm 20\%$	100V	105°C	35*40mm	058 PLL-SI

