

Vishay Bcomponents_
Snap-In鋁電容詳細產品規格請點擊www.100y.com.tw

- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Large types, very small dimensions, cylindrical aluminum case, insulated with a blue sleeve
- Low ESR, high ripple current capability
- Useful life: 5000 hours at 105°C
- Keyed polarity snap-in version available

VISHAY

Part No.	Product No.	製造廠商	說明	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)	Type
61186	159-220uF/450V	BC components	BComponents_220uF/450V 超長壽命鋁電容	220uF	±20%	450V	105°C	30*40mm	159 PUL-SI
63544	159-47uF/400V	BC components	Bcomponents_47uF/400V 超長壽命鋁電容	47uF	±20%	400V	105°C	22*35mm	159 PUL-SI

Vishay Bcomponents_
徑向鋁電容詳細產品規格請點擊www.100y.com.tw

- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, all-insulated(light blue)
- Natural pitch 2.5mm and 5mm
- Charge and discharge proof
- Miniaturized, high CV-product per unit volume
- Low leakage current, low energy consumption
- Lead(Pb)-free versions are RoHS compliant

VISHAY

Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
23560	013-4.7uF/50V	BC components	Vishay-BCcomponents_4.7uF/50V 電解電容	013 RLC	4.7uF	±20%	50V	85°C	5*11mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, all-insulated(light blue)
- Natural pitch 2.5mm and 5mm
- Charge and discharge proof
- Miniaturized, high CV-product per unit volume
- Reduced leakage current
- Lead(Pb)-free versions are RoHS compliant

VISHAY

Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
64530	036-1uF/63V	BC components	Vishay-BCcomponents_1uF/63V Semi-Professional Aluminum Capacitor	036 RSP	1uF	±20%	63V	85°C	5*11mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, insulated with a blue vinyl sleeve
- Pressure relief for case $\Phi D \geq 6.3\text{mm}$
- Charge and discharge proof
- Miniaturized, high CV-product per unit volume

VISHAY


Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
64368	037-100uF/25V	BC components	Vishay-BCcomponents_100uF/25V 電解電容	037 RSM	100uF	±20%	25V	85°C	6.3*11mm
63212	037-100uF/50V	BC components	Vishay-BCcomponents_100uF/50V 電解電容	037 RSM	100uF	±20%	50V	85°C	8*11.5mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads. Cylindrical aluminum case with pressure relief, insulated with a blue vinyl sleeve
- Charge and discharge proof
- Very long useful life: 3000 to 4000 hours at 105°C, high reliability
- High ripple current capability, low impedance, low ESR
- Lead(Pd)-free versions are RoHS compliant

VISHAY

Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
63215	046-470uF/40V	BC components	Vishay-BCcomponents_470uF/40V (低阻長壽命)音頻發燒電容	046 RSL	470uF	±20%	40V	105°C	12.5*25mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case with pressure relief, insulated with a blue vinyl sleeve
- Charge and discharge proof
- Miniaturized, high CV-product per unit volume
- Very long useful life:3000 hours to 4000 hours at 105°C, high reliability
- Compliant to RoHS directive 2002/95/EC

VISHAY

Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
63227	048-1500uF/50V	BC components	Vishay-BCcomponents_1500uF/50V 長壽命電解電容	048 RML	1500uF	±20%	50V	105°C	18*35mm
63534	048-470uF/50V	BC components	Vishay-Bcomponents_470uF 50V 長壽命電解電容	048 RML	470uF	±20%	50V	105°C	12.5*20mm



電話：台灣：886-3-5753170
傳真：台灣：886-3-5753172
郵箱：台灣：sale@100y.com.tw

深圳：86-755-83298787
深圳：86-755-83640655
深圳：100y@vip.163.com

上海：86-21-34970699
上海：86-21-64605107
上海：100y-1@vip.163.com

5-13