



## Vishay Bcomponents\_徑向 鋁電容

詳細產品規格請點擊[www.100y.com.tw](http://www.100y.com.tw)



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, all-insulated(light blue)
- Natural pitch 2.5 mm and 5mm
- Charge and discharge proof
- Miniaturized, high CV-product per unit volume
- Long useful life:2000 h at 105°C, high reliability
- Lead(Pb)-free versions are RoHS compliant



Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
64531	116-68uF/50V	BC components	Vishay-BCcomponents_68uF 50V 長壽命電解電容	116 RLL	68uF	±20%	50V	105°C	8.2*11mm



- Polarized aluminum electrolytic capacitors, non-solid
- Radial leads, cylindrical aluminum case with pressure relief, insulated with a blue vinyl sleeve
- Charge and discharge proof
- Long useful life:1500 to 2500 hours at 105°C
- Low ESR, low impedance, high ripple current capability
- 低電阻, 低損失高電流, 高耐壓, 長壽命



Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
23558	135-2200uF/25V	PHILIPS	2200uF/25V 電解電容	135 RLI	2200uF	±20%	25V	105°C	21.11*18.15mm
63885	135-220uF/16V	BC components	Vishay-BCcomponents_220uF/16V(低阻長壽命)音頻電容	135 RLI	220uF	±20%	16V	105°C	8*12mm
63884	135-47uF/63V	BC components	Vishay-BCcomponents_47uF/63V(低阻長壽命)音頻電容	135 RLI	47uF	±20%	63V	105°C	8*12mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case with pressure relief, insulated with a blue vinyl sleeve
- Charge and discharge proof
- Very long useful life:4000 to 10000 hours at 105°C, very high reliability
- Very low impedance or ESR respectively, which is significantly lower than the RLI 135 series
- Excellent ripple current capability



Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
13636	136-220u/63V	BC components	Vishay-BCcomponents_220u/63V(低阻)音頻電容	136 RVI	220uF	±20%	63V	105°C	10*16mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case with pressure relief, insulated with a blue sleeve
- Charge and discharge proof
- Very long useful life:2500 to 4000 h at 125°C, high stability, high reliability
- Extended temperature range up to 125°C
- High ripple current capability
- Lead(Pb)-free versions are RoHS compliant



Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
63228	140-100uF/63V	BC components	Vishay-BCcomponents_100uF/63V 耐高溫電解電容	140 RTM	100uF	±20%	63V	125°C	10*20mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case with pressure relief, insulated with a blue vinyl sleeve
- Charge and discharge proof
- Very long useful life: 4000 to 10 000h at 105°C, high stability, high reliability
- Very low impedance or ESR respectively, at smaller case sizes than the 136 RVI series
- Excellent ripple current capability
- Lead(Pb)-free versions are RoHS compliant



Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
63886	150-1000uF/35V	BC components	Vishay-BCcomponents_1000uF/35V(低阻長壽命)頂級音頻發燒電容	150 RMI	1000uF	±20%	35V	105°C	12.5*25mm
63213	150-2200uF/25V	BC components	Vishay-BCcomponents_2200uF/25V(低阻長壽命)頂級音頻發燒電容	150 RMI	2200uF	±20%	25V	105°C	16*22mm



- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, insulated with a blue vinyl sleeve
- Pressure relief
- Charge and discharge proof
- Miniaturized, ultra high CV-product per unit volume
- Long useful life: 3000 to 4000 h at 105°C, high reliability
- Lead(Pb)-Free versions are RoHS compliant



Part No.	Product No.	製造廠商	說明	Type	Capacitance(uF)	Tolerance(±)	Voltage (Vdc)	Temp. range °C	Size Dia.*L.(mm)
64527	152-22uF/400V	BC components	Vishay-BCcomponents_22uF 400V 長壽命電解電容	152 RMIH	22uF	±20%	400V	105°C	12.5*25mm

