



鋁質電解電容 站立鎖螺絲電解電容

詳細產品規格請點擊www.100y.com.tw



- This is large capacitance product developed for use in power supply, inverter, etc, for industrial equipment
- Although this product is made compact much more than the conventional ones, its rated ripple current is on the same level as that of the conventional one




Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)	Type
50722	1HSL104MD11	TK	10000uF/50V 鎖螺絲電解電容	10000uF	50V	63.5*115mm	85°C	±20%	SL
19505	1JSL333MC8	TK	33000uF/63V 鎖螺絲電解電容	33000uF	63V	51*80mm	85°C	±20%	SL
19503	1KSL223MC8	TK	22000uF/80V 鎖螺絲電解電容	22000uF	80V	51*80mm	85°C	±20%	SL
32079	1KSL473MD10	TK	47000uF/80V 鎖螺絲電解電容	47000uF	80V	63.5*100mm	85°C	±20%	SL
47924	2ASL103MC6	TK	10000uF/100V 鎖螺絲電解電容	10000uF	100V	51*63mm	85°C	±20%	SL
56522	2DSL102MA5	TK	1000uF/200V 鎖螺絲電解電容	1000uF	200V	35*58mm	85°C	±20%	SL
24681	2DSL153ME11	TK	15000uF/200V 鎖螺絲電解電容	15000uF	200V	76*115mm	85°C	±20%	SL
56521	2DSL472MC9	TK	4700uF/200V 鎖螺絲電解電容	4700uF	200V	51*90mm	85°C	±20%	SL
53821	2GSL472MD13	TK	4700uF/400V 鎖螺絲電解電容	4700uF	400V	63.5*130mm	85°C	±20%	SL
29123	2VSL222MC9	TK	2200uF/350V 鎖螺絲電解電容	2200uF	350V	51*90mm	85°C	±20%	SL
16731	2VSL472ME9	TK	4700uF/350V 鎖螺絲電解電容	4700uF	350V	76*90mm	85°C	±20%	SL



- CASE: aluminum made
- TERMINALS: screw
- SEALING: hermetic by beading on an EPR gasket, housed on a resin cover
- PRESSURE RELEASE VENT: made in silicone-rubber
- SLEEVE: self-extinguishing thermoshrinkable sleeve

Part No.	Product No.	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)	Type
62363	AYUX-HR103X250DF1	Itelcond_10000uF 250V 鎖螺絲電解電容(Mounting Stud)	10,000uF	250V	76*147mm	85°C	±20%	AY



- General technical data: VDE 0560, IEC 071, EN61071
- Application class(DIN 40040): GPD/LS
- Max permissible ambient temperature: +70°C



Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)
64157	C44AHGP5330ZA0J	KEMET	鋁質電解電容	33uF	600VDC	ψ55*101mm	-40 to +85°C	±5%



- Polarized aluminum electrolytic capacitors, non-solid
- Large types, minimized dimensions, cylindrical aluminum case, insulated with a blue sleeve
- Also available in bolt version(PEC-STB)
- Pressure relief in the sealing
- Charge and discharge proof
- Long useful life: 12 000 hours at 85°C
- High ripple current capability
- High resistance to shock and vibration achieved by longitudinal rills and special internal construction



Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C
37814	PH-154-689M63	PHILIPS	PHILIPS_站立式高壓電解電容	68000uF	63V	76*118mm	85°C



- Screw terminal type
- Smaller dimensions and large capacity
- Ideal for inverter, computer
- Large allowable ripple current
- Load life fo 2000 hours at 85°C

Part No.	Product No.	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)
51608	PSA-150000uF/25V	DAEWOO/PARTSNIC_150000uF/25V 鎖螺絲電解電容	150000uF	25V	51*120mm	-40°C ~85°C	±20%
56523	PSA-3300uF/250V	DAEWOO/PARTSNIC_3300uF/250V 鎖螺絲電解電容	3300uF	250V	50*100mm	-40°C ~85°C	±20%
51609	PSA-47000uF/50V	DAEWOO/PARTSNIC_47000uF/50V 鎖螺絲電解電容	47000uF	50V	51*90mm	-40°C ~85°C	±20%

