



徑向電解電容



- Endurance: +105°C 1000 to 2000h
- Smaller than Series NHE
- RoHS directive compliant

Panasonic

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)	Type
41734	ECA1JHG102	Panasonic	鋁質電解電容	1000uF	63V	16*25mm	-55 to +105°C	±20%	NHG



- Endurance: 105°C 5000 to 10000h
- High Ripple High Frequency(High Voltage)

Panasonic

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Temp. range°C	Tolerance(±)	Type
41519	EEUEB2C330	Panasonic	高頻電解電容	33uF	160V	105°C	±20%	EB



標準系列，用於一般用途

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)
53945	GR1000M10W0814	STONE	鋁質電解電容器	1000uF	10V	8*14mm	105°C	±20%
19684	GR10M16W0511	STONE	鋁質電解電容器	10uF	16V	5*11	85°C	±20%
53244	GR15000M25W2542	STONE	鋁質電解電容器	15000uF	25V	25*42mm	85°C	±20%
24414	GR220M63W1020	STONE	電解電容	220uF	63V	6.3*12	85°C	±20%
39075	GR470M50W1321	STONE	電解電容	470uF	50V	13*21	85°C	±20%



Part No.	Product No.	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)
24018	GR10016	立式電解電容	10uF	16V	5*11mm	85°C	±20%
24020	GR10025	立式電解電容	10uF	25V	5*11	85°C	±20%
24015	GR10050	立式電解電容	10uF	50V	5*11	85°C	±20%
24019	GR1R050	立式電解電容	1uF	50V	5*11	85°C	±20%
24017	GR2213512	立式電解電容	22uF	35V	8*12	85°C	±20%
42884	GR22016	鋁質電解電容器	22uF	16V	5*11mm	105°C	±20%
44234	GR56125	立式電解電容	560uF	25V	10*17	105°C	±20%



Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)
62832	HR-1000uF/25V	STONE	鋁質電解電容器	1000UF	25V	10*20	105°C	±20%
62834	HR-1000uF/35V	STONE	鋁質電解電容器	1000UF	35V	13*21	105°C	±20%
52549	HR100M400W1840	STONE	電解電容	100uF	400V	18*41	105°C	±20%



- Used in communication equipments. Switching power supply. Etc
- Safety vent construction design

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)	Type
10599	LHK-470uF/160V	LIKET	鋁質電解電容	470uF	160V	18*35	105°C	±20%	LHK



- 超小型產品
- 適用於手提電腦，隨身聽等袖珍型電子設備

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)
15755	H5-100UF/6.3V	Su'scon	鋁質電解電容	100uF	6.3V	5*5	-40°C ~105°C	±20%
40520	H5-3.3uF/50V	Su'scon	鋁質電解電容	3.3uF	50V	4*5	-40°C ~105°C	±20%
15757	H5-4.7uF/50V	Su'scon	鋁質電解電容	4.7uF	50V	4*5	-40°C ~105°C	±20%
15754	H5-47uF/6.3V	Su'scon	鋁質電解電容	100uF	6.3V	5*5	-40°C ~105°C	±20%



- 較低阻抗於高頻範圍
- 較小體積於高紋波電流

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range°C	Tolerance(±)
53506	MG-2200uF/25V	Su'scon	鋁質電解電容器	2200	25	13*26	105°C	±20%

● 假如您需要適合特殊用途的產品或更詳細的技術資料，我們的業務專員將會透過電話，傳真，E-mail,幫助您



電話：台灣：886-3-5753170
傳真：台灣：886-3-5753172
郵箱：台灣：sale@100y.com.tw

深圳：86-755-83298787
深圳：86-755-83640655
深圳：100y@vip.163.com

上海：86-21-34970699
上海：86-21-64605107
上海：100y-1@vip.163.com