



## JACKCON\_小型電解電容

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)

- Used in communication equipments, switching power supply, etc
- Safety vent construction design



Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Voltage (Vdc)	Size Dia.*L.(mm)	Temp. range	Tolerance(±)
39922	EC100025H1017	JACKCON	鋁質電解電容器-無鉛	1000	25	10*17	105°C	±20%
38690	EC100035H1321	JACKCON	鋁質電解電容器-無鉛	1000	35	13*21	105°C	±20%
38692	EC150H511	JACKCON	鋁質電解電容器-無鉛	1	50	5*11	105°C	±20%
40238	EC2200025H2242	JACKCON	鋁質電解電容器-無鉛	22000	25	22*42	105°C	±20%
38684	EC220016H1321	JACKCON	鋁質電解電容器-無鉛	2200	16	13*21	105°C	±20%
32693	EC220025H1321	JACKCON	鋁質電解電容器-無鉛	2200	25	13*21	105°C	±20%
38688	EC220035H1626	JACKCON	鋁質電解電容器-無鉛	2200	35	16*26	105°C	±20%
38687	EC22016H611	JACKCON	鋁質電解電容器-無鉛	220	16	6*11	105°C	±20%
40570	EC22025H811	JACKCON	鋁質電解電容器-無鉛	220	25	8*11	105°C	±20%
38689	EC47016H811	JACKCON	鋁質電解電容器-無鉛	470	16	8*11	105°C	±20%
40569	EC47025H814	JACKCON	鋁質電解電容器-ROHS	470	25	8*14	105°C	±20%
38685	EC4716H511	JACKCON	鋁質電解電容器-無鉛	47	16	5*11	105°C	±20%
62846	LHK220M100V611	JACKCON	鋁質電解電容器-無鉛	220	100V	6*11	105°C	±20%

## CDE\_鋁質電解電容

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)

## CDE/MALLORY\_徑向鋁電容



- Type VPR is a radial leaded aluminum electrolytic capacitors with a 105°C, 2000 hours long life ratings.
- The VPR has 3 optional case styles with a third lead.
- The low ESR rating makes it ideal for output filtering in switching power supplies

## 產品規格

電容範圍：34 to 12,000µF  
 電壓範圍：6.3 to 100Vdc(250Vdc on special request)  
 靜電容量允許誤差：-10%+75%(others on special request)  
 工作溫度範圍：-55°C to +105°C  
 漏洩電流：I<sub>L</sub> = .002CV after 2 minutes @ 25°C  
 C=Capacitance in (µF)  
 V=Rated voltage  
 I=Leakage current in µA

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Voltage (Vdc)	Temp. range°C	Size Dia.*L.(mm)	Type
61714	VPR620U075EIA	CDE	MALLORY_62uF 75V Low ESR 電解電容	62uF	-10%,+75%	75VDC	-40°C ~+105°C	Φ13*26mm	VPR

## CDE/MALLORY\_臥式鋁電容

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)

Type WBR capacitors are the preferred choice for many varied industrial applications because they have high capacitance and extended life characteristics. The rugged construction delivers the high vibration resistance required in industrial applications

## 產品規格

電容範圍：1.0 to 5,000 µF  
 電壓範圍：16 to 450Vdc  
 靜電容量允許誤差：16 to 50Vdc -10+150%, 75 to 350Vdc -10+100%, 450Vdc -10+50%  
 工作溫度範圍：-40°C to +85°C  
 漏洩電流：16-75Vdc≤0.01CV+10µA  
 150-450Vdc≤0.03CV+20µA

CDE

Part No.	Product No.	製造廠商	說明	Type	Capacitance (uF)	Tolerance(±)	Voltage (Vdc)	Temp. range°C	Size Dia.*L.(mm)
62026	WBR2-450A	CDE	CDE_2MFD/450VDC 臥式電解電容	WBR	2uF	-10/+50%	450Vdc	85°C	9*24mm
62364	WBR2000-16A	CDE	CDE_2000MFD/16V 臥式電解電容	WBR	2000uF	-10/+150%	16V	85°C	20*50mm

## CDE/MALLORY\_Snap-In電解電容

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)

The excellent value of Type 380L/LX capacitors finds application in switching power supply input and output circuits and even motor drives where the high surface area of multiple units in parallel approaches the ripple capability of our Type 520C computer-grade capacitor. Type 380LX delivers more capacitance per can size while Type 380L available in the largest case sizes gives lower ESR for the same capacitance. Type 382L and 382LX give the choice of 4 or 5 leads for stable, reverse proof mounting

## 產品規格

工作溫度範圍：-40°C to 85°C up to 300V, -25°C to 85°C≥315V  
 額定電壓：16 Vdc to 500Vdc  
 電容：33µF to 270,000µF±20%

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Rated Volt.	Temp. range	Dia.*L.(mm)	Type
62198	380LX103M063A042	CDE	CDE_10000uF 63V Low ESR 插板式電解電容	10000uF	±20%	50V	85°C	35*40mm	380LX
63151	380LX121M450J022	CDE	CDE_120uF 450V Low ESR 插板式電解電容	120uF	±20%	450V	85°C	25*30mm	380LX
62199	380LX123M063A052	CDE	CDE_12000uF 63V Low ESR 插板式電解電容	12000uF	±20%	50V	85°C	35*50mm	380LX
63518	380LX221M400J042	CDE	CDE_220uF 400V Low ESR 插板式電解電容	220uF	±20%	400V	85°C	25*40mm	380LX
60530	380LX223M050A052	CDE	CDE_22000uF 50V Low ESR 插板式電解電容	22000uF	±20%	50V	85°C	35*50mm	380LX
63150	380LX680M400H012	CDE	CDE_68uF 400V Low ESR 插板式電解電容	68uF	±20%	400V	85°C	22*25mm	380LX

