



CDE/MALLORY\_Snap-In電解電容

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)



Adding longer-life and more ripple capability to the excellent value of Type 380L/LX capacitors, the 381L/LX readily handles tough switching power supply input and output circuits and motor-drive bus capacitor applications where the high surface area of multiple units in parallel equals the ripple capability of our Type 520C inverter-grade capacitor. Type 381LX delivers more capacitance per can size while Type 381L gives lower ESR for the same capacitance rating. Type 383L gives the choice of 4 or 5 leads for stable, reverseproof mounting. Type 383LX has 5 leads available

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Rated Volt.	Temp. range	Dia.*L(mm)	Type
62200	381LX103M063A052	CDE	CDE_10000uF 63V 長壽命高紋波電解電容	10000uF	±20%	63V	105°C	35*50mm	381LX
64366	381LX682M025J012	CDE	CDE_6800uF 25V 長壽命高紋波電解電容	6800uF	±20%	25V	105°C	25*25mm	381LX

CDE/MALLORY\_鎖螺絲電解電容

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)




The Type 101C is the wide-temperature, low voltage version of the Type 550C. It is ideal for high-ripple current military and industrial applications that need full performance to -40°C and solid performance to -55°C. It also excels as a power-supply output capacitor because of its exceptionally low ESR. The extended cathode foil of the 101C assures heat flow from the capacitor element to the can in all mounting orientations

**產品規格**  
 工作電壓範圍: -55°C to 105°C  
 額定電壓: 7.5 to 250Vdc  
 電容: 290µF to 1.5F  
 電容容差值: 7.5 to 150Vdc:-10+75%, 200 & 250Vdc:-10+50%

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Rated Volt.	Temp. range	Dia.*L(mm)	Type
16720	101C333U063DC2B	CDE	CDE_33000uF 63V 鎖螺絲型 Low ESR 電解電容	33000uF	-10~+75%	63Vdc	-55~105°C	72*112mm	101C



Type 500C capacitors are designed for mainframe computer and other long life UPS and power supply filter applications. They deliver nearly as much capacitance as the Type DCMC capacitors, but with two times the life expectancy. They are an excellent choice for high ripple applications. The extended cathode foil of the 500C assures cool operation with heat flow from the capacitor element to the can

**產品規格**  
 工作溫度範圍: -40°C to +95°C  
 額定電壓: 6.3 to 500Vdc  
 電容: 100µF to 2.6F  
 電容容差值: <200Vdc:-10+75%; ≥200Vdc:-10%+50%

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Rated Volt.	Temp. range	Dia.*L(mm)	Type
62696	500103U075BB2A	CDE	CDE_10000uF 75V 螺絲型電解電容	10000uF	-10%~+75%	75Vdc	-40 to +95°C	50*80mm	500C



Type CGS screw terminal, aluminum electrolytic capacitors have a high CV rating and are suitable for use in most demanding applications requiring high current filtering or energy storage

**產品規格**  
 工作溫度範圍: -40°C to +85°C  
 額定電壓: 6.3 to 500 WVdc  
 電容: 75 to 1,500,000 µF  
 電容容差值: -10%+75%(6.3-150WVdc)  
 -10%+50%(200-450WVdc)

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Rated Volt.	Temp. range	Dia.*L(mm)	Type
62206	CGS103U050R4C	CDE	MALLORY_10000uF/50V High CV 螺絲型電解電容	10000uF	-10%~+75%	50Vdc	-40 to +85°C	35*105mm	CGS
62211	CGS103U075V3C	CDE	MALLORY_10000uF/75V High CV 螺絲型電解電容	56000uF	-10%~+75%	75Vdc	-40 to +85°C	50.8*79.4mm	CGS
62213	CGS103U100W4C	CDE	MALLORY_10000uF/100V High CV 螺絲型電解電容	10000uF	-10%~+75%	100Vdc	-40 to +85°C	63.5*105mm	CGS
62695	CGS153U075V5L	CDE	MALLORY_15000uF/75V High CV 螺絲型電解電容	15000uF	-10%~+75%	75Vdc	-40 to +85°C	50*140mm	CGS
62208	CGS183U050V3C	CDE	MALLORY_18000uF/50V High CV 螺絲型電解電容	18000uF	-10%~+75%	50Vdc	-40 to +85°C	50.8*79.4mm	CGS
62212	CGS253U075W5L	CDE	MALLORY_25000uF/75V High CV 螺絲型電解電容	25000uF	-10%~+75%	75Vdc	-40 to +85°C	63.5*143mm	CGS
62209	CGS313U050W4C	CDE	MALLORY_31000uF/50V High CV 螺絲型電解電容	31000uF	-10%~+75%	50Vdc	-40 to +85°C	63.5*105mm	CGS
62210	CGS563U050X3L	CDE	MALLORY_56000uF/50V High CV 螺絲型電解電容	56000uF	-10%~+75%	50Vdc	-40 to +85°C	76.2*92.08mm	CGS



With more capacitance and often more ripple-current capability than the best-value Type 3186 capacitor, the Type DCMC capacitor is the better choice for high-capacitance, power supply filters and energy storage applications such as welding equipments, UPS systems and computer hold-up power. The extended cathode foil of the DCMC assures cool operation with heatflow from the capacitor element to the can.

**產品規格**  
 工作溫度範圍: -40°C to +85°C  
 額定電壓: 6.3 to 550Vdc  
 電容: 110µF to 2.7F  
 電容容差值: -10%+75% up to 100Vdc, -10+50% 160Vdc & up

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Rated Volt.	Temp. range	Dia.*L(mm)	Type
62201	DCMC103U050AA2B	CDE	CDE_10000uF/50V 螺絲型電解電容	10000uF	-10%~+75%	50Vdc	-40 to +85°C	35*54mm	DCMC
62204	DCMC103U100AD2B	CDE	CDE_10000uF/100V 螺絲型電解電容	10000uF	-10%~+75%	100Vdc	-40 to +85°C	35*117.5mm	DCMC
62205	DCMC163U100EC2B	CDE	CDE_16000uF/100V 螺絲型電解電容	16000uF	-10%~+75%	100Vdc	-40 to +85°C	44.5*105mm	DCMC
62203	DCMC223U075AF2B	CDE	CDE_22000uF/75V 螺絲型電解電容	22000uF	-10%~+75%	75Vdc	-40 to +85°C	35*143mm	DCMC
20041	DCMC253U075BJ2B	CDE	CDE_25000uF 75V 螺絲型電解電容	25000uF	-10%~+75%	75Vdc	-40 to +85°C	50*92mm	DCMC
62202	DCMC263U050AC2B	CDE	CDE_26000uF/50V 螺絲型電解電容	26000uF	-10%~+75%	50Vdc	-40 to +85°C	35*105mm	DCMC

