



CDE_Type TDC 濾波電容



- 額定電壓: 600-5000Vdc
- 電容範圍: 0.1 μ F 到 15.0 μ F
- 電容容差: \pm 10%
- 溫度範圍: -55°C 到 85°C
- 105°C operation with derating
- Hermetically sealed for long life
- 10-32 screw terminals

Use Type T capacitors for filter applications. Typical applications include: filtering, bypass and blocking radar amplifiers and power supplies

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(\pm)	Rated Volt.	Temp. range	A*B*H
20574	T30W6NR/81D89605K86	CDE	Type T High Voltage DC Filter Capacitor	6 μ F	\pm 10%	3000Vdc	-55 to 85°C	1.97**3.66**8**

CDE_MLP Flatpack 鋁質電容



- Low-profile replacement for snap-ins
- Double the ripple capability with a heatsink
- Nearly hermetic welded seal assures 50-year life
- Withstands more than 80,000 feet altitude
- New 2 inch case size

規格參數

工作溫度範圍: -55°C 到 +85°C up to 250Vdc, -40°C 到 85°C 300Vdc & up
額定電壓: 7.5 到 450Vdc
電容: 110 μ F 到 47,000 μ F \pm 20%
峰值電流: \leq 0.002CV μ A@25°C and 5 min

CDE

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(\pm)	Voltage (Vdc)	Temp. range	Size L*W*H(in)
44279	MLP113M050EB0A	CDE	CDE_Flatpack 鋁質電容	11000uF	\pm 20%	50V	-55°C ~85°C	3*1.75*0.5(in)
44273	MLP123M025EA0A	CDE	CDE_Flatpack 鋁質電容	12000uF	\pm 20%	25V	-55°C ~85°C	2*1.75*0.5(in)
44263	MLP133M016EK0A	CDE	CDE_Flatpack 鋁質電容	13000uF	\pm 20%	10V	-55°C ~85°C	1.5*1.75*0.5(in)
44269	MLP143M020EA0A	CDE	CDE_Flatpack 鋁質電容	14000uF	\pm 20%	20V	-55°C ~85°C	2*1.75*0.5(in)
44280	MLP152M080EK0A	CDE	CDE_Flatpack 鋁質電容	1500uF	\pm 20%	80V	-55°C ~85°C	1.5*1.75*0.5(in)
43331	MLP193M7R5EK0A	CDE	CDE_Flatpack 鋁質電容	19000uF	\pm 20%	7.5Vdc	-55°C ~85°C	1.5*1.75*0.5(in)
44274	MLP203M025EB0A	CDE	CDE_Flatpack 鋁質電容	20000uF	\pm 20%	25V	-55°C ~85°C	3*1.75*0.5(in)
44281	MLP212M080EA0A	CDE	CDE_Flatpack 鋁質電容	2100uF	\pm 20%	80V	-55°C ~85°C	2*1.75*0.5(in)
44264	MLP213M016EA0A	CDE	CDE_Flatpack 鋁質電容	21000uF	\pm 20%	10V	-55°C ~85°C	2*1.75*0.5(in)
44271	MLP243M020EB0A	CDE	CDE_Flatpack 鋁質電容	24000uF	\pm 20%	20V	-55°C ~85°C	3*1.75*0.5(in)
44259	MLP283M7R5EA0A	CDE	CDE_Flatpack 鋁質電容	28000uF	\pm 20%	7.5V	-55°C ~85°C	2.0*1.75*0.5(in)
44282	MLP332M080EB0A	CDE	CDE_Flatpack 鋁質電容	3300uF	\pm 20%	80V	-55°C ~85°C	3*1.75*0.5(in)
44265	MLP383M016EB0A	CDE	CDE_Flatpack 鋁質電容	38000uF	\pm 20%	10V	-55°C ~85°C	3*1.75*0.5(in)
44277	MLP442M050EK0A	CDE	CDE_Flatpack 鋁質電容	4400uF	\pm 20%	50V	-55°C ~85°C	1.5*1.75*0.5(in)
44261	MLP473M7R5EB0A	CDE	CDE_Flatpack 鋁質電容	47000uF	\pm 20%	7.5V	-55°C ~85°C	3*1.75*0.5(in)
44275	MLP562M035EK0A	CDE	CDE_Flatpack 鋁質電容	5600uF	\pm 20%	35V	-55°C ~85°C	1.5*1.75*0.5(in)
44278	MLP662M050EA0A	CDE	CDE_Flatpack 鋁質電容	6600uF	\pm 20%	50V	-55°C ~85°C	2*1.75*0.5(in)
44272	MLP802M025EK0A	CDE	CDE_Flatpack 鋁質電容	8000uF	\pm 20%	25V	-55°C ~85°C	1.5*1.75*0.5(in)
44276	MLP842M035EA0A	CDE	CDE_Flatpack 鋁質電容	8400uF	\pm 20%	35V	-55°C ~85°C	1.5*1.75*0.5(in)
44267	MLP962M020EK0A	CDE	CDE_Flatpack 鋁質電容	9600uF	\pm 20%	20V	-55°C ~85°C	1.5*1.75*0.5(in)

鉮質電容

DIP鉮質電容

詳細產品規格-請點擊www.100y.com.tw

Part No.	Product No.	說明	Capacitance uF	Voltage DCV	Tolerance(\pm)
15175	47uF \pm 20% 16V	豆型鉮質電容	47uF	16V	\pm 20%



Part No.	Product No.	說明	Capacitance uF	Voltage DCV	Tolerance(\pm)	Size: D*L (mm)
6361	CB0J107M1EBB	鉮質電容 P:2.54mm	100uF	6.3V	\pm 20%	P:2.54mm
3810	CB1A107M2EBB	鉮質電容 P:5.08mm	100uF	10V	\pm 20%	P:5.08mm
32122	CB1V105M1ABB	鉮質電容	1uF	35V	\pm 20%	
50798	CB1V106K1DBB	鉮質電容	10 μ F	35V	\pm 10%	6.5*11mm
45941	CB1V476K2FBB	鉮質電容	47uF	35V	\pm 10%	
40852	CB1V685K1DBB	鉮質電容	6.8uF	35V	\pm 10%	
6360	CT22UM16VBV	鉮質電容	22uF	16V	\pm 20%	

