



VISHAY_SMD鉍質電容

詳細產品規格-請點擊www.100y.com.tw



293D 107 X9 010 D 2 W
 1 2 3 4 5 6 7

1. 表示系列, 293D表示普通鉍電容
2. 表示電容的容量, 範圍從0.1UF-680UF
3. 表示容量誤差, 鉍電容的容量誤差有兩種: 一是±10%(K)和±20%(M)
4. 表示電容的耐壓, 指在85°C時額定直流電壓, 鉍電容的耐壓範圍從4V-50V
5. 表示鉍電容的尺寸大小, 有A,B,C,D,E,P五種尺寸
6. 表示電容的焊點材料, 一般是鍍銀和鈦銀
7. 表示包裝方式, 有路兩種包裝方式, 7寸盤和13寸盤

字母代碼	長度L	寬度W	厚度H
A	3.2±0.2	1.6±0.2	1.6±0.2
B	3.5±0.2	2.8±0.2	1.9±0.2
C	6.0±0.3	3.2±0.3	2.5±0.3
D	7.3±0.3	4.3±0.3	2.8±0.3
E	7.3±0.3	4.3±0.3	4.0±0.3

Unit:mm



Part No.	Product No.	製造廠商	說明	Capacitance uF	Tolerance(±)	Voltage	Case(L*W1*H*L1*W2*K)	Pes./Reel
52509	293D105X9035B2TE3	VISHAY	SMD 鉍質電容	1uF	±10%	35V	B	2000 個/R
52544	293D105X9035B2TE3	VISHAY	SMD 鉍質電容	1uF	±10%	35V	B	2000 個/R
28524	293D106X9016B2TE3	VISHAY	SMD 鉍質電容	10uF	±10%	16V	B	2000/R
23826	293D106X9020B2T	VISHAY	SMD 鉍質電容	10uF	±10%	20V	B	2000pcs/R
29423	293D107X96R3B2T	VISHAY	SMD 100uF/6.3V-B 鉍質電容	100uF	±10%	6.3V	B	2000
42930	293D107X96R3B2TE3	VISHAY	SMD 鉍質電容	100uF	±10%	6.3V	B	2000/R
48799	293D225X9035B2TE3	VISHAY	SMD 鉍質電容	2.2uF	±10%	35V	B	2000/R
32123	293D226X9010B2T	VISHAY	SMD 鉍質電容	22uF	±10%	10V	B	2000
39662	293D226X9010B2TE3	VISHAY	SMD 鉍質電容【無鉛】	22uF	±10%	10V	B	2000/R
48800	293D475X9025B2TE3	VISHAY	SMD 鉍質電容	4.7uF	±10%	25V	B	2000/R
29807	293D476X9010B2T	VISHAY	SMD 47uF/10V-B 鉍質電容	47uF	±10%	10V	B	2000
29422	293D476X9010B2T	VISHAY	SMD 鉍質電容	47uF	±10%	10V	B	2000
61664	293D476X96R3B2TE3	VISHAY	SMD 鉍質電容	47uF	±10%	6.3V	B	2000/R
58525	293D475X9035C2TE3	VISHAY	SMD 鉍質電容	4.7uF	±10%	35V	C	500
52748	293D105X9050C2TE3	VISHAY	SMD 鉍質電容	1uF	±10%	50V	C	500PCS/R
40273	293D106X9025C2TE3	VISHAY	SMD 鉍質電容	10uF	±10%	25V	C	500pcs/R
2330	293D107X9010C2TE3	VISHAY	SMD 鉍質電容	100uF	±10%	10V	C	500/R
22414	293D107X9010C2TE3	VISHAY	SMD 鉍質電容【無鉛】	100uF	±10%	10V	C	500
58748	293D107X96R3C2TE3	VISHAY	SMD 鉍質電容	100uF	±10%	6.3V	C	500Pcs/R
39434	293D226X9016C2TE3	VISHAY	SMD 鉍質電容【無鉛】	22uF	±10%	16V	C Case	500 個/捲
40502	293D336X9016C2TE3	VISHAY	SMD 鉍質電容	33uF	±10%	16V	C	500pcs/R
50439	293D227X96R3C2TE3	VISHAY	SMD 鉍質電容	220uF	±10%	6.3V	C	500
24909	293D476X9016C2TE3	VISHAY	SMD 47uF/16V-C 鉍質電容	47uF	±10%	16V	C	500
45195	293D106X9035D2TE3	VISHAY	SMD 鉍質電容	10uF	±10%	35V	D	500/R
28568	293D107X9010D2TE3	VISHAY	SMD 鉍質電容	100uF	±10%	10V	D	500/R
52281	293D107X9016D2TE3	VISHAY	SMD 鉍質電容	100uF	±10%	16V	D	500/R
23825	293D157X9010D2T	VISHAY	SMD 鉍質電容	150uF	±10%	10V	D	500pcs/R
50440	293D157X9010D2TE3	VISHAY	SMD 鉍質電容	150uF	±10%	10V	D	500pcs/R
52891	293D225X9050D2TE3	VISHAY	SMD 鉍質電容	2.2uF	±10%	50V	D	500/R
40360	293D226X9035D2TE3	VISHAY	SMD 鉍質電容【無鉛】	22uF	±10%	35V	D	500/R
40358	293D226X9035D2TE3	VISHAY	SMD 鉍質電容	22uF	±10%	35V	D	500/R
28732	293D227X9010D2TE3	VISHAY	SMD 鉍質電容	220uF	±10%	10V	D	500
59594	293D227X9010D2TE3	VISHAY	SMD 鉍質電容	220uF	±10%	10V	D	500
55204	293D336X9025D2TE3	VISHAY	SMD 鉍質電容	33uF	±10%	25V	D	500pcs/R
31300	293D337X96R3D2T	VISHAY	SMD 鉍質電容	330uF	±10%	6.3V	D	500pcs/R
29475	293D337X96R3D2TE3	VISHAY	SMD 鉍質電容	330uF	±10%	6.3V	D	500
31298	293D475X9050D2T	VISHAY	SMD 鉍質電容	4.7uF	±10%	50V	D	500/R
29395	293D476X9020D2T	VISHAY	SMD 鉍質電容	47uF	±10%	20V	D	500
22462	293D476X9020D2TE3	VISHAY	SMD 鉍質電容【無鉛】	47uF	±20%	20V	D	500
12231	293D686X9020D2TE3	VISHAY	SMD 鉍質電容	68uF	±10%	20V	D	500/R
52282	293D107X9016E2TE3	VISHAY	SMD 鉍質電容	100uF	±10%	16V	E	500/R



293D 107 X9 010 D 2 W
 1 2 3 4 5 6 7

1. 表示系列, 593D表示低阻抗鉍電容, 直流電阻小於1歐, 一般在100毫歐到500毫歐之間
2. 表示電容的容量, 範圍從0.1UF-680UF
3. 表示容量誤差, 鉍電容的容量誤差有兩種: 一是±10%(K)和±20%(M)
4. 表示電容的耐壓, 指在85°C時額定直流電壓, 鉍電容的耐壓範圍從4V-50V
5. 表示鉍電容的尺寸大小, 有A,B,C,D,E,P五種尺寸
6. 表示電容的焊點材料, 一般是鍍銀和鈦銀
7. 表示包裝方式, 有路兩種包裝方式, 7寸盤和13寸盤

字母代碼	長度L	寬度W	厚度H
A	3.2±0.2	1.6±0.2	1.6±0.2
B	3.5±0.2	2.8±0.2	1.9±0.2
C	6.0±0.3	3.2±0.3	2.5±0.3
D	7.3±0.3	4.3±0.3	2.8±0.3
E	7.3±0.3	4.3±0.3	4.0±0.3

Unit:mm



Part No.	Product No.	製造廠商	說明	Capacitance uF	Tolerance(±)	Voltage	Case(L*W1*H*L1*W2*K)	Pes./Reel
39661	593D157X9010D2TE3	VISHAY	SMD 鉍質電容【無鉛】	150uF	±10%	10V	D	500/R

● 假如您需要適合特殊用途的產品或更詳細的技術資料, 我們的業務專員將會透過電話, 傳真, E-mail,幫助您

