



## AC(BXE型)金屬化塑膠膜電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


改善功率因素等一般用途，主要運用在各類機電馬達，壓縮機，風扇等

Part No.	Product No.	製造廠商	說明	L*W*H (mm)	Temp. Range°C	Tolerance(±)	Capacitance	Rated Volt.
4422	BXE/MPP-1.5uF/250VAC	DJE	AC 電容	32*12.5*21.5	25°C ~+70°C	±10%	1.5uF	250VAC
4416	BXE/MPP-10uF/250VAC	DJE	AC 電容	51*22*32	25~+70°C	±10%	10uF	250VAC
54629	BXE/MPP-1uF/2100vac	DJE	AC 電容	25°C ~+70°C	32*12.5*21.5	±10%	1uF	2100v
4418	BXE/MPP-1uF/250VAC	DJE	AC 電容	32*12.5*21.5	25°C ~+70°C	±10%	1uF	250VAC
4421	BXE/MPP-2.0uF/250VAC	DJE	AC 電容	32*13*23	25°C ~+70°C	±10%	2.0uF	250VAC
4420	BXE/MPP-2.2uF/250VAC	DJE	AC 電容	32*13*23	25°C ~+70°C	±10%	2.2uF	250VAC
30148	BXE/MPP-2.5uF/250VAC	DJE	AC 電容	32*13*23	25°C ~+70°C	±5%	2.5uF	250VAC
4414	BXE/MPP-20uF/250VAC	DJE	AC 電容	51*30*40	25°C ~+70°C	±10%	20uF	250VAC
11656	BXE/MPP-3.5uF/250V	DJE	AC 電容	32*14*24	25°C ~+70°C	±5%	3.5uF	250VAC
4419	BXE/MPP-4uF/300VAC	DJE	AC 電容	38*17*27	25°C ~+70°C	±5%	4uF	300VAC
28324	BXE/MPP-4uF/350VAC	DJE	AC 電容	39*22*32	25°C ~+70°C	±5%	4uF	350VAC
4417	BXE/MPP-5uF/250VAC	DJE	AC 電容	38*17*27	25°C ~+70°C	±10%	5uF	250VAC
40560	BXE/MPP-7uF/250VAC	DJE	金屬化塑膠膜電容	32*13*23	25°C ~+70°C	±5%	7uF	250VAC



改善功率因素，濾波，馬達運轉等一般用途，運用在各類機電馬達，齒輪馬達，風扇，壓縮機，冷氣機，空調系統，電源設備，電機電子設備等

Part No.	Product No.	製造廠商	說明	L*W*H (mm)	Temp. Range°C	Tolerance(±)	Capacitance	Rated Volt.
30117	BXF/MPP-2uF/250VAC	DJE	AC 電容	32*13*23	25°C ~+70°C	±10%	2uF	250VAC
29365	BXF/MPP-5uF/250VAC	DJE	AC 電容	37*15*24	25°C ~+70°C	±10%	5uF	250VAC

## CDE\_X2 Suppressor 電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- Radial Leads in Two Lengths
- UL-1414 and CSA Approved
- Flame Retardant Case Meets UL94V-0
- Potting End Fill Meets UL94V-0
- Used in applications where damage to the capacitor will not lead to the danger of electrical shock
- Leak Material Tinned Copper Clad Steel

Part No.	Product No.	製造廠商	說明	Capacitance (uF)	Tolerance(±)	Rated Volt.	Temp. range	Size L*W*H	Pitch
60430	158X224K	CDE	聚酯薄膜電容【ROHS】	0.22uF	±10%/	250VAC	-40~100°C	25*8*17.5mm	22.5mm

## AC X2 濾波電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


主要用於電子，音頻，視頻設備，充電器，測量儀器，電氣手工具，家用電器，開關電源和某些機械的抗無線電干擾電路，跨接電路等，其優點在於在相同的規格下尺寸較小，其溫度範圍較廣，高溫可做到125°C



Part No.	Product No.	製造廠商	說明	Capacitance	Rated Volt.	Tolerance(±)	L*H*W(mm)	Temp. Range°C
61512	KNB1560-0.15uF/275VAC	Iskra	Iskra X2 濾波電容	0.15uF	275VAC	±10%	18*13*7mm	-40°C ~+100°C
52483	KNB1560-0.1uF/275VAC	Iskra	Iskra X2 濾波電容	0.1uF	275VAC	+/-20%	13*12*6	-40°C ~+100°C
52484	KNB1560-0.1uF/275VAC	Iskra	Iskra X2 濾波電容	0.1uF	275VAC	+/-20%	18*11*5.5	-40°C ~+100°C
52485	KNB1560-0.22uF/275VAC	Iskra	Iskra X2 濾波電容	0.22uF	275VAC	±10%	18*14.5*8.2	-40°C ~+100°C
52486	KNB1560-0.22uF/275VAC	Iskra	Iskra X2 濾波電容	0.22uF	275VAC	±10%	18*14.5*8.2	-40°C ~+100°C
52487	KNB1560-0.33uF/275VAC	Iskra	Iskra X2 濾波電容	0.33uF	275VAC	±10%	18*16*9.5	-40°C ~+100°C
52488	KNB1560-0.47uF/275VAC	Iskra	Iskra X2 濾波電容	0.47uF	275VAC	±10%	18*18.5*11	-40°C ~+100°C
52572	KNB1560-0.47uF/275VAC	Iskra	Iskra X2 濾波電容	0.47uF	275VAC	±10%	26.5*17*8.5	-40°C ~+100°C
61511	KNB1560-0.47uF/300VAC	Iskra	Iskra X2 濾波電容	0.47uF	300VAC	±10%	18*18.5*11mm	-40°C ~+100°C
52489	KNB1560-0.68uF/275VAC	Iskra	Iskra X2 濾波電容	0.68uF	275VAC	±10%	26.5*18.5*10	-40°C ~+100°C
52490	KNB1560-0.68uF/275VAC	Iskra	Iskra X2 濾波電容	0.68uF	275VAC	±10%	26.5*18.5*10	-40°C ~+100°C
52491	KNB1560-1.0uF/275VAC	Iskra	Iskra X2 濾波電容	1uF	275VAC	±10%	26.5*21.5*12.5	-40°C ~+100°C
52492	KNB1560-1.5uF/275VAC	Iskra	Iskra X2 濾波電容	1.5uF	275VAC	±10%	31.5*23.5*14	-40°C ~+100°C
52493	KNB1560-2.2uF/275VAC	Iskra	Iskra X2 濾波電容	2.2uF	275VAC	±10%	31.5*26.5*17	-40°C ~+100°C

- 每月上百種新產品入庫中，若您在網上PDF目錄上找不到您需要的元件，歡迎您來電或在我們網站查詢
- 您也可以請我們代購產品，歡迎您的來電
- 商品說明僅供參考，商品規格，外型若有不符，以出貨品為主

