



WIMA_ 聚丙烯膜電容

詳細產品規格-請點擊www.100y.com.tw



- 材質：整片金屬膜導體，聚丙烯膜絕緣(PP)
- 結構及特性：高脈沖承受結構/超低損失角/負溫度系數/極低介質損失
- 典型的應用：高頻電路/取樣保持/弛張電路/時基電路/LC濾波電路/音響設備



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
50875	WIMA-FKP2-430pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	430pF	±2.5%	100V		-55°C to +100°C	5mm
33955	WIMA-FKP2-4700pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	4700pF	±2.5%	100V	5.5*7*7.2mm	-55°C to +100°C	5mm
50899	WIMA-FKP2-4700pF/630V	WIMA	聚丙烯膜絕緣(PP)電容	4700pF	±2.5%	630V	6.5*8*7.2	-55°C to +100°C	5mm
50898	WIMA-FKP2-4700pF/63V	WIMA	聚丙烯膜絕緣(PP)電容	4700pF	±2.5%	63V	4.5*6*7.2	-55°C to +100°C	5mm
50876	WIMA-FKP2-470pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	470pF	±2.5%	100V	4.5*6*7.2	-55°C to +100°C	5mm
50877	WIMA-FKP2-470pF/630V	WIMA	聚丙烯膜絕緣(PP)電容	470pF	±2.5%	630V	4.5*6*7.2	-55°C to +100°C	5mm
50857	WIMA-FKP2-47pF/630V	WIMA	聚丙烯膜絕緣(PP)電容	47pF	±2.5%	630V		-55°C to +100°C	5mm
50878	WIMA-FKP2-500pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	500pF	±2.5%	100V		-55°C to +100°C	5mm
50879	WIMA-FKP2-510pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	510pF	±2.5%	100V		-55°C to +100°C	5mm
50901	WIMA-FKP2-5600pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	5600pF	±2.5%	100V		-55°C to +100°C	5mm
50900	WIMA-FKP2-5600pF/63V	WIMA	聚丙烯膜絕緣(PP)電容	5600pF	±2.5%	63V		-55°C to +100°C	5mm
50880	WIMA-FKP2-560pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	560pF	±2.5%	100V		-55°C to +100°C	5mm
50881	WIMA-FKP2-620pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	620pF	±2.5%	100V		-55°C to +100°C	5mm
50903	WIMA-FKP2-6800pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	6800pF	±2.5%	100V	5.5*7*7.2	-55°C to +100°C	5mm
50904	WIMA-FKP2-6800pF/630V	WIMA	聚丙烯膜絕緣(PP)電容	6800pF	±2.5%	630V	7.2*8.5*7.2	-55°C to +100°C	5mm
50902	WIMA-FKP2-6800pF/63V	WIMA	聚丙烯膜絕緣(PP)電容	6800pF	±2.5%	63V	4.5*6*7.2	-55°C to +100°C	5mm
50883	WIMA-FKP2-680pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	680pF	±2.5%	100V	4.5*6*7.2	-55°C to +100°C	5mm
50882	WIMA-FKP2-680pF/63V	WIMA	聚丙烯膜絕緣(PP)電容	680pF	±2.5%	63V	4.5*6*7.2	-55°C to +100°C	5mm
50858	WIMA-FKP2-68pF/630V	WIMA	聚丙烯膜絕緣(PP)電容	68pF	±5%	630V		-55°C to +100°C	5mm
50859	WIMA-FKP2-68pF/630V	WIMA	聚丙烯膜絕緣(PP)電容	68pF	±2.5%	630V		-55°C to +100°C	5mm
50905	WIMA-FKP2-8200pF/63V	WIMA	聚丙烯膜絕緣(PP)電容	8200pF	±2.5%	63V		-55°C to +100°C	5mm
50884	WIMA-FKP2-820pF/100V	WIMA	聚丙烯膜絕緣(PP)電容	820pF	±5%	100V		-55°C to +100°C	5mm



- 材質：整片金屬膜導體，聚丙烯膜絕緣(PP)
- 結構及特性：高脈沖承受結構/超低損失角/負溫度系數/極低介質損失
- 典型的應用：高頻電路/取樣保持/弛張電路/時基電路/LC濾波電路/音響設備



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
50956	WIMA-FKP3-0.015uF/250V	WIMA	聚丙烯膜電容	0.015uF	±5%	250V	6*12*13	-55°C to +100°C	10mm
50955	WIMA-FKP3-0.01uF/1000V	WIMA	聚丙烯膜電容	0.01uF	±5%	1000V	6*12.5*18	-55°C to +100°C	15mm
50952	WIMA-FKP3-0.01uF/100V	WIMA	聚丙烯膜電容	0.01uF	±5%	100V	4*9*10	-55°C to +100°C	7.5mm
50953	WIMA-FKP3-0.01uF/250V	WIMA	聚丙烯膜電容	0.01uF	±5%	250V	5*11*13	-55°C to +100°C	10mm
50954	WIMA-FKP3-0.01uF/630V	WIMA	聚丙烯膜電容	0.01uF	±5%	630V	6*12.5*18	-55°C to +100°C	15mm
50959	WIMA-FKP3-0.022uF/1000V	WIMA	聚丙烯膜電容	0.022uF	±5%	1000V	9*16*18	-55°C to +100°C	15mm
50957	WIMA-FKP3-0.022uF/160V	WIMA	聚丙烯膜電容	0.022uF	±5%	160V		-55°C to +100°C	10mm
50958	WIMA-FKP3-0.022uF/400V	WIMA	聚丙烯膜電容	0.022uF	±5%	400V	7*14*18	-55°C to +100°C	15mm
50960	WIMA-FKP3-0.033uF/100V	WIMA	聚丙烯膜電容	0.033uF	±5%	100V	6*12*13	-55°C to +100°C	10mm
50961	WIMA-FKP3-0.033uF/250V	WIMA	聚丙烯膜電容	0.033uF	±5%	250V	7*14*18	-55°C to +100°C	15mm
50962	WIMA-FKP3-0.033uF/400V	WIMA	聚丙烯膜電容	0.033uF	±5%	400V	8*15*18	-55°C to +100°C	15mm
50964	WIMA-FKP3-0.047uF/160V	WIMA	聚丙烯膜電容	0.047uF	±5%	160V		-55°C to +100°C	15mm
50963	WIMA-FKP3-0.047uF/63V	WIMA	聚丙烯膜電容	0.047uF	±5%	63V	5*11*13	-55°C to +100°C	10mm
50966	WIMA-FKP3-0.068uF/160V	WIMA	聚丙烯膜電容	0.068uF	±5%	160V		-55°C to +100°C	15mm
50965	WIMA-FKP3-0.068uF/63V	WIMA	聚丙烯膜電容	0.068uF	±5%	63V	6*12*13	-55°C to +100°C	10mm
50967	WIMA-FKP3-0.15uF/100V	WIMA	聚丙烯膜電容	0.15uF	±5%	100V	9*16*18	-55°C to +100°C	15mm
31939	WIMA-FKP3-0.1uF/100V	WIMA	聚丙烯膜電容	0.1uF	±10%	100V	7*14*18	-55°C to +100°C	15mm
50968	WIMA-FKP3-0.22uF/63V	WIMA	聚丙烯膜電容	0.22uF	±5%	63V	9*16*18	-55°C to +100°C	15mm
31938	WIMA-FKP3-1.0uF/100V	WIMA	聚丙烯膜電容	1.0uF		100V		-55°C to +100°C	
50935	WIMA-FKP3-1000pF/1000V	WIMA	聚丙烯膜電容	1000pF	±5%	1000V	4*9*10	-55°C to +100°C	7.5mm
50929	WIMA-FKP3-100pF/1000V	WIMA	聚丙烯膜電容	100pF	±5%	1000V	3*8.5*10	-55°C to +100°C	7.5mm
31936	WIMA-FKP3-10uF/100V	WIMA	聚丙烯膜電容	10uF		100V		-55°C to +100°C	
50937	WIMA-FKP3-1500pF/1000V	WIMA	聚丙烯膜電容	1500pF	±5%	1000V	4*9.5*13	-55°C to +100°C	10mm
50936	WIMA-FKP3-1500pF/400V	WIMA	聚丙烯膜電容	1500pF	±5%	400V	4*9*10	-55°C to +100°C	7.5mm
50930	WIMA-FKP3-150pF/1000V	WIMA	聚丙烯膜電容	150pF	±5%	1000V	3*8.5*10	-55°C to +100°C	7.5mm
50939	WIMA-FKP3-2200pF/1000V	WIMA	聚丙烯膜電容	2200pF	±5%	1000V	4*9.5*13	-55°C to +100°C	10mm
50938	WIMA-FKP3-2200pF/400V	WIMA	聚丙烯膜電容	2200pF	±5%	400V	4*9*10	-55°C to +100°C	7.5mm
50932	WIMA-FKP3-220pF/1000V	WIMA	聚丙烯膜電容	220pF	±5%	1000V	3*8.5*10	-55°C to +100°C	7.5mm
50941	WIMA-FKP3-3300pF/1000V	WIMA	聚丙烯膜電容	3300pF	±5%	1000V	5*11*13	-55°C to +100°C	10mm
50940	WIMA-FKP3-3300pF/160V	WIMA	聚丙烯膜電容	3300pF	±5%	160V		-55°C to +100°C	7.5mm
50931	WIMA-FKP3-330pF/1000V	WIMA	聚丙烯膜電容	330pF	±5%	1000V	3*8.5*10	-55°C to +100°C	7.5mm
50949	WIMA-FKP3-4700pF/1000V	WIMA	聚丙烯膜電容	4700pF	±5%	1000V	6*12*13	-55°C to +100°C	10mm
50948	WIMA-FKP3-4700pF/160V	WIMA	聚丙烯膜電容	4700pF	±5%	160V		-55°C to +100°C	7.5mm
50933	WIMA-FKP3-470pF/1000V	WIMA	聚丙烯膜電容	470pF	±5%	1000V	3*8.5*10	-55°C to +100°C	7.5mm
50950	WIMA-FKP3-6800pF/160V	WIMA	聚丙烯膜電容	6800pF	±5%	160V		-55°C to +100°C	7.5mm
50951	WIMA-FKP3-6800pF/400V	WIMA	聚丙烯膜電容	6800pF	±5%	400V	6*12*13	-55°C to +100°C	10mm
50934	WIMA-FKP3-680pF/1000V	WIMA	聚丙烯膜電容	680pF	±5%	1000V	3*8.5*10	-55°C to +100°C	7.5mm

