



WIMA_金屬化聚脂膜電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- 材質：整片金屬導體 聚乙烯膜絕緣(PET)
- 結構及特性：高脈沖承受結構
- 典型的應用：DC電路/交連耦合/退交連



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
31905	WIMA-FKS2-0.01uF/100V	WIMA	聚脂膜電容	0.01uF	±5%	100V	3*7.5*7.2	-55°C to +100°C	5mm
50976	WIMA-FKS2-0.01uF/400V	WIMA	聚脂膜電容	0.01uF	±5%	400V	3.5*8.5*7.2	-55°C to +100°C	5mm
31899	WIMA-FKS2-1000pF/100V	WIMA	聚脂膜電容	1000pF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
31906	WIMA-FKS2-1000pF/400V	WIMA	聚脂膜電容	1000pF	±5%	400V	2.5*6.5*7.2	-55°C to +100°C	5mm
31907	WIMA-FKS2-2200pF/100V	WIMA	聚脂膜電容	2200pF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
50971	WIMA-FKS2-2200pF/400V	WIMA	聚脂膜電容	2200pF	±5%	400V	2.5*6.5*7.2	-55°C to +100°C	5mm
50972	WIMA-FKS2-3300pF/100V	WIMA	聚脂膜電容	3300pF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
50973	WIMA-FKS2-3300pF/400V	WIMA	聚脂膜電容	3300pF	±5%	400V	2.5*6.5*7.2	-55°C to +100°C	5mm
51194	WIMA-FKS2-4700pF/100V	WIMA	聚脂膜電容	4700pF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
50974	WIMA-FKS2-4700pF/400V	WIMA	聚脂膜電容	4700pF	±5%	400V	2.5*6.5*7.2	-55°C to +100°C	5mm
50975	WIMA-FKS2-6800pF/100V	WIMA	聚脂膜電容	6800pF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm



- 材質：整片金屬導體，聚乙烯膜絕緣(PET)
- 結構及特性：高脈沖承受結構
- 典型的應用：DC電路/交連耦合/退交連電路



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
31933	WIMA-FKS3-0.1uF/250V	WIMA	聚脂膜電容	0.1uF	±5%	250V	8*15*18	-55°C to +100°C	15mm
31935	WIMA-FKS3-1000pF/400V	WIMA	聚脂膜電容	1000pF	±5%	400V	3*9*13	-55°C to +100°C	10mm
50983	WIMA-FKS3-1000pF/630V	WIMA	聚脂膜電容	1000pF	±5%	630V	3*9*13	-55°C to +100°C	10mm
31934	WIMA-FKS3-2200pF/400V	WIMA	聚脂膜電容	2200pF	±5%	400V	3*9*13	-55°C to +100°C	10mm
50984	WIMA-FKS3-2200pF/630V	WIMA	聚脂膜電容	2200pF	±5%	630V	3*9*13	-55°C to +100°C	10mm
50985	WIMA-FKS3-3300pF/400V	WIMA	聚脂膜電容	3300pF	±5%	400V	3*9*13	-55°C to +100°C	10mm
50986	WIMA-FKS3-3300pF/630V	WIMA	聚脂膜電容	3300pF	±5%	630V	4*9.5*13	-55°C to +100°C	10mm
50987	WIMA-FKS3-4700pF/400V	WIMA	聚脂膜電容	4700pF	±5%	400V	3*9*13	-55°C to +100°C	10mm
51195	WIMA-FKS3-4700pF/630V	WIMA	聚脂膜電容	4700pF	±5%	630V	4*9.5*13	-55°C to +100°C	10mm
50988	WIMA-FKS3-6800pF/400V	WIMA	聚脂膜電容	6800pF	±5%	400V	3*9*13	-55°C to +100°C	10mm



- 材質：金屬化聚乙烯膜(PET)
- 結構及特性：高[體積/容量]比/具自愈能力
- 典型的應用：DC電路/時振電路/旁路電路/交連耦合/退交連/時基電路



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
31874	WIMA-MKS-02-0.022uF/63V	WIMA	金屬化聚脂膜電容	0.022uF	±10%	63V	2.5*7*4.6	-55°C to +100°C	2.5mm
31870	WIMA-MKS-02-0.033uF/63V	WIMA	金屬化聚脂膜電容	0.033uF	±5%	63V	2.5*7*4.6	-55°C to +100°C	2.5mm
31869	WIMA-MKS-02-0.047uF/63V	WIMA	金屬化聚脂膜電容	0.047uF	±10%	63V	2.5*7*4.6	-55°C to +100°C	2.5mm
51294	WIMA-MKS-02-0.1uF/63V	WIMA	金屬化聚脂膜電容	0.1uF	±10%	63V	3*7.5*4.6	-55°C to +100°C	2.5mm
51295	WIMA-MKS-02-0.22uF/50V	WIMA	金屬化聚脂膜電容	0.22uF	±5%	50V	3*7.5*4.6	-55°C to +100°C	2.5mm
51298	WIMA-MKS-02-0.33uF/50V	WIMA	金屬化聚脂膜電容	0.33uF	±10%	50V	3*7.5*4.6	-55°C to +100°C	2.5mm
51296	WIMA-MKS-02-0.47uF/50V	WIMA	金屬化聚脂膜電容	0.47uF	±5%	50V	4.6*9*4.6	-55°C to +100°C	2.5mm
31875	WIMA-MKS-02-1.0uF/63V	WIMA	金屬化聚脂膜電容	0.01uF	±10%	63V	2.5*7*4.6	-55°C to +100°C	2.5mm
51297	WIMA-MKS-02-1uF/50V	WIMA	金屬化聚脂膜電容	1uF	±10%	50V	5.5*10*4.6	-55°C to +100°C	2.5mm



- 材質：金屬化聚乙烯膜(PET)
- 結構及特性：高[體積/容量]比/具自愈能力
- 典型的應用：DC電路/時振電路/旁路電路/交連耦合/退交連/時基電路



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
51240	WIMA-MKS2-0.015uF/100V	WIMA	金屬化聚脂膜電容	0.015uF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
51241	WIMA-MKS2-0.015uF/250V	WIMA	金屬化聚脂膜電容	0.015uF	±5%	250V	2.5*6.5*7.2	-55°C to +100°C	5mm
51242	WIMA-MKS2-0.015uF/400V	WIMA	金屬化聚脂膜電容	0.015uF	±5%	400V	2.5*6.5*7.2	-55°C to +100°C	5mm
31894	WIMA-MKS2-0.015uF/63V	WIMA	金屬化聚脂膜電容	0.015uF	±5%	63V	2.5*6.5*7.2	-55°C to +100°C	5mm
31893	WIMA-MKS2-0.01uF/100V	WIMA	金屬化聚脂膜電容	0.01uF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
31885	WIMA-MKS2-0.01uF/250V	WIMA	金屬化聚脂膜電容	0.01uF	±5%	250V	2.5*6.5*7.2	-55°C to +100°C	5mm
63707	WIMA-MKS2-0.01uF/400V	WIMA	金屬化聚脂膜電容	0.01uF	±5%	400VDC	2.5*6.5*7.2	-55°C to +100°C	5mm
31878	WIMA-MKS2-0.01uF/63V	WIMA	金屬化聚脂膜電容	0.01uF	±5%	63V	2.5*6.5*7.2	-55°C to +100°C	5mm
51244	WIMA-MKS2-0.022uF/100V	WIMA	金屬化聚脂膜電容	0.022uF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
51245	WIMA-MKS2-0.022uF/250V	WIMA	金屬化聚脂膜電容	0.022uF	±5%	250V	2.5*6.5*7.2	-55°C to +100°C	5mm
51243	WIMA-MKS2-0.022uF/63V	WIMA	金屬化聚脂膜電容	0.022uF	±5%	63V	2.5*6.5*7.2	-55°C to +100°C	5mm
51247	WIMA-MKS2-0.033uF/100V	WIMA	金屬化聚脂膜電容	0.033uF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
51248	WIMA-MKS2-0.033uF/250V	WIMA	金屬化聚脂膜電容	0.01uF	±5%	250V	3.5*8.5*7.2	-55°C to +100°C	5mm

