



WIMA_金屬化聚脂膜電容

詳細產品規格-請點擊www.100y.com.tw



- 材質：金屬化聚乙烯膜(PET)
- 結構及特性：高[體積/容量]比/具自愈能力
- 典型的應用：DC電路/時振電路/旁路電路/交連偶合/退交連/時基電路



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
51246	WIMA-MKS2-0.033uF/63V	WIMA	金屬化聚脂膜電容	0.033uF	±5%	63V	2.5*6.5*7.2	-55°C to +100°C	5mm
51250	WIMA-MKS2-0.047uF/100V	WIMA	金屬化聚脂膜電容	0.047uF	±5%	100V	2.5*6.5*7.2	-55°C to +100°C	5mm
51251	WIMA-MKS2-0.047uF/250V	WIMA	金屬化聚脂膜電容	0.047uF	±5%	250V	3.5*8.5*7.2	-55°C to +100°C	5mm
51249	WIMA-MKS2-0.047uF/63V	WIMA	金屬化聚脂膜電容	0.047uF	±5%	63V	2.5*6.5*7.2	-55°C to +100°C	5mm
51357	WIMA-MKS2-0.068uF/100V	WIMA	金屬化聚脂膜電容	0.068uF	±5%	100VDC/63VAC	2.5*6.5*7.2	-55°C to +100°C	5mm
51358	WIMA-MKS2-0.068uF/250V	WIMA	金屬化聚脂膜電容	0.068uF	±5%	250VDC/160VAC	3.5*8.5*7.2	-55°C to +100°C	5mm
51252	WIMA-MKS2-0.068uF/63V	WIMA	金屬化聚脂膜電容	0.068uF	±5%	63V	2.5*6.5*7.2	-55°C to +100°C	5mm
51257	WIMA-MKS2-0.15uF/100V	WIMA	金屬化聚脂膜電容	0.15uF	±5%	100VDC/63VAC	3.5*8.5*7.2	-55°C to +100°C	5mm
51258	WIMA-MKS2-0.15uF/250V	WIMA	金屬化聚脂膜電容	0.15uF	±5%	250VDC/160VAC	5*10*7.2	-55°C to +100°C	5mm
51255	WIMA-MKS2-0.15uF/50V	WIMA	金屬化聚脂膜電容	0.15uF	±5%	50VDC/30VAC	2.5*6.5*7.2	-55°C to +100°C	5mm
51256	WIMA-MKS2-0.15uF/63V	WIMA	金屬化聚脂膜電容	0.15uF	±5%	63VDC/40VAC	2.5*6.5*7.2	-55°C to +100°C	5mm
41987	WIMA-MKS2-0.1uF/100V	WIMA	金屬化聚脂膜電容	0.1uF	±5%	100V	2.5*6.5*7.2mm	-55°C to +100°C	5mm
51253	WIMA-MKS2-0.1uF/250V	WIMA	金屬化聚脂膜電容	0.1uF	±5%	250V	4.5*9.5*7.2	-55°C to +100°C	5mm
51254	WIMA-MKS2-0.1uF/400V	WIMA	金屬化聚脂膜電容	0.1uF	±5%	400V	7.2*13*7.2	-55°C to +100°C	5mm
48140	WIMA-MKS2-0.1uF/63V	WIMA	金屬化聚脂膜電容	0.1uF	±5%	63V	2.5*6.5*7.2mm	-55°C to +100°C	5mm
51270	WIMA-MKS2-0.22uF/100V	WIMA	金屬化聚脂膜電容	0.22uF	±5%	100VDC/63VAC	3.5*8.5*7.2	-55°C to +100°C	5mm
51272	WIMA-MKS2-0.22uF/250V	WIMA	金屬化聚脂膜電容	0.22uF	±5%	250VDC/160VAC	5.5*11.5*7.2	-55°C to +100°C	5mm
51259	WIMA-MKS2-0.22uF/50V	WIMA	金屬化聚脂膜電容	0.22uF	±5%	50VDC/30VAC	3*7.5*7.2	-55°C to +100°C	5mm
51269	WIMA-MKS2-0.22uF/63V	WIMA	金屬化聚脂膜電容	0.22uF	±5%	63VDC/40VAC	3*7.5*7.2	-55°C to +100°C	5mm
51273	WIMA-MKS2-0.33uF/100V	WIMA	金屬化聚脂膜電容	0.33uF	±5%	100VDC/63VAC	4.5*9.5*7.2	-55°C to +100°C	5mm
40077	WIMA-MKS2-0.33uF/50V	WIMA	金屬化聚脂膜電容	0.33uF	5%	50Vdc/30Vac	2.5*6.5*7.2mm	-55°C to +100°C	5mm
40076	WIMA-MKS2-0.33uF/63V	WIMA	金屬化聚脂膜電容	0.33uF	5%	63Vdc/40Vac	3.5*8.5*7.2mm	-55°C to +100°C	5mm
51275	WIMA-MKS2-0.47uF/100V	WIMA	金屬化聚脂膜電容	0.47	±5%	100VDC/63VAC	4.5*9.5*7.2	-55°C to +100°C	5mm
42727	WIMA-MKS2-0.47uF/50V	WIMA	金屬化聚脂膜電容	0.47uF	±5%	50V	3*7.5*7.2	-55°C to +100°C	5mm
49809	WIMA-MKS2-0.47uF/63V	WIMA	金屬化聚脂膜電容	0.47uF	±5%	63V	3.5*8.5*7.2	-55°C to +100°C	5mm
51278	WIMA-MKS2-0.68uF/100V	WIMA	金屬化聚脂膜電容	0.68uF	±5%	100VDC/63VAC	5*10*7.2	-55°C to +100°C	5mm
51277	WIMA-MKS2-0.68uF/63V	WIMA	金屬化聚脂膜電容	0.68uF	±5%	63VDC/40VAC	4.5*9.5*7.2	-55°C to +100°C	5mm
51282	WIMA-MKS2-1.5uF/50V	WIMA	金屬化聚脂膜電容	1.5uF	±5%	50VDC/30VAC	4.5*9.5*7.2	-55°C to +100°C	5mm
51283	WIMA-MKS2-1.5uF/63V	WIMA	金屬化聚脂膜電容	1.5uF	±5%	63VDC/40VAC	5.5*11.5*7.2	-55°C to +100°C	5mm
51289	WIMA-MKS2-10uF/16V	WIMA	金屬化聚脂膜電容	10uF	±5%	16VDC/10VAC		-55°C to +100°C	5mm
41990	WIMA-MKS2-1uF/100V	WIMA	金屬化聚脂膜電容	1uF	±10%	100V	7.2*13*7.2mm	-55°C to +100°C	5mm
51279	WIMA-MKS2-1uF/16V	WIMA	金屬化聚脂膜電容	1uF	±5%	16VDC/10VAC	3.5*8.5*7.2	-55°C to +100°C	5mm
51280	WIMA-MKS2-1uF/50V	WIMA	金屬化聚脂膜電容	1uF	±10%	50VDC/30VAC	3.5*8.5*7.2	-55°C to +100°C	5mm
51281	WIMA-MKS2-1uF/63V	WIMA	金屬化聚脂膜電容	1uF	±5%	63VDC/40VAC	5*10*7.2	-55°C to +100°C	5mm
51285	WIMA-MKS2-2.2uF/50V	WIMA	金屬化聚脂膜電容	2.2uF	±5%	50VDC/30VAC	5*10*7.2	-55°C to +100°C	5mm
51286	WIMA-MKS2-3.3uF/50V	WIMA	金屬化聚脂膜電容	3.3uF	±5%	50VDC/30VAC	5.5*11.5*7.2	-55°C to +100°C	5mm
51288	WIMA-MKS2-4.7uF/50V	WIMA	金屬化聚脂膜電容	4.7uF	±5%	50VDC/30VAC	7.2*13*7.2	-55°C to +100°C	5mm
63708	WIMA-MKS2-5600pF/630V	WIMA	金屬化聚脂膜電容	5600pF	±5%	630VDC	4.5*9.5*7.2	-55°C to +100°C	5mm



- 材質：金屬化聚乙烯膜(PET)
- 結構及特性：高[體積/容量]比/具自愈能力
- 典型的應用：DC電路/時振電路/旁路電路/交連偶合/退交連/時基電路



Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
27060	WIMA-MKS4-1.0uF/630V	WIMA	金屬化聚脂膜電容	1.0uF	10%	630Vdc/300Vac	11*21*31.5mm	-55°C to +100°C	27.5mm
51301	WIMA-MKS4-0.015uF/250V	WIMA	金屬化聚脂膜電容	0.015uF	±10%	250V	4*9*13	-55°C to +100°C	10mm
55462	WIMA-MKS4-0.015uF/400V	WIMA	金屬化聚脂膜電容	0.015uF	±10%	400VDC	4*9*13	-55°C to +100°C	10mm
51300	WIMA-MKS4-0.01uF/1000V	WIMA	金屬化聚脂膜電容	0.01uF	±5%	1000V	5*11*13	-55°C to +100°C	10mm
41123	WIMA-MKS4-0.01uF/100V	WIMA	金屬化聚脂膜電容	0.01uF	±5%	100V	2.5*7*10mm	-55°C to +100°C	7.5mm
45052	WIMA-MKS4-0.01uF/400V	WIMA	金屬化聚脂膜電容	0.01uF/	±5%	400V	4*9*13mm	-55°C to +100°C	10mm
51304	WIMA-MKS4-0.022uF/1000V	WIMA	金屬化聚脂膜電容	0.022uF	±5%	1000V	5*11*18mm	-55°C to +100°C	15mm
51303	WIMA-MKS4-0.022uF/400V	WIMA	金屬化聚脂膜電容	0.022uF	±5%	400V	4*9*13mm	-55°C to +100°C	10mm
51307	WIMA-MKS4-0.033uF/1000V	WIMA	金屬化聚脂膜電容	0.033uF	±5%	1000V	6*12.5*18	-55°C to +100°C	15mm
51305	WIMA-MKS4-0.033uF/250V	WIMA	金屬化聚脂膜電容	0.033uF	±5%	250V	4*9*13	-55°C to +100°C	10mm
51324	WIMA-MKS4-0.033uF/400V	WIMA	金屬化聚脂膜電容	0.033uF	±5%	400V	4*9*13	-55°C to +100°C	10mm
41124	WIMA-MKS4-0.047uF/100V	WIMA	金屬化聚脂膜電容	0.047uF	±5%	100V	2.5*7*10mm	-55°C to +100°C	7.5mm
51306	WIMA-MKS4-0.047uF/250V	WIMA	金屬化聚脂膜電容	0.047uF	±10%	250V	4*9*13	-55°C to +100°C	10mm
51309	WIMA-MKS4-0.068uF/100V	WIMA	金屬化聚脂膜電容	0.068uF	±5%	100V	2.5*7*10	-55°C to +100°C	7.5mm
51310	WIMA-MKS4-0.068uF/250V	WIMA	金屬化聚脂膜電容	0.068uF	±5%	250V	4*9*13	-55°C to +100°C	10mm
51311	WIMA-MKS4-0.068uF/400V	WIMA	金屬化聚脂膜電容	0.068uF	±5%	400V	5*11*18mm	-55°C to +100°C	15mm

