



PSI/PSR聚苯烯膜-箔式電容(有感型)

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- Low DF(Dissioation Factor) and high IR (Insulation Resistance)
- Low Temperature Coefficient
- Small Dissipation Factor
- High stability of capacitance and DF versus temperature and frequency
- Electrode and lead are spot welded series resistance is minimized
- High precision of capacitance is available
- Excellent environmental performance
- Ideal for commercial, industrial, and measuring instruments applications in high frequency circuits


Part No.	Product No.	說明	Capacitance	Tolerance(±)	Rated Volt.
23684	PSA1000J500V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	1000PF	±5%	500Vdc
23681	PSA100J500V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	100PF	±5%	500Vdc
23685	PSA2200J500V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	2200PF	±5%	500Vdc
49760	PSA220J400V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	220PF	±5%	400Vdc
23682	PSA220J500V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	220PF	±5%	500Vdc
23686	PSA3300J500V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	3300PF	±5%	500Vdc
14031	PSA330J400V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	330PF	±5%	400Vdc
23687	PSA4700J500V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	4700PF	±5%	500Vdc
23683	PSA470J500V	PSA (卧式)-聚苯乙 烯膜-箔式電容(有感型)	470PF	±5%	500Vdc



- Low DF(Dissioation Factor) and high IR (Insulation Resistance)
- Low Temperature Coefficient
- Small Dissipation Factor
- High stability of capacitance and DF versus temperature and frequency
- Electrode and lead are spot welded series resistance is minimized
- High precision of capacitance is available
- Excellent environmental performance
- Ideal for commercial, industrial, and measuring instruments applications in high frequency circuits

Part No.	Product No.	說明	Capacitance	Tolerance(±)	Rated Volt.
23677	PSR1000J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	1000PF	±5%	400Vdc
49757	PSR1000J500V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	1000PF	±5%	500Vdc
23673	PSR100J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	100PF	±5%	400Vdc
23678	PSR2200J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	2200PF	±5%	400Vdc
23674	PSR220J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	220PF	±5%	400Vdc
23679	PSR3300J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	3300PF	±5%	400Vdc
14032	PSR330J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	330PF	±5%	400Vdc
23680	PSR4700J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	4700PF	±5%	400Vdc
23675	PSR470J400V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	470PF	±5%	400Vdc
49756	PSR470J500V	PSR (直式)-聚苯乙 烯膜-箔式電容(有感型)	470PF	±5%	500Vdc

EVOX RIFA_金屬化聚脂膜電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- Dielectric: polyester film (polyethylene terephthalate)
- Plates: aluminum layer deposited by evaporation under vacuum
- Winding: non-inductive type
- Leads: tinned wire
- Protection: polyester tape wrapping and thermosetting resin end fill

Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C
64142	A50CK5100AA00J	KEMET	金屬化聚脂膜電容	10.0uF	±5%	50VDC/30VAC	12.0*20.5mm	+85°C
64143	A50IT4220AA60K	KEMET	金屬化聚脂膜電容	2.2uF	±10%	250VDC/160VAC	11.0*33.0mm	+85°C
64144	A50IT4220ZM60J	KEMET	金屬化聚脂膜電容	2.2uF	±5%	250VDC/160VAC	11.0*33.0mm	+85°C



- 引線薄膜電容器MMK系列
- 技術應用：旁路，信號耦合，通用的高可靠性

Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
23665	MMK10-102K1000A01L4	EVOX RIFA	金屬皮膜電容	0.001uF	±10%	1000Vdc/250Vac	4*9*13*10mm	-55°C to +100°C	10mm
63838	MMK10-104K100A01L4	EVOX RIFA	金屬化聚脂膜電容	0.10uF	±10%	100VDC/63VAC	4.0*9.0*13.0mm	-55°C to +100°C	10mm
22267	MMK10-104M250A01L4	EVOX RIFA	金屬皮膜電容	0.1uF	±20%	250Vdc/160Vac	9*13*4*10mm	-55°C to +100°C	10mm
63839	MMK10-153K630A01L4	EVOX RIFA	金屬化聚脂膜電容	0.015uF	±10%	630VDC/220VAC	4.0*9.0*13.0mm	-55°C to +100°C	10mm
63860	MMK10-223K400A01L4	EVOX RIFA	金屬化聚脂膜電容(PEN)-SMD 型	0.022uF	±10%	400VDC/200VAC	4.0*9.0*13.0mm	-55 °C to +100 °C	10mm
63862	MMK10-563K630A04L4	EVOX RIFA	金屬化聚脂膜電容(PEN)-SMD 型	0.056uF	±10%	630VDC/220VAC	6.0*12.0*13.0mm	-55°C to +100°C	10mm

