



EVOX RIFA_金屬化聚脂膜電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- The highest possible safety regarding active and passive flammability
 - Self-extinguishing UL 94V-0 encapsulation material
 - Excellent self-healing properties
- Ensures long life even when subjected to frequent overvoltages

Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
64284	PME271M610KR30	EVOX RIFA	雙面金屬膜脈衝電容	0.1uF	±10%	275Vac	7.6*14.0*24.0mm	110°C	20.3mm
41170	PME271M622KR30	EVOX RIFA	雙面金屬膜脈衝電容	0.22uf	±10%	275VAC	11.3*16.5*24mm	110°C	



TYPICAL APPLICATIONS

The capacitors are intended for use as interference suppressors in Y2(line-to-earth) applications

CONSTRUCTION

Multi-layer metallized paper. Encapsulated and impregnated in self-extinguishing material meeting the requirements of UL 94V-0

Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
41184	PME271Y415MR30AS	EVOX RIFA	金屬化聚脂膜電容	0.0015uf	±20%	250VAC--Y2	3.9*7.5*13.5mm		
41187	PME271Y433MR30	EVOX RIFA	金屬化聚脂膜電容	0.0033uf	±10%	250VAC-Y2	4.1*8.2*13.5mm		
64050	PME271Y468MR30	EVOX RIFA	金屬膜脈衝電容	0.0068uF	±20%	250VAC	5.2*10.5*18.5mm	+100°C	15.2mm
41189	PME271Y510MR30	EVOX RIFA	金屬化聚脂膜電容	0.01uf	±10%	250VAC/	5.2*10.5*18.5mm		
64052	PME271Y515MR30	EVOX RIFA	金屬膜脈衝電容	0.015uF	±20%	250VAC	5.5*11.0*18.5mm	+100°C	15.2mm
41172	PME271Y610MR30	EVOX RIFA	金屬化聚脂膜電容	0.1uF	±20%	250VAC	12.1*19*30.5*25.4mm		
64053	PME271YA4220MR30	EVOX RIFA	金屬膜脈衝電容	0.0022uF	±20%	300VAC	3.9*7.5*13.5mm	+115°C	10.2mm



- EMI suppressor, class Y1, metallized paper capacitors
- Safety capacitor, ceramic replacement
- 470-4700pF, 440VAC/480VAC, +115°C, test voltage 4000VAC 60s
- Replaces PME294


Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C	Pitch(mm)
41173	PME295RB3470MR30	EVOX RIFA	Y1 金屬化聚脂膜電容	470pf/0.00047uF	±20%	440/480VAC	5.5*12.5*18mm	-40 to +115°C	15.0mm
64062	PME295RB3560MR30	EVOX RIFA	金屬膜脈衝電容	560pF	±20%	440/480VAC	5.5*12.5*18.0mm	-40 to +115°C	15.0mm
48289	PME295RB4220MR30	EVOX RIFA	EVOX RIFA_金屬化聚脂膜電容	2200pf	± 20%	440 VAC 50/60 Hz (ENEC)/480 VAC 50/60 Hz (UL, CSA)			
64073	PME295RB4270MR30	EVOX RIFA	金屬膜脈衝電容	2700pF	±20%	440/480VAC	7.5*14.5*18.0mm	-40 to +115°C	15.0mm



- RC unit, class X1, metallized paper with integrated resistor
- 0.022-0.1uF, 100Ω, 250VAC, +85°C

Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L
41175	PMR210MB5220M100R30	EVOX RIFA	EVOX RIFA_金屬化聚脂膜電容	0.022uF	±10%	100Ω250VAC	7.3*13*19mm

EVOX RIFA_金屬化聚丙稀電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


TYPICAL APPLICATIONS

General purpose coupling, bypass, filtering, timing, time constant, oscillation circuits. Suitable for filters in PLL circuits

CONSTRUCTION

Metallized polypropylene sulphide (PPS) non-encapsulated stacked film capacitor

Part No.	Product No.	製造廠商	說明	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C
41590	ERS0603HUX222J165	EVOX RIFA	SMD 金屬化多層薄膜電容	0.0022uF	± 2%	16v	0.8*0.7*1.6	-55 to +125°C
41591	ERS0805HUX471J505	EVOX RIFA	SMD 金屬化多層薄膜電容	0.0047uF	± 2%	50v	1.25*0.9*2.0	-55 to +125°C
41583	ERS0805HUX821J505	EVOX RIFA	SMD 金屬化多層薄膜電容	0.00082UF	± 5%	50V	1.25*0.9*2.0	-55 to +125°C
41589	ERS1206HUX273J165	EVOX RIFA	SMD 金屬化多層薄膜電容	0.027uF	± 2%	16v	1.6*1.1*3.2	-55 to +125°C
41588	ERS1260HUX153J165	EVOX RIFA	SMD 金屬化多層薄膜電容	0.015uF	± 2%	16v	1.6*0.9*3.2	-55 to +125°C



電話：台灣：886-3-5753170
 傳真：台灣：886-3-5753172
 郵箱：台灣：sale@100y.com.tw

深圳：86-755-83298787
 深圳：86-755-83640655
 深圳：100y@vip.163.com

上海：86-21-34970699
 上海：86-21-64605107
 上海：100y-1@vip.163.com