




## EVOX RIFA\_金屬化聚丙烯電容

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


## TYPICAL APPLICATIONS

High frequency and high voltage applications with high current stress, such as deflection circuits in TV-sets, protection circuits in SMPS and in electronic ballasts

## CONSTRUCTION

Series winding with polypropylene dielectric and double metallized polyester film as electrodes. Encapsulation in self-extinguishing material meeting the requirements of UL94V-0



Part No.	Product No.	製造廠商	說明	Pitch(mm)	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C
41592	PHE428RB4330JR06	EVOX RIFA	Double metallized film pulse capacitor, polypropylene dielectric	LEAD SPACING 15 MM	0.0033uF	±5%	1600V	55*10.5*18.0	-55°C to +105°C



- EMI suppressor, class X2, metallized polypropylene
- 0.01-10µF, 300VAC, +105°C
- New improved design: small dimensions including low profile capacitors



Part No.	Product No.	製造廠商	說明	Pitch(mm)	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C
32430	PHE840EB6100MB05R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.10uF	±20% standard, ±10% option	300VAC	18.0*12.5*5.5	-55 to +105°C
64039	PHE840ED6330MD17R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容	22.5mm	0.33uF	±20%	300VAC	7.0*16.5*26mm	-55 to +105°C
32431	PHE840EX6220MB06R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.22uF	±20% standard, ±10% option	300VAC	18.0*14.5*7.5	-55 to +105°C



- EMI suppressor, class X2, metallized polypropylene
- 0.01-10.0µF, 275/280VAC, +105°C
- Small dimensions including low profile capacitors



Part No.	Product No.	製造廠商	說明	Pitch(mm)	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C
41156	PHE840MA5470MA02R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.1uF	±10%	275/280VAC	4.5*10.5*13*10mm	-55 to +105°C
28270	PHE840MA6100MA04R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.1uF	±20%	275/280VAC	13*12*6mm	-55 to +105°C
41157	PHE840MB5680MB04R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.068uF	±10%	275/280VAC	5.5*10.5*18mm	-55 to +105°C
28271	PHE840MB6100MB05R05	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.1uF	±20%	275/280VAC	18*12.5*15mm	-55 to +105°C
28274	PHE840MB6100MB05R25	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.1uF	±20%	275/280VAC	18*12.5*15mm	-55 to +105°C
41158	PHE840MB6220MB12R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.22uF	±10%	275/280VAC	8*15*18mm	-55 to +105°C
28275	PHE840MB6470MB16R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.47uF	±20%	275/280VAC	18*19*11mm	-55 to +105°C
41160	PHE840MD6220MD13R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.22uF	±10%	275/280VAC	6.5*14.5*26mm	-55 to +105°C
28276	PHE840MD7150MD19R06	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		1.5uF	±20%	275/280VAC	26*24.5*15.5	-55 to +105°C
41161	PHE840MD7150MD19R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		1.5uF	±10%	275/280VAC	15.5*24.5*26mm	-55 to +105°C
64042	PHE840MF7120MF03R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容	27.5mm	1.2uF	±20%	275/280VAC	13.5*23.0*31.5mm	-55 to +105°C
41162	PHE840MH6330MB17R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.33uF	+/-10%	275/280VAC	13*12.5*18mm	-55 to +105°C
28277	PHE840MH6330MB17R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.33uF	±20%	275/280VAC	18*12.5*13mm	-55 to +105°C
41163	PHE840MP6100MA05R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.1uF	±10%	275/280VAC	9.5*7.5*13mm	-55 to +105°C
41164	PHE840MR7220MR05R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		2.2uF	±10%	275/280VAC	13*24*41mm	-55 to +105°C
28278	PHE840MX6100MR05	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容	10mm	0.1uF	±20%	275/280VAC		-55 to +105°C
28279	PHE840MX6220MB06R17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.22uF	±20%	275/280VAC		-55 to +105°C
28280	PHE840MX6330MR17	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.33uF	±20%	275/280VAC		-55 to +105°C
28281	PHE840MY6470MD14R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		0.47uF	±20%	275/280VAC	20*16*22mm	-55 to +105°C
28282	PHE840MY6680MD15R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容	22.5mm	0.68uF	±20%	275/280VAC	21.5*26*11mm	-55 to +105°C
41167	PHE840MY7100MD16R06L2	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容		1.0uF	±10%	275/280VAC	11*21.5*26mm	-55 to +105°C
28283	PHE840MZ7100MR06	EVOX RIFA	EMI suppressor, class X2 金屬聚丙烯膜電容	27.5mm	1uF	±20%	275/280VAC	22.5*31.5*11.5mm	-55 to +105°C



## TYPICAL APPLICATIONS

For worldwide use as electromagnetic interference suppressor in all X1 and across-the-line applications  
Not for use in series with the mains.

## CONSTRUCTION

Metallized polypropylene winding, encapsulated in self-extinguishing material meeting the requirements of UL94V-0



Part No.	Product No.	製造廠商	說明	Pitch(mm)	Capacitance	Tolerance(±)	Rated Volt.	W*H*L	Temp. Range°C
64045	PHE841ED6100MR06L2	EVOX RIFA	EMI suppressor, class X1 金屬聚丙烯膜電容	22.5mm	0.1uF	±20%	330VAC	7.0*16.5*26.0mm	-40 to +100°C

