



立式陶瓷電容



- 特點**
- 工作溫度範圍上限保證值達125°C(UL:85°C)
 - 介電強度：AC4000V
 - 經UL/CSA/VDE/BSI/SEMCO/DEMCO/FIMKO/NEMKO/ESTI/IMQ認證的X1/Y1等級電容器
 - 依據標準UL1492,IEC60065和IEC60950,可與需要強化絕緣和雙重絕緣的電氣用品中的組件一起使用
 - 塗有阻燃環氧樹脂塗層(符合UL94V-0規格)
 - 自動插入型，成本效益顯著



Part No.	Product No.	製造廠商	說明	Capacitance	Voltage DCV	Lead Pitch (mm)	Tolerance(±)	Dielectric
62545	DE1E3KX222MN5AA01	MuRata	陶瓷電容器	2200pF	250V	10.0mm ±1.0mm	±20%	陶瓷



Part No.	Product No.	說明	Capacitance	Voltage DCV	Lead Pitch (mm)	Tolerance(±)	Dielectric
10881	NPO-15J-50V	立式陶瓷電容	15PF	50V	5	±5%	NPO
3983	Y5V-104Z-50V	立式陶瓷電容	0.1uF	50	5	+80-20%	Y5V

可調電容 立式陶瓷可調電容



- FEATURES**
- As well as applications to small sized electronic apparatus, this series is designed for easy handling and is available with a variety of adjustment method(top, bottom, side and double sides)
- wide mounting sizes and type of adjustment available
- lots of capacity ranges, 2pF through 90pF
- sturdy mechanical structure against vibration or shock

Part No.	Product No.	說明	Cap. Max.	Cap. Min.	Volt.	Case Color
49268	HCV05A050	全陶式可調電容	6pF	2pF	100Vdc	White



- Recommended Applications**
- TV and VTR
 - Audio equipment
 - Electronic equipment
- Features**
- Color coded case permits easy identification
 - Sealed construction prevent the penetration of flux and dust
 - Wide range of nominal capacitance

Part No.	Product No.	說明	Cap. Max.	Cap. Min.	Volt.	Case Color
40098	HS-HCV06E300	可調電容(半陶)	30pF	6.5pF	100Vdc	Green



Part No.	Product No.	說明	Cap. Max.	Cap. Min.	Volt.	Case Color
9533	HSE-HV05A0501	全陶式可調電容	5pF	2pF	100Vdc	White
9531	HSE-HV05C100	全陶式可調電容	10pF	3pF	100Vdc	White



- 額定電壓：100V
- 最大電壓：200V
- 絕緣電阻：100000MΩ
- 旋轉力矩：10~30mN.m
- 工作環境溫度：15~35°C
- 相對濕度：45%~75%
- 大氣壓強：66~106KPa

墊圈	聚四氟乙烯	乳白色
定片	氧化鋁	白色
動片	陶瓷	多種
簧片	304不銹鋼	白色
140引線	銅合金	白色
139引線	銅合金	白色
轉軸	銅合金	白色

Part No.	Product No.	說明	Cap. Max.	Cap. Min.	Volt.
38945	JML05-1-2/5	全陶式可調電容	5.0pF	2.0pF	100vdc
64078	JML05-1-5/20	全陶式可調電容	20pF	5pF	100vdc
38952	JML05-1-7/30	全陶式可調電容	30.0pF	7.0pF	100vdc
38955	JML05-2-15/100	全陶式可調電容	100pF	15.0pF	100vdc
38949	JML05-2-3/10	全陶式可調電容	10.0pF	3.0pF	100Vdc
38950	JML05-2-5/20	全陶式可調電容	20.0pF	5.0pF	100Vdc
38951	JML05-2-6/25	全陶式可調電容	25pF	6pF	100Vdc
38953	JML05-2-8/50	全陶式可調電容	50.0pF	8.0pF	100vdc
38954	JML05-2-9/60	全陶式可調電容	60.0pF	9.0pF	100vdc

● 假如您需要適合特殊用途的產品或更詳細的技術資料，我們的業務專員將會透過電話，傳真，E-mail,幫助您

