



## Panasonic\_F系列金電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


Panasonic

Part No.	Product No.	製造廠商	說明	H*Dia	V.DC	Capacitance (F)	Lead Pitch(mm)
18596	EECF5R5H104	Panasonic	金電容	9.5*13.5mm	5.5V	0.10F	5mm
18599	EECF5R5H105	Panasonic	金電容	9.5*21.5mm	5.5V	1.00F	5mm
18595	EECF5R5H473	Panasonic	金電容	6*13.5mm	5.5V	0.047F	5mm
18597	EECF5R5H474	Panasonic	金電容	9.5*21.5mm	5.5V	0.47F	5mm
18598	EECF5R5H684	Panasonic	金電容	9.5*21.5mm	5.5V	0.68F	5mm
40892	EECF5R5U155	Panasonic	Panasonic_F 系列金電容	8*21.5	5.5V	1.5F	5mm

## Panasonic\_NF 系列金電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- 浸液型雙層電解電容器 (活性碳電極和有機電解質)
- 適用於IC(集成電路)存儲備份(μA系列負載)
- 不象電池一樣需要充電、放電電路, 因此不會充電過足或不滿  
充電/放電循環多於100,000次
- 容積效率(SD系列比SG系列小30%, SG系列比NF系列小50%)
- 壽命比蓄電池長

Panasonic

Part No.	Product No.	製造廠商	說明	H*Dia	Lead Pitch(mm)	V.DC	Capacitance (F)
28339	EECF5R5U104	Panasonic	金電容	13.5*7.5mm	5	5.5V	0.1F
28341	EECF5R5U105	Panasonic	金電容	21.5*8mm	5	5.5V	1F
28340	EECF5R5U224	Panasonic	金電容	21.5*7.5mm	5	5.5V	0.22F
28338	EECF5R5U473	Panasonic	金電容	21.5*7.5mm	5	5.5V	0.047F
15202	EECF5R5U474	Panasonic	金電容	0.47F	5.5V	21.5*8mm	5

## ELNA\_金電容

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


Has a total withstand voltage rating of 5.5V. Utilizing ELNA's unique flat spring technology, which enhances the reliability of the internal coin cells, this series is ideal for a wide range of applications from consumer appliances to sophisticated instrumentation

ELNA  
AMERICA, INC.

Part No.	Product No.	製造廠商	說明	H*Dia	Lead Pitch(mm)	V.DC	Capacitance (F)
20125	DB-5R5D104	ELNA	金電容	13.5 x 7.5	5mm	5.5V	0.1F
20126	DB-5R5D105	ELNA	金電容	8*21.5	5mm	5.5V	1F
38958	DB-5R5D224	ELNA	金電容	13.5 x 7.5 mm	5mm	5.5V	0.22F
38959	DB-5R5D334	ELNA	金電容	13.5 x 7.5 mm	5mm	5.5V	0.33F
38956	DB-5R5D473	ELNA	金電容	13.5 x 7.5 mm	5mm	5.5V	0.047F
38960	DB-5R5D474	ELNA	金電容	21.5*8.0mm	5mm	5.5V	0.47F



- High voltage tolerant (6.3V guaranteed) and highly reliable
- Ideal for backing up of Li-battery-backed equipment such as cameras, video and telephone sets

ELNA  
AMERICA, INC.

Part No.	Product No.	製造廠商	說明	H*Dia	Lead Pitch(mm)	V.DC	Capacitance (F)
59165	DK-6R3D473T	ELNA	金電容	9.5*13.5mm	5mm	6.3V	0.047F



- Can be used as a rechargeable battery and ideal for backing up purposes
- Capable of several hundreds of thousands of charge/discharge cycles; free from throwaway disposal
- It does not contain toxic materials such as nickel and cadmium

ELNA  
AMERICA, INC.

Part No.	Product No.	製造廠商	說明	H*Dia	Lead Pitch(mm)	V.DC	Capacitance (F)
38966	DX-5R5H104	ELNA	金電容	11.5*5.0mm	5mm	5.5V	0.1F
41466	DX-5R5H105	ELNA	金電容	Dia:20.5mm	5mm	5.5V	1.0F
38969	DX-5R5H224	ELNA	金電容	11.5*5.0mm	5mm	5.5V	0.22F
38972	DX-5R5H334	ELNA	金電容	11.5*5.0mm	5mm	5.5V	0.33F
38963	DX-5R5H473	ELNA	金電容	11.5*5.0mm	5mm	5.5V	0.047F

- 每月上百種新產品入庫中, 若您在網上PDF目錄上找不到您需要的元件, 歡迎您來電或在我們網站查詢
- 您也可以請我們代購產品, 歡迎您的來電
- 商品規格, 外型若有不符, 以出貨品為主

