



S端子連接線

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- These gold plated super video cables are used in Home Theater applications including DSS receivers, VCRs, PVRs, Camcorders, and DVD players
- Low-loss, fully shielded and molded
- 4 contact with din plug to plug
- Y/C video and S-VHS are other terms for s-video

Part No.	Product No.	說明	Length
9114	6050	S 端子線 4P (真空包)	3 尺
2631	6050A	S 端子線 4P (真空包)	6 尺
2632	6050B	S 端子線 4P (真空包)	12 尺
7695	6050C	S 端子線 4P (真空包)	20 尺
12968	6050D	S 端子線 4P (真空包)	30 尺



- S 端子音源信號<-->梅花接頭 左右聲道
- 長度：5尺

Part No.	Product No.	說明	Length
5245	6052	S 端子+2RCA 線	5 尺



Part No.	Product No.	說明	Length
36619	6187A	S 端子線 4P	5 尺



- S Video male to three (3) rca males
- Length:1.5M

Part No.	Product No.	說明	Length
15471	6203	S 端子-3RCA(公)線(真空)	5 尺




- Note book 連接至電視或影像端
- 長度：1.8米



Part No.	Product No.	說明	Length
16229	6211	S 端子+RCA 公線	5 尺

Jack連接頭

d.c. 電源座-插板式

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


Part No.	Product No.	說明	Pin Size
17466	CSCD-523C	DC Power Jack	2.0mm



Specification

- Contact resistance: 30m ohm. Max. At AC 100Ma max. 1KHz
- Insulation resistance: 100M ohm min. At 500VDC
- Rating: DC 12V, 2A max; AC 100V, 1A max
- Dielectric withstanding voltage: 500V AC(rms) for 1 minute
- Insertion force: 3.0Kg maximum
- Extraction force: 0.3Kg minimum

Material

Housing: PBT UL94V-0
Center Pin: Copper Alloy
Terminal: Copper Alloy

Part No.	Product No.	說明	Pin Size	重量
3817	KD-011 1.0 ϕ	DC 公座	ϕ 1.0mm	0.6g
3818	KD-011A	DC 公座	ϕ 1.3mm	0.6g

● 假如您需要適合特殊用途的產品或更詳細的技術資料，我們的業務專員將會透過電話，傳真，E-mail,幫助您

