





F 對各款連結頭的 (T型或一字型) 轉換頭


詳細產品規格請點擊www.100y.com.tw




Part No.	Product No.	說明
3268	MCI-7236	F Quick Male To F Female




WITH WASHER & NUTS		W/O WASHER & NUTS	
Part No.	Product No.	說明	重量
2947	MCI-7242A	F Double Female	5g



Part No.	Product No.	說明	重量
6336	MCI-7250	F Female to PAL Quick Female	9.9g




Part No.	Product No.	說明
2948	MCI-7254	F Female To 3.5MO Male



Part No.	Product No.	說明	重量
3269	MCI-7258	F Male To RCA Female	10.9g

鎖面板式 F公 / 母焊接頭

詳細產品規格請點擊www.100y.com.tw




WITH WASHER & NUTS		W/O WASHER & NUTS	
Part No.	Product No.	說明	
2398	MCI-7221A	F 母 Bulkhead	


N 連接頭

詳細產品規格請點擊www.100y.com.tw

N 壓接公 / 母頭系列



Part No.	Product No.	說明	適用線材	Impedance (Ω)
3270	MCI-7301A-RG58/U	N Male Crimp Type	RG58/U	50Ω



- Voltage rating: AC 500V
- Withstanding Voltage: AC 1,500V one minute
- Insulation resistance: 1,000MΩ min at DC 500V
- Contact resistance: 3mΩ max. At DC 1A
- Frequency range: 0-2 Ghz



Part No.	Product No.	製造廠商	說明	適用線材	重量
58084	N-301D-BNGTA	PLT	Nseries RF CO-AXIAL connectors	RG-8.9/U.213	73.9g

