



PCB連接座 (Solt)

2.54mm 插板式SOLT 180°



- 絕緣體：Glass-Fiber P.B.T.(UL94V-0)
- 接點材質：Phosphor Bronze(P) or Brass (B)
- 鍍層：Gold plating Over Nickel

- 絕緣阻抗：5000MΩ min at 500VDC
- 介質耐壓：1000 V-AC/ 1 min
- 額定電流：3A
- 接點電阻：20mΩ max
- 工作溫度：-55°C to 105°C

詳細產品規格請點擊www.100y.com.tw

Part No.	Product No.	說明	Contact Centers	Mounting Ears Yes/No	Pins
39679	B22	插板式 SOLT	Tin	No	30
60166	B22-3	插板式 SOLT	Tin	NO	2*12
2919	B23	插板式 SOLT 2*18Pins	Tin	No	36
2922	B24	插板式 SOLT 2*22Pins	Tin	No	44
39739	B24-1	插板式 SOLT 2*22Pins	Tin	No	48
4147	B25	插板式 SOLT 2*25Pins	Tin	No	50
4148	B26	插板式 SOLT 2*31Pins	Tin	No	62
61265	B26-2	插板式 SOLT 2*31Pins	Tin	No	64
4150	B27	插板式 SOLT 2*36Pins	Tin	No	72
12545	B27-1	插板式 SOLT 2*35Pins	Tin	NO	70
4149	B28	插板式 SOLT 2*49Pins	Tin	No	98
2310	B29	插板式 SOLT 2*50Pins	Tin	No	100
14413	B30	插板式 SOLT 2*60Pins	Tin	No	120
17469	B38	插板式 SOLT	Tin	No	40
48826	B68	插板式 SOLT 2*7Pins	Tin	No	14

2.54mm 插板式SOLT 90°




- 額定電流：3 Amp. Max.
- 介質耐壓：1000V AC R.M.S./min
- 絕緣電阻：5000M ohms min. At 1000V DC

- 接觸電阻：30m ohms Max
- 工作溫度範圍：-55°C to +105°C
- 外殼：P.B.T.(UL 94V-0) Color: Black
- 端子：Copper Alloy

詳細產品規格請點擊www.100y.com.tw

Part No.	Product No.	說明	Pins
22495	B31-2	插板式 SOLT 90°	20*2P



- 額定電流：3 Amp. Max.
- 介質耐壓：1000V AC R.M.S./min
- 絕緣電阻：5000M ohms min. At 1000V DC

- 接觸電阻：30m ohms Max
- 工作溫度範圍：-55°C to +105°C
- 外殼：P.B.T.(UL 94V-0) Color: Black
- 端子：Copper Alloy

Part No.	Product No.	說明	Pins
22494	B53	插板式 SOLT 10*2pins	10*2pins

2.54mm 壓排式SOLT



- Reinforced card-edge resists mouth bowing for consistent contact performance
- Metal cover clips provide superior cover retention
- Bifurcated contacts provide reliable contact with PC boards
- Keying plug 3439-2 provides polarization and/or keying
- Optional strain relief
- RoHS* compliant

詳細產品規格請點擊www.100y.com.tw

Part No.	Product No.	製造廠商	說明	Pins
28926	3358-0001	3M	3M 壓排母頭/SLOT	10P
53917	3461-0001	3M	3M 壓排母頭/SLOT	20P
53918	3462-0001	3M	3M 壓排母頭/SLOT	26P
28927	3463-0001	3M	3M 壓排母頭/SLOT	34P
53919	3464-0001	3M	3M 壓排母頭/SLOT	40P



- 額定電流：3A
- 絕緣電阻：5000MΩ min
- 接觸電阻：20mΩ max.
- 介質耐壓：AC500V
- 工作溫度範圍：-40°C to +105°C
- 接點材質：Phosphor Bronze
- 絕緣材質：P.B.T. UL 94V-0

Part No.	Product No.	說明	Pins
3811	D02-16P	壓排母頭/SLOT 16P	2*8P
4158	D02-20P	壓排母頭/SLOT 20P	2*10P
4163	D02-26P	壓排母頭/SLOT 26P	2*13P
4164	D02-34P	壓排母頭/SLOT 34P	2*17P
4165	D02-40P	壓排母頭/SLOT 40P	2*20P
4166	D02-50P	壓排母頭/SLOT 50P	2*25P
4167	D02-60P	壓排母頭/SLOT 60P	2*30P
2367	D02-62P	壓排母頭/SLOT 62P	2*31P

