



## 2.54mm IDC 壓排公插頭

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- 外殼：30% Glass filled PBT UL94V-0
- 接點：Brass
- 鍍層：Selective gold plated: gold plated on mating area and nickel plated on wire cutting area
- 線：1.27mm(0.050")pitch flat cable
- 額定電流：1 AMP
- 絕緣電阻：5000MΩmin. At DC 500V
- 接點電阻：20mΩmax. At DC 100mA
- 工作溫度範圍：-55°C~+105°C

Part No.	Product No.	說明	Contacts
3762	D08-10P	IDC 壓排牛角公頭	10P
4185	D08-14P	IDC 壓排牛角公頭	14P
4191	D08-16P	IDC 壓排牛角公頭	16P
3803	D08-20P	IDC 壓排牛角公頭	20P
17848	D08-24P	IDC 壓排牛角公頭	24P
4184	D08-26P	IDC 壓排牛角公頭	26P
4183	D08-34P	IDC 壓排牛角公頭	34P
2363	D08-40P	IDC 壓排牛角公頭	40P
4186	D08-50P	IDC 壓排牛角公頭	50P
3812	D08-60P	IDC 壓排牛角公頭	60P
4187	D08-64P	IDC 壓排牛角公頭	64P



Part No.	Product No.	說明	Contacts
48538	D08-50PE	IDC 壓排牛角公頭-附螺絲固定孔	50P



- Fully shrouded provides ultimate reliability
- With polarization
- Mounting ears optional
- 外殼：30% Glass filled PBT UL94V-0
- 接點：Brass
- 鍍層：Selective gold plated: gold plated on mating area and nickel plated on wire cutting area
- 線：1.27mm(0.050")pitch flat cable
- 額定電流：1AMP
- 絕緣電阻：5000MΩmin. At DC500V
- 接點電阻：20mΩmax. At DC 100mA
- 工作溫度範圍：-55°C~+105°C

Part No.	Product No.	說明	Contacts
13969	D09-10P	IDC 壓排牛角公頭	64P
28759	D09-14P	簡易壓排公頭 34P(附耳朵)	14P
28760	D09-16P	簡易壓排公頭 34P(附耳朵)	16P
28761	D09-20P	簡易壓排公頭 34P(附耳朵)	20P
28762	D09-26P	簡易壓排公頭 34P(附耳朵)	26P
28763	D09-30P	簡易壓排公頭 30P	30P
12062	D09-34P	簡易壓排公頭 34P	34P
28764	D09-40P	簡易壓排公頭 40P	40P
28765	D09-50P	簡易壓排公頭 50P	50P
28766	D09-60P	簡易壓排公頭 60P	60P
28767	D09-64P	簡易壓排公頭 64P	64P



Part No.	Product No.	說明	Contacts
30387	D09-10PE	簡易壓排公頭 10P(有定位孔)	10P
30386	D09-14PE	簡易壓排公頭 14P(有定位孔)	14P
30385	D09-16PE	簡易壓排公頭 16P(有定位孔)	16P
30384	D09-20PE	簡易壓排公頭 20P(有定位孔)	20P
30383	D09-26PE	簡易壓排公頭 26P(有定位孔)	26P
30382	D09-30PE	簡易壓排公頭 30P(有定位孔)	30P
30381	D09-34PE	簡易壓排公頭 34P(有定位孔)	34P
30380	D09-40PE	簡易壓排公頭 40P(有定位孔)	40P
30379	D09-50PE	簡易壓排公頭 50P(有定位孔)	50P
30378	D09-60PE	簡易壓排公頭 60P(有定位孔)	60P
30377	D09-64PE	簡易壓排公頭 64P(有定位孔)	64P

## 3M\_2.54mm IDC 壓排公插頭

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- 絕緣體：30% Glass fiber PBT
- 接點針：Copper alloy
- 額定電流：1AMP
- 絕緣電阻：1000MQ Min at 500VDC
- 接點電阻：10mΩ Max
- 介質電壓：500V AC for one minute
- 工作溫度範圍：-40°C to +105°C

3M

Part No.	Product No.	製造廠商	說明	Contacts
16824	4234-0000LCSC/0300	3M	壓排公頭 (附固定座)	34P



產品圖片與說明僅供參考，如需更詳細的產品信息請聯絡我們


 電話：台灣：886-3-5753170  
 傳真：台灣：886-3-5753172  
 郵箱：台灣：sale@100y.com.tw

 深圳：86-755-83298787  
 深圳：86-755-83640655  
 深圳：100y@vip.163.com

 上海：86-21-34970699  
 上海：86-21-64605107  
 上海：100y-1@vip.163.com

10-08