



2.00mm IDC簡易公座180°



- Insulator: Nylon-6T G.F
- Contact Pin: Brass Square Pin
- Plated: Gold plated
- Tin plated

- Current Rate: 1 AMP
- Insulation Resistance: 5000MΩ Min at DC500V
- Contact Resistance: 20mΩ max at dc 100mA
- Operation Temperature: -55°C~+105°C

| Part No. | Product No. | 說明 | Contacts |
|----------|-------------|------|----------|
| 46998 | D62-26P | 牛角公座 | 26P |
| 37776 | D62-40P | 牛角公座 | 40P |
| 16601 | D62-44P | 牛角公座 | 44P |

詳細產品規格請點擊www.100y.com.tw

2.00mm SMD IDC簡易公座180°



- Insulator: Nylon-6T G.F
- Contact Pin: Brass Square Pin
- Plated: Gold plated
- Tin plated

- Current Rate: 1 AMP
- Insulation Resistance: 5000MΩ Min at DC500V
- Contact Resistance: 20mΩ max at dc 100mA
- Operation Temperature: -55°C~+105°C

| Part No. | Product No. | 說明 | Contacts |
|----------|-------------|-----------------|----------|
| 56933 | D62-20P-SMD | 2.00mm SMD 牛角公座 | 20P |
| 45279 | D62-44P-SMD | 2.00mm SMD 牛角公座 | 44P |

詳細產品規格請點擊www.100y.com.tw

2.54mm插板式壓排IC座



| Part No. | Product No. | 製造廠商 | 說明 | Contacts |
|----------|-------------|------|-------------------------------|-----------------|
| 63720 | 103956-2 | Tyco | CONN RECPT 3POS 100 POLAR TIN | AMPMODUR(R) MTE |

詳細產品規格請點擊www.100y.com.tw



- 外殼: 30% Glass filled PBT UL94V-0
- 接點: Brass or Phosphor bronze
- 鍍層: Selective gold plated: gold plated on mating area and nickel plated on wire cutting area
- 線: 1.27mm(0.050")pitch flat cable

- 額定電流: 1 AMP
- 絕緣電阻: 5000MΩmin. At DC 500V
- 接點電阻: 20mΩmax. At DC 100mA
- 工作溫度範圍: -55°C~+105°C

| Part No. | Product No. | 說明 | Contacts | Width(inch) |
|----------|-------------|---------|----------|-------------|
| 5787 | C21-10P | 壓排 IC 座 | 10P | 0.1*0.1 |
| 8741 | C21-14P | 壓排 IC 座 | 14P | 0.1*0.1 |
| 8742 | C21-16P | 壓排 IC 座 | 16P | 0.1*0.1 |
| 8743 | C21-20P | 壓排 IC 座 | 20P | 0.1*0.1 |
| 8745 | C21-24P | 壓排 IC 座 | 24P | 0.1*0.1 |
| 8744 | C21-26P | 壓排 IC 座 | 26P | 0.1*0.1 |
| 8746 | C21-30P | 壓排 IC 座 | 30P | 0.1*0.1 |
| 5972 | C21-34P | 壓排 IC 座 | 34P | 0.1*0.1 |
| 8747 | C21-40P | 壓排 IC 座 | 40P | 0.1*0.1 |



- 外殼: 30% Glass filled PBT UL94V-0
- 接點: Brass or Phosphor bronze
- 鍍層: Selective gold plated: gold plated on mating area and nickel plated on wire cutting area

- 線: 1.27mm(0.050")pitch flat cable
- 額定電流: 1 AMP
- 絕緣電阻: 5000MΩmin. At DC 500V
- 接點電阻: 20mΩmax. At DC 100mA
- 工作溫度範圍: -55°C~+105°C

| Part No. | Product No. | 說明 | Contacts | Width(inch) |
|----------|-------------|---------|----------|-------------|
| 3813 | C22-10P | 壓排 IC 座 | 10P | 0.1*0.3 |
| 7823 | C22-14P | 壓排 IC 座 | 14P | 0.1*0.3 |
| 4198 | C22-16P | 壓排 IC 座 | 16P | 0.1*0.3 |
| 4205 | C22-18P | 壓排 IC 座 | 18P | 0.1*0.3 |
| 4201 | C22-20P | 壓排 IC 座 | 20P | 0.1*0.3 |



- 外殼: 30% Glass filled PBT UL94V-0
- 接點: Brass or Phosphor bronze
- 鍍層: Selective gold plated: gold plated on mating area and nickel plated on wire cutting area

- 額定電流: 1 AMP
- 絕緣電阻: 5000MΩmin. At DC 500V
- 接點電阻: 20mΩmax. At DC 100mA
- 工作溫度範圍: -55°C~+105°C

| Part No. | Product No. | 說明 | Contacts | Width(inch) |
|----------|-------------|---------|----------|-------------|
| 4200 | C23-24P | 壓排 IC 座 | 24P | 0.1*0.6 |
| 4204 | C23-28P | 壓排 IC 座 | 28P | 0.1*0.6 |
| 4203 | C23-32P | 壓排 IC 座 | 32P | 0.1*0.6 |
| 4202 | C23-40P | 壓排 IC 座 | 40P | 0.1*0.6 |

