



1.27mm單/雙排 排針

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


Part No.	Product No.	說明	Angle	Up(mm)	排*Pins	Down(mm)	全長
60774	D76-100P/0924A	1.27mm 雙排排針	180°	3mm	2*50	6.6mm	11.2mm



Part No.	Product No.	說明	Angle	排*Pins
60441	D76-40P-SMD	1.27*1.27mm SMD 雙排排針	SMD	2*20

1.27mm 單/雙排 排針母座

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


- 外殼材質：30% Glass filled PBT UL94V-0
- 接點材質：Brass
- 鍍層：Gold plated: 2u" over 50u" nickel
Tin plated: 50u" over 100u" nickel

- 額定電流：1 AMP
- 絕緣電阻：5000MΩmin. At DC500V
- 接點電阻：20mΩmax. At DC100mA
- 工作溫度範圍：-55°C~+105°C


Part No.	Product No.	說明	Angle	排*Pins	全長(mm)
10485	885-08-HHPFS108GB1	Pitch : 1.27 鍍金排針母座	180°	1*8	7.7
10484	885-20-HHPFS120GB1	Pitch : 1.27 鍍金排針母座	180°	1*20	7.7
10486	885-32-HHPFS132GB1	Pitch : 1.27 鍍金排針母座	180°	1*32	7.7
10487	885-40-HHPFS140GB1	Pitch : 1.27 鍍金排針母座	180°	1*40	7.7



Part No.	Product No.	說明	Angle	排*Pins	全長(mm)
29440	886-10-HHPFS210GB1	Pitch : 1.27 鍍金排針母座	180°	2*5	7.8mm
10488	886-16-HHPFS216GB1	Pitch : 1.27 鍍金排針母座	180°	2*8	7.8mm
32236	886-20-H06-HHPFS220GB106H	Pitch : 1.27 鍍金排針母座	180°	2*10	13mm
10489	886-20-HHPFS220GB1	Pitch : 1.27 鍍金排針母座	180°	2*10	7.8mm
22628	886-40-01-HHPFS240GB101	Pitch : 1.27 鍍金排針母座/ 黑色 高度 8.5mm	180°	2*20	7.8mm
32235	886-40-H06-HHPFS240GB106H	Pitch : 1.27 鍍金排針母座	180°	2*20	25.5mm
10491	886-40-HHPFS240GB1	Pitch : 1.27 鍍金排針母座/ 黑色 高度 4.6mm	180°	2*20	7.8mm
10492	886-100-HHPFS2100GB1	Pitch : 1.27 鍍金排針母座	180°	2*50	7.8mm
10490	886-64-HHPFS264GB1	Pitch : 1.27 鍍金排針母座	180°	2*32	7.8mm



Part No.	Product No.	說明	Angle	排*Pins	全長(mm)
13285	886-60-HHPFS260GB1	Pitch : 1.27 鍍金排針母座	180°	2*30	38mm



Part No.	Product No.	說明	Angle	排*Pins	全長(mm)
38123	D69-40P-A2	Pitch : 1.27 鍍金排針母座	180°	2*20	26mm

2.0mm 單/雙排 排針

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


- 額定電流：1A
- 耐壓：600VAC(1 Minute)
- 絕緣電阻：1000 Megohms Min.
- 接點電阻：30 Milliohms Max.
- 工作溫度範圍：-40°C to +85°

- 接點材質：Phosphor Bronze
- 絕緣體材質：P.B.T+30% G.F

Part No.	Product No.	說明	排*Pins	Angle	Up(mm)	Down(mm)	全長(mm)
3824	D22-40P	2.0mm 單排排針	1*40	180°	3.4	2.8	8.8



- 額定電流：1A
- 耐壓：600VAC(1 Minute)
- 絕緣電阻：1000 Megohms Min.
- 接點電阻：30 Milliohms Max.
- 工作溫度範圍：-55°C to +105°

- 接點材質：Phosphor Bronze
- 絕緣體材質：NYLON-6T(UL 94V-0)

Part No.	Product No.	說明	排*Pins	Angle	Up(mm)	Down(mm)	全長(mm)
31972	D48-20P	2.0mm 單排排針	1*20	90°	-	-	-
17114	D48-40P	2.0mm 單排排針	1*40	90°	5mm	4mm	10mm

