



5080 系列 5.08mm 公座/母頭和端子

詳細產品規格請點擊www.100y.com.tw



- 1-20 Circuits
- With or without locking ramp nylon(UL94V-2)
- Mates with 045(1014mm)square or round pins
- Accepts double cantilever crimp terminal
- Housing available with integrally molded polarizing keys
- Terminal retention to housing-8lbs(3.6kg) minimum


Part No.	Product No.	說明	公/母座/頭	Pins	角度 °	Pitch
4638	F26-02P	5080S 母頭	母頭	2P	180°	5.08mm
28912	F26-03P	5080S 母頭	母頭	3P	180°	5.08mm
4640	F26-04P	5080S 母頭	母頭	4P	180°	5.08mm
4641	F26-06P	5080S 母頭	母頭	6P	180°	5.08mm
4642	F26-08P	5080S 母頭	母頭	8P	180°	5.08mm
4643	F26-10P	5080S 母頭	母頭	10P	180°	5.08mm
4645	F26-12P	5080S 母頭	母頭	12P	180°	5.08mm

7010 系列 5.0mm阻立公座/母頭和端子

詳細產品規格請點擊www.100y.com.tw




- Terminal
Material: 0.25T, Phos. Bronze, Brass
Plating: Copper-undercoated, Tin-plated
Wire Rating: Suitable for AWG#20-#26
- Housing
Material: Nylon 66, UL94V-0, V-2
- Wafer: Post: Brass, $\Phi 1.55(\Phi 0.61)$ Round Pin, Tin-plated
Circuits: 1-6



Product No.	A
F32-03P	17.68mm
F32-04P	22.65mm
F32-05P	27.74mm
F32-06P	32.56mm

Part No.	Product No.	說明	公/母座/頭	Pins
4599	F32-03P	7010-3P 阻立母頭 5.0mm	母頭	3P
4600	F32-04P	7010-4P 阻立母頭 5.0mm	母頭	4P
4601	F32-05P	7010-5P 阻立母頭 5.0mm	母頭	5P
4602	F32-06P	7010-6P 阻立母頭 5.0mm	母頭	6P



Product No.	A
F34-03P	17.52mm
F34-04P	23.14mm
F34-05P	27.97mm
F34-06P	32.61mm

Part No.	Product No.	說明	公/母座/頭	Pins	角度 °
4589	F34-03P	7010-3P 阻立接頭公座 5.0mm	公座	3P	180°
4590	F34-04P	7010-4P 阻立接頭公座 5.0mm	公座	4P	180°
4591	F34-05P	7010-5P 阻立接頭公座 5.0mm	公座	5P	180°
4593	F34-06P	7010-6P 阻立接頭公座 5.0mm	公座	6P	180°

7004, 7001 系列 5.08mm磁碟機電源公座/母頭和Pins (大4P)

詳細產品規格請點擊www.100y.com.tw



公頭



母頭

- Terminal
Material: 0.25T Brass
Plating: Copper-Undercoated, Tin-plated
- Housing
Material: Nylon 66, UL94V-0, V-2

Part No.	Product No.	說明	Pins	公/母座/頭	角度 °
4614	F48 (P-7001-N2-W10400)	磁碟機電源公頭-大 4P	4P	公頭	180
30157	F48-3P	磁碟機電源公頭	3P	公頭	180
4611	F49 (P-7004-N2-W10400)	磁碟機電源母頭-大 4P	4P	母頭	180
30156	F49-3P	磁碟機電源母頭	3P	母頭	180

