



PLT-25系列金屬連接頭和附件

詳細產品規格請點擊[www.100y.com.tw](http://www.100y.com.tw)



No. Of contacts	2	3	4	5	6
Contacts Configuration					
Rated current / voltage	10A 250V	10A 250V	10A 250V	10A 250V	10A 250V
Operation limit voltage(AC.V.rms)	400	400	400	400	300
Withstanding voltage(AC.V.rms)1 minute	2000	2000	2000	1800	1800
Insulation resistance(MΩ MIN.)at DC 500V	2000	2000	2000	2000	2000
Contact resistance(MΩ MAX.)at DC 1A	3	3	3	3	3
Solder inter diameter	1.9	1.9	1.9	1.9	1.9



Part No.	Product No.	製造廠商	說明	M/F Plug/Socket	Pins	Shell Size	Rate Current/Voltage
6232	PLT-25-Rca	PLT	PLT-25 連接頭防塵蓋			25mm	
6237	PLT-252-AD	PLT	PLT-25 Series -Industrial Circular Connectors	Male Plug	2P	25mm	10A/250V
6261	PLT-253-AD	PLT	PLT-25 Series -Industrial Circular Connectors	Male Plug	3P	25mm	10A/250V
6243	PLT-254-AD	PLT	PLT-25 Series -Industrial Circular Connectors	Male Plug	4P	25mm	10A/250V
6178	PLT-252-P	PLT	PLT-25 Series -Industrial Circular Connectors	Female Plug	2P	25mm	10A/250V
6241	PLT-253-P	PLT	PLT-25 Series -Industrial Circular Connectors	Female Plug	3P	25mm	10A/250V
6249	PLT-254-P	PLT	PLT-25 Series -Industrial Circular Connectors	Female Plug	4P	25mm	10A/250V
6284	PLT-252-R	PLT	PLT-25 Series -Industrial Circular Connectors	Male Socket	2P	25mm	10A/250V
6283	PLT-253-R	PLT	PLT-25 Series -Industrial Circular Connectors	Male Socket	3P	25mm	10A/250V
6245	PLT-254-R	PLT	PLT-25 Series -Industrial Circular Connectors	Male Socket	4P	25mm	10A/250V



No. Of contacts	2	4
Contacts Configuration		
Rated current / voltage	10A 250V	10A 250V
Operation limit voltage(AC.V.rms)	400	400
Withstanding voltage(AC.V.rms)1 minute	2000	2000
Insulation resistance(MΩ MIN.)at DC 500V	2000	2000
Contact resistance(MΩ MAX.)at DC 1A	3	3
Solder inter diameter	1.9	1.9



Part No.	Product No.	製造廠商	說明	M/F Plug/Socket	Pins	Shell Size	Rate Current/Voltage
50698	PLT-252-PM+RF	PLT	PLT-25 Series -Industrial Circular Connectors	Female Socket+Male Plug	2P	25mm	10A/250V
50712	PLT-254-PM+RF	PLT	4P 母插座 10A/250V	Female Socket+Male Plug	4P	25mm	10A/250V

PLT-30系列金屬連接頭和附件

詳細產品規格請點擊[www.100y.com.tw](http://www.100y.com.tw)



No. Of contacts	2	3	4	5	7
Contacts Configuration					
Rated current / voltage	15A 250V	15A 250V	15A 250V	15A 250V	15A 250V
Operation limit voltage(AC.V.rms)	400	400	400	400	400
Withstanding voltage(AC.V.rms)1 minute	2000	2000	2000	1800	1800
Insulation resistance(MΩ MIN.)at DC 500V	2000	2000	2000	2000	2000
Contact resistance(MΩ MAX.)at DC 1A	3	3	3	3	3
Solder inter diameter	2.8	2.8	2.8	2.8	2

● Shell Size: 30mm



Part No.	Product No.	製造廠商	說明	Shell Size	Pins	M/F Plug/Socket	Rate Current/Voltage
6230	PLT-30-Rca	PLT	PLT-30 連接頭防塵蓋	30mm			
4831	PLT-302-AD	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	2P	Male Plug	15A/250V
6262	PLT-303-AD	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	3P	Male Plug	15A/250V
9946	PLT-304-AD	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	4P	Male Plug	15A/250V
4834	PLT-305-AD	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	5P	Male Plug	15A/250V
7003	PLT-302-P	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	2P	母插頭	15A/250V
8590	PLT-303-P	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	3P	Female Plug	15A/250V
7004	PLT-304-P	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	4P	Female Plug	15A/250V
6279	PLT-305-P	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	5P	Female Plug	15A/250V
48748	PLT-404-P	PLT	PLT-30 Series -Industrial Circular Connectors	45mm	4P	Female Plug	30A/250V
6239	PLT-302-R	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	2P	Male Socket	15A/250V
4826	PLT-303-R	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	3P	公插座	15A/250V
6263	PLT-304-R	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	4P	Male Socket	15A/250V
5118	PLT-305-R	PLT	PLT-30 Series -Industrial Circular Connectors	30mm	5P	Male Socket	15A/250V

