



PLS-20系列金屬連接頭和附件

詳細產品規格-請點擊www.100y.com.tw



INPUT TYPE

No. Of contacts	2	3	4	7
Contacts Configuration				
Rated current / voltage	15A 250V	15A 250V	10A 250V	10A 250V
Operation limit voltage(AC.V.rms)	250	250	250	250
Withstanding voltage(AC.V.rms)1 minute	1500	1500	1000	1000
Insulation resistance(MΩ MIN.)at DC 500V	2000	2000	2000	2000
Contact resistance(MΩ MAX.)at DC 1A	3	3	3	3
Solder inter diameter	1.8	1.8	1.6	1.6



Part No.	Product No.	製造廠商	說明	M/F Plug/Socket	Shell Size	Pins	Rate Current/Voltage
6234	PLS-20-Rca	PLT	PLS-20 連接頭防塵蓋		20mm		
52390	PLS-203-ADM	PLT	PLS-20 Series -Industrial Circular Connectors	公頭	20mm	3P	15A/250V
14426	PLS-207-ADM	PLT	PLS-20 Series -Industrial Circular Connectors	公頭	20mm	7P	8A/250V
3188	PLS-207-PF	PLT	PLK-16 Series -Industrial Circular Connectors	母頭	20mm	7P	10A/250V
6273	PLS-207-RM	PLT	PLS-20 Series -Industrial Circular Connectors	公座	20mm	7P	8A/250V



OUTPUT TYPE

No. Of contacts	2	3	4	7
Contacts Configuration				
Rated current / voltage	15A 250V	15A 250V	10A 250V	10A 250V
Operation limit voltage(AC.V.rms)	250	250	250	250
Withstanding voltage(AC.V.rms)1 minute	1500	1500	1500	1000
Insulation resistance(MΩ MIN.)at DC 500V	2000	2000	2000	2000
Contact resistance(MΩ MAX.)at DC 1A	3	3	3	3
Solder inter diameter	1.8	1.8	1.6	1.6

INPUT TYPE

No. Of contacts	2	3	4	7
Contacts Configuration				
Rated current / voltage	15A 250V	15A 250V	10A 250V	10A 250V
Operation limit voltage(AC.V.rms)	250	250	250	250
Withstanding voltage(AC.V.rms)1 minute	1500	1500	1000	1000
Insulation resistance(MΩ MIN.)at DC 500V	2000	2000	2000	2000
Contact resistance(MΩ MAX.)at DC 1A	3	3	3	3
Solder inter diameter	1.8	1.8	1.6	1.6



Part No.	Product No.	製造廠商	說明	M/F Plug/Socket	Shell Size	Pins	Rate Current/Voltage
50730	PLS-202-PM+RF	PLT	PLS-20 Series -Industrial Circular Connectors	公頭+母座	20mm	2P	15A/250V
50732	PLS-203-PM+RF	PLT	PLS-20 Series -Industrial Circular Connectors	公插頭+母座	20mm	3P	15A/250V
50738	PLS-207-PM+RF	PLT	PLS-20 Series -Industrial Circular Connectors	母座+公頭	20mm	7P	10A/250V
50743	PLS-204-RF+PM	PLT	PLS-20 Series -Industrial Circular Connectors	母座+公頭	20mm	4P	10A/250V
50718	PLS-202-RM+PF	PLT	PLS-20 Series -Industrial Circular Connectors	Male Socket+Female Plug	20mm	2P	15A/250V
50734	PLS-203-RM+PF	PLT	PLS-20 Series -Industrial Circular Connectors	公座+母頭	20	3P	15A/250V
50742	PLS-204-RM+PF	PLT	PLS-20 Series -Industrial Circular Connectors	母頭+公座	20mm	4P	10A/250V

PLS-24系列金屬連接頭和附件

詳細產品規格-請點擊www.100y.com.tw



INPUT TYPE

No. Of contacts	10
Contacts Configuration	
Rated current / voltage	10A 250V
Operation limit voltage(AC.V.rms)	250
Withstanding voltage(AC.V.rms)1 minute	1000
Insulation resistance(MΩ MIN.)at DC 500V	2000
Contact resistance(MΩ MAX.)at DC 1A	3
Solder inter diameter	1.6

OUTPUT TYPE

No. Of contacts	10
Contacts Configuration	
Rated current / voltage	10A 250V
Operation limit voltage(AC.V.rms)	250
Withstanding voltage(AC.V.rms)1 minute	1000
Insulation resistance(MΩ MIN.)at DC 500V	2000
Contact resistance(MΩ MAX.)at DC 1A	3
Solder inter diameter	1.6



Part No.	Product No.	製造廠商	說明	M/F Plug/Socket	Pins	Shell Size	Rate Current/Voltage
6233	PLS-24-Rca	PLT	PLS-24 連接頭防塵蓋	-	-	24mm	-
50744	PLS-2410-PF+RM	PLT	PLS-24 Series -Industrial Circular Connectors	Female Plug+Male Socket	10P	24mm	10A/250V
50741	PLS-2410-PM+RF	PLT	PLS-24 Series -Industrial Circular Connectors	Male Plug+Female Socket	10	24mm	10A/250V



假如您需要適合特殊用途的產品或更詳細的技術資料，我們的業務專員將會透過電話，傳真，E-mail，幫助您

