



PLS-35系列金屬連接頭和附件

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


OUTPUT TYPE	
No. Of contacts	24
Contacts Configuration	
Rated current / voltage	8A 250V
Operation limit voltage(AC.V.rms)	200
Withstanding voltage(AC.V.rms)1 minute	1000
Insulation resistance(MΩ MIN.)at DC 500V	1000
Contact resistance(MΩ MAX.)at DC 1A	3
Solder inter diameter	1.8



Part No.	Product No.	製造廠商	說明	Shell Size	Pins	M/F Plug/Socket	Rate Current/Voltage
50731	PLS-3524-PM+RF	PLT	PLS-35 Series -Industrial Circular Connectors	35mm	24P	Male Plug+Female Socket	8A/250V

PLK-16系列金屬連接頭和附件

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


INPUT TYPE				
No. Of contacts	2	3	4	5
Contacts Configuration				
Rated current / voltage	5A 125V	5A 125V	5A 125V	5A 125V
Operation limit voltage(AC.V.rms)	200	200	200	200
Withstanding voltage(AC.V.rms)1 minute	1000	1000	1000	1000
Insulation resistance(MΩ MIN.)at DC 500V	1000	1000	1000	1000
Contact resistance(MΩ MAX.)at DC 1A	3	3	3	3
Solder inter diameter	1.5	1.5	1.5	1.3



Part No.	Product No.	製造廠商	說明	Shell Size	Pins	M/F Plug/Socket	Rate Current/Voltage
50683	PLK-162-R+P	PLT	PLK-16 Series -Industrial Circular Connectors	16mm	2P	Female Plug+Male Socket	5A/125V
50699	PLK-163-R+P	PLT	PLK-16 Series -Industrial Circular Connectors	16mm	3P	Female Plug+Male Socket	5A/125V
50707	PLK-164-R+P	PLT	PLK-16 Series -Industrial Circular Connectors	16mm	4P	Male Socket+Female Plug	5A/125V
50700	PLK-165-R+P	PLT	PLK-16 Series -Industrial Circular Connectors	16	5P	Male Socket+Female Plug	5A/125V

PLK-30系列金屬連接頭和附件

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


OUTPUT TYPE		
No. Of contacts	4	7
Contacts Configuration		
Rated current / voltage	15A 250V	15A 250V
Operation limit voltage(AC.V.rms)	400	400
Withstanding voltage(AC.V.rms)1 minute	2000	1800
Insulation resistance(MΩ MIN.)at DC 500V	2000	2000
Contact resistance(MΩ MAX.)at DC 1A	3	3
Solder inter diameter	3.5	3



Part No.	Product No.	製造廠商	說明	Pins	M/F Plug/Socket	Rate Current/Voltage	Shell Size
28464	PLK-304-PM	PLT	PLK-30 Series -Industrial Circular Connectors	4P	公插頭	15A / 250V	30
28830	PLK-307-PM	PLT	PLK-30 Series -Industrial Circular Connectors	7P	公插頭	15A / 250V	30
28465	PLK-304-RF	PLT	PLK-30Series -Industrial Circular Connectors	4P	母插座	15A / 250V	30
28829	PLK-307-FR	PLT	PLK-30Series -Industrial Circular Connectors	7P	母插座	15A / 250V	30

XS8系列鍍鎳金屬連接器

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


X型高可靠圓形小型連接器採用螺紋式連接，適用於各類儀器，儀表或電子設備等線路的連接，其最小外殼直徑只有8mm

- 額定電流/電壓：1A/36V
- 接觸電阻：≤10mΩ
- 絕緣電阻：>5000MΩ
- 頻率：50Hz~60Hz

Part No.	Product No.	說明	Shell Size	Pins	M/F Plug/Socket	Rate Current/Voltage
15208	X8K5P+X8J5Y-鍍鎳	推拉式鍍鎳圓形連接器	8mm	5P	母插頭+公插座	1A/36V

增加目錄完美及商品多樣化及市場占有率

- 因此-
- ✘ 不進步則落後
 - ✘ 不擴張則縮小
 - ✘ 不合作則孤立的精神

我們努力不懈

