




USB 連接座(頭)

詳細產品規格-請點擊www.100y.com.tw



Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
53157	USA-S041-BOA20	USB-A SMT 04P/ 2.0	FEMALE	A Type	90° SMT

- 材質: PE(本色)
- 用途: 作為USB接頭之保護及防塵用

- Shell: Copper alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper alloy
- Voltage Current Rating: 1Amp, 30V AC
- Insulation Resistance: 1000mΩ Min
- Contact Resistance: 30mΩ Max
- Dielectric Withstanding Voltage: AC 500V R.M.S
- Temperature Range: -20°C to +85°C




Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
52652	USAF-041N-WR00	USB Jack DIP (90°) 單層 1*4P	1* Female	A Type	90° DIP



- Shell: Copper alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper alloy
- Voltage Current Rating: 1Amp, 30V AC
- Insulation Resistance: 1000mΩ Min
- Contact Resistance: 30mΩ Max
- Dielectric Withstanding Voltage: AC 500V R.M.S
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
47859	USAF-081N-WR01	USB Jack DIP (90°) 雙層 2*4P	2* Female	A Type	90° DIP



- Shell: Copper alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper alloy
- Voltage Current Rating: 1Amp, 30V AC
- Insulation Resistance: 1000mΩ Min
- Contact Resistance: 30mΩ Max
- Dielectric Withstanding Voltage: AC 500V R.M.S
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
61759	USAF-086N-BR06	USB Jack DIP (90°) 雙層 2*4P	2* Female	A Type	90° DIP



- Shell: Steel
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1AMP,30VAC
- Insulation Resistance: 1000mΩ Min
- Contact Resistance: 30mΩ Max
- Dielectric Withstanding Voltage: AC500V R.M.S
- Temperature Range: -20°C to +85°C


Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
51717	USAM-041N-BR00	USB / A 4P Male/90° DIP Type	Male	A Type	90° DIP



Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
22041	USB SERIES A USA-04	USB-A SMT 04P/ 2.0	Female	A Type	90° SMT




- 材質: PE(本色)
- 用途: 作為USB接頭之保護及防塵用



Part No.	Product No.	製造廠商	說明
47490	USB-1	KSS	KSS_USB 插頭護蓋



Part No.	Product No.	說明	Male/Female	A/B Type
17582	USB-ADP-AF/AF	USB 轉換頭(A 母/A 母)	F/F	A to A Type



- Housing: Thermoplastic, UL94V-0
- Standard Nylon 66
- Contact: Phosphor Bronze
- Current Rating: 1 Amp
- Insulation Resistance: 1,000 Megohms Min.
- Contact Resistance: 20 Milliohms Max
- Dielectric Withstanding Voltage: 500VAC
- Temperature: -40°C--+105°C

Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
16916	USBAS-00401B012	USB CONNECTOR	Male	A Type	Flat 90° SMT

