



USB 連接座(頭)

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Cover: Thermoplastic, UL94V-0
- Voltage Current Rating: 1AMP, 30VAC

- Insulation Resistance: 1000mΩ Min
- Contact Resistance: 30mΩ Max
- Dielectric Withstanding Voltage: AC500V R.M.S
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
57547	USBF-041N-WP00	USB CONN / B 4P FEMALE /180° DIP Type	Female	B Type	180° DIP



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1AMP, 30VAC

- Insulation Resistance: 1000mΩ Min
- Contact Resistance: 30mΩ Max
- Dielectric Withstanding Voltage: AC500V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Male/Female	A/B Type	DIP/SMT
39295	USBF-041N-WR05	USB CONN / B 4P FEMALE /90° DIP Type	Female	B Type	90° DIP
62235	USBF-046N-BR03	USB CONN / B 4P FEMALE /90° DIP Type	母	B Type	90° DIP
61818	USBF-046N-BR05	USB CONN / B 4P FEMALE /90° DIP Type	母	B Type	90° DIP
57223	USBF-046N-WR05	USB CONN / B 4P FEMALE /90° DIP Type	母	B Type	90° DIP

Mini USB 連接座(頭)

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


- SHELL: Copper Alloy
- HOUSING: Thermoplastic, UL94V-0
- CONTACT: Copper Alloy

- Voltage Current Rating: 1 AMP, 30V AC
- Insulation Resistance: 100MΩ Min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: 100V AC
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT	AB/B Type	Male/Female
13966	MUBF-051N-BH00	Mini USB 5PIN Socket	5Pins	SMT	B Type	Female
62156	MUBF-056N-BH00	Mini USB 5PIN Socket	5Pins	SMT	B Type	Female



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1 AMP, 30VAC

- Insulation Resistance: 100mΩ Min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC100V R.M.S.
- Temperature Range: -50°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT	AB/B Type	Male/Female
49868	MUBF-051N-BP00	USB 迷你 5Pin 母 180°	5Pin	180° DIP	B Type	Female



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1AMP, 30VAC

- Insulation Resistance: 100mΩ min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC100V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT	AB/B Type	Male/Female
49867	MUBF-051N-BR60	USB 迷你 5Pin 母 90°	5 Pins	90° DIP	B Type	Female



Part No.	Product No.	說明	Pins	DIP/SMT	AB/B Type	Male/Female
51060	MUBF-081G-BV40	USB 迷你 8Pin 母 180°	8Pin	SMT	B Type	Female



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1AMP, 30VAC

- Insulation Resistance: 100mΩ Min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC 100V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT	Male/Female
55762	MUNF-041N-BH01	Mini USB 4PIN Socket SU* SMT	4P	SMT	Female
13964	MUNF-041N-BH02	Mini USB 4PIN Socket SU* SMT	4P	SMT	Female
55763	MUNF-041N-BH03	Mini USB 4PIN Socket SU* SMT	4P	SMT	Female



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1.5AMP, 250VAC

- Insulation Resistance: 100mΩ Min
- Contact Resistance: 30mΩ Max
- Dielectric Withstanding Voltage: AC 500V R.M.S.
- Temperature Range: -50°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT	AB/B Type	Male/Female
51065	MUNF-101T-BV40	USB 迷你 10Pin 母 180°	10Pin	SMT	B Type	Female

