



IEEE 1394 連接座(頭)

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- Shell: Stell
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 0.5AMP, 5VAC

- Insulation Resistance: 100mΩ Min.
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC100V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT
13965	IENF-041N-BH05	IEEE 1394 4PIN Socket SMT	4Pins	SMT



- Shell: Stell
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 0.5AMP,5VAC

- Insulation Resistance: 100mΩ Min
- Contact Resistance:50mΩ Max
- Dielectric Withstanding Voltage: AC100V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT
51069	IENF-041N-BR05	IEEE-1394/4 PIN/RECEPTACLE/DIP 90° TYPE	4P	DIP 90° TYPE



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1.5AMP, 40V AC

- Insulation Resistance: 500mΩ Min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC500V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT
12083	IENF-061N-BC00	IEEE-1394 DIP UP Right 6P GOLD PLATING	6 Pins	Short Flank DIP 90°



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1.5AMP, 40VAC

- Insulation Resistance: 500mΩ Min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC500V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT
51231	IENF-061N-BC30	IEEE-1394/6PIN/RECEPTACLE/ FLANK DIP 90° TYPE	6 Pins	Flank DIP 90°



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1.5AMP, 40VAC

- Insulation Resistance: 500mΩ Min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC500V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT
12082	IENF-061N-BR00	IEEE-1394 DIP 6P GOLD PLATING	6P	DIP



- Shell: Copper Alloy
- Housing: Thermoplastic, UL94V-0
- Contact: Copper Alloy
- Voltage Current Rating: 1.5AMP, 40VAC

- Insulation Resistance: 500mΩ Min
- Contact Resistance: 50mΩ Max
- Dielectric Withstanding Voltage: AC500V R.M.S.
- Temperature Range: -20°C to +85°C

Part No.	Product No.	說明	Pins	DIP/SMT
51072	IENF-061N-BV00	IEEE 1394 6PIN RECEPTACLE SMT 90° TYPE	6P/F	SMT 90° TYPE

HDMI 連接座(頭)

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- 觸點電阻：
Unmated plug socket, 30m ohm. Maximum.
Mated Plug Socket, 60m Ohm. Maximum
- 絕緣電阻：100M Ohm Min. At 500VDC
- 額定電壓/電流：AC 40V, 0.5A Minimum
- 電介質耐受電壓：500VAC(rms) For 1 Minute
- 工作溫度範圍：-20°C~+85°C

Part No.	Product No.	說明	Type	Male/Female
55965	HDMI-KPKB00-C01G3-L	HDMI 連接頭	C Type	Male/Plug



- 觸點電阻：
Unmated Plug Socket, 30m ohm. Maximum
Mated Plug Socket, 60m ohm. Maximum
- 絕緣電阻：100M Ohm Min. At 500VDC
- 額定電壓/電流：AC 40V, 0.5A Minimum
- 電介質耐受電壓：500V AC(rms) For 1 minute
- 工作溫度範圍：-20°C~+85°C

Part No.	Product No.	說明	Type	Male/Female
56013	HDMI-KPKB01-A02N2-L	HDMI 連接頭	A Type	Male/Plug

