



1.0~1.25mm FPC/FFC ZIF SMT 上接式連接頭



Part No.	Product No.	說明	Contacts	Pitch (mm)
11964	FPCTJ-T04TTW032	ZIF Mode Horizontal Type Top Entry	4p-卧上接	1.0
11965	FPCTJ-T08TTW032	ZIF Mode Horizontal Type Top Entry	8p-卧上接	1.0
11963	FPCTJ-T18TTW032	0.5mm Pitch ZIF Mode Horizontal Type Top Entry	18p-卧上接	1.0
11966	FPCTJ-T30TTW032	ZIF FPC P:1mm SMT 90° 卧上接	30P-卧上接	1.0
62291	ZIF-FPC-1.0mm-SMT-10P	FPC ZIF SMT 上接式連接頭	10 Pins 卧上接	1.0mm

詳細產品規格—請點擊www.100y.com.tw

1.0~1.25mm FPC/FFC ZIF SMT 下接式連接頭



- VOLTAGE: 50V MAX
- CURRENT: 0.5A MAX
- CONTACT RESISTANCE: 20 milliohms MAX
- INSULATION RESISTANCE: 50 Megohms MIN
- DIELECTRIC WITHSTANDING VOLTAGE: 250VAC
- TEMPERATURE: -40°C to 85°C


- ACTUATOR: HIGH-TEMP. THERMOPLASTIC. UL 94V-0
- CONTACT: PHOSPHOR BRONZE
- HOLDDOWN: BRASS

Part No.	Product No.	說明	Contacts	Pitch (mm)	重量
52960	F11-220-5221-A	FPC ZIF SMT 下接式連接頭	20P--卧下接	1.0mm	0.4g
52883	JF11-210-5221-A	FPC ZIF SMT 下接式連接頭	10P--卧下接	1.0mm	0.2g

詳細產品規格—請點擊www.100y.com.tw



Part No.	Product No.	說明	Contacts	Pitch (mm)
11959	FPCTJ-B04TTW032	FPC ZIF SMT 下接式連接頭	4P-卧下接	1.0mm
11961	FPCTJ-B08TTW032	FPC ZIF SMT 下接式連接頭	8p-卧下接	1.0mm
11960	FPCTJ-B18TTW032	FPC ZIF SMT 下接式連接頭	18p-卧下接	1.0mm
48076	FPCTJ-B20TTW032	FPC ZIF SMT 90° 下接式連接頭	20P 卧下接	1.0mm
11962	FPCTJ-B30TTW032	FPC ZIF SMT 下接式連接頭	30p-卧下接	1.0mm



Part No.	Product No.	說明	Contacts	Pitch (mm)	重量
65335	SMT-32P-1.0mm-卧下接-白	ZIF SMT Bottom Side Entry Connectors	32P-卧下接	1.0mm	0.85g

DVI型-連接頭/座 DVI 插板式連接頭



- Rated: 1.5A@40VAC(rms)
- Contact Resistance: 20 milliohms maximum
- Insulation Resistance: 1000 Megohms Minimum
- Dielectric Withstanding Voltage: 500V AC(rms)

- Housing: Glass filled thermoplastic, black, UL 94V-0
- Contact: Brass
- Shell: Steel, Tin over nickel plated

Part No.	Product No.	說明	角度	公、母座	Pins
13962	CA-24DVIPD-A	DVI 插板式連接頭	180°	公座	24P

詳細產品規格—請點擊www.100y.com.tw



- Rated: 1.5A @ 40VAC(rms)
- Contact Resistance: 20 Milliohms Maximum
- Insulation Resistance: 1000 Megohms minimum
- Dielectric withstanding Voltage: 500V AC(rms)

- Housing: Glass filled thermoplastic, Natural, UL94V-0
- Contact: Phosphor bronze
- Shell: Zinc alloy, nickel plated
- Board lock: copper alloy, tin plate

Part No.	Product No.	說明	角度	公、母座	Pins	重量
13961	CA-24DVISR-A-2-Z	DVI 插板式連接頭	90°	母座	24P	6.95g



- Insulator Material: Glass-filled thermoplastic, black, UL94V-0
- Shell Material: Steel
- Contact Material: Brass
- Contact Plating: Gold Flash

- Current Rating: 1.5AMP
- Insulation Resistance: 1000 Megohms Min
- Dielectric Withstanding: 500VAC(rms)
- Contact Resistance: 20 Milliohms max

Part No.	Product No.	說明	角度	公、母座	Pins	重量
13963	CA-29DVIPD-A	DVI 插板式連接頭	180°	公座	29P	6.6g

