



測試鉤, 棒

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


GRIP-B/100



GRIP-B/50

Test clip with flexible shaft and spring wire grabber(stainless steel) for a good contact to pins and wires in inaccessible places. Especially suitable for measuring voltage. The shaft is Silicone insulated and guarantees good heat resistance and flexibility even at low temperatures. Φ 4mm rigid socket in handle accepting spring-loaded Φ 4mm plugs with rigid insulating sleeve.

Rated voltage/current: 1000V, CATIII / 1A

MC®

Part No.	Product No.	製造廠商	說明	Color	L(mm)
14567	GRIP-B/100-BLACK	MC	(大)測試鉤	BLACK	197mm
14435	GRIP-B/100-RED	MC	(大)測試鉤	RED	197mm
19470	GRIP-B/50-BLACK	MC	測試鉤	BLACK	115mm
19471	GRIP-B/50-RED	MC	測試鉤	RED	115mm



Test clip with steel jaws especially for connections to ground rails and thick cables. For increased safety when making connections, the jaws are insulated on the outside. Φ 4mm rigid socket in handle accepting spring-loaded Φ 4mm plugs with rigid insulating sleeve

Rated voltage/current: 1000V, CATIII/16A

MC®

Part No.	Product No.	製造廠商	說明	Color	L(mm)
19466	GRIP-CI-21-BLACK	MC	測試夾	BLACK	113mm
19467	GRIP-CI-22-RED	MC	測試夾	BLACK	113mm



Part No.	Product No.	製造廠商	說明	L(mm)
32014	KT410	MC	小型測試鉤, 棒	2.8mm

MC®



Part No.	Product No.	製造廠商	說明
32013	LS410N	MC	小型測試鉤, 棒

MC®



- 最大輸入電壓/電流-60V DC/6A
- 阻抗: 16m Ω
- 接端: 4mm diameter pin and socket

Part No.	Product No.	說明	Color	L(mm)	重量
16676	L12-0200-04	轉換式長刺針	紅黑各一	109	12g



- Material:
Handle: ABS
Clip: phosphor bronze
- EFits 2.5mm IC lead
- EFits O.D. Less than 4mm wire by screwing
- 3A DC500V 100M Ω
- AC 1500V 1 minute

Part No.	Product No.	說明	Color	L(mm)
17916	R8-16C-B	IC 夾子	黑	139mm
17915	R8-16C-R	IC 夾子	紅色	139mm



Pincer Opening: 0.16in(4.06mm) dia. Test point
Fit 4mm Banana plugs connections
Rating: Overvoltage CAT III, 1000V, 10A per IEC1010-2-031
Std. Colors: -0 black, -1 red

Part No.	Product No.	說明	Color
59514	TP-51-X-B	測試鉤	黑色
59513	TP-51-X-R	測試鉤	紅色

測試鉤夾組

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


Test clip with steel jaws especially for connections to ground rails and thick cables. For increased safety when making connections, the jaws are insulated on the outside. Φ 4mm rigid socket in handle accepting spring-loaded Φ 4mm plugs with rigid insulating sleeve

Rated voltage/current: 1000V, CATIII/16A

MC®

Part No.	Product No.	製造廠商	說明	Color
49618	GRIP-CI-23-BLACK	MC	測試夾	BLACK
14436	GRIP-CI-23-BLUE	MC	測試夾	blue
49617	GRIP-CI-23-RED	MC	測試夾	RED

