



DT-貫通型端子台-平檯鎖螺絲式

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


Part No.	Product No.	說明	Poles	U:長 mm	Pitch(mm)
8617	DT-25-B01W-04G	柵板型端子台	4P 鍍金	32.5	7.62
10952	DT-25-B01W-06G	柵板型端子台	6P 鍍金	47.7	7.62
10951	DT-25-B01W-08G	柵板型端子台	8P 鍍金	63	7.62
15069	DT-25-B01W-09G	柵板型端子台	9P 鍍金	70	7.62
8618	DT-25-B01W-10G	柵板型端子台	10P 鍍金	78.2	7.62



Part No.	Product No.	說明	Poles	Pitch(mm)
3177	DT-45-A03W-05G	柵板型端子台	鍍金 05P	9.5
10585	DT-45-A03W-06G	配線盤 300V/20A	6P	9.5
10586	DT-45-A03W-07	配線盤 300V/20A	7P	9.5
10587	DT-45-A03W-08	配線盤 300V/20A	8P	9.5



- Pitch: 10.00mm
- Rated voltage: 300V
- Rated current: 25A
- Plastic Housing: PA6.6, UL94V-0, Black
- Terminal: Brass, 0.8t, Tin plated
- Screw: Steel, M3.5, Nickel plated



Part No.	Product No.	製造廠商	說明	Poles	U:長 mm	Pitch(mm)
22891	DT-55-B01W-03	DINKLE	柵板型端子台	3P	32mm	10
22898	DT-55-B01W-04	DINKLE	柵板型端子台	4P	42mm	10
22899	DT-55-B01W-05	DINKLE	柵板型端子台	3P	52mm	10
22893	DT-55-B01W-06	DINKLE	柵板型端子台	6P	62mm	10
22894	DT-55-B01W-09	DINKLE	柵板型端子台	9P	92mm	10
22900	DT-55-B01W-15	DINKLE	柵板型端子台	15P	152mm	10



- Rating: 250V 20A
- Insulation Withstands Voltage: AC 2200V/MIN
- Insulation Resistance: 500MΩ or more at DC 500V

Part No.	Product No.	說明	Poles	Pitch(mm)
59170	DT-5C-B01W-05	柵板型端子台	5P	10



- Pitch: 11.00mm
- Rated voltage: 300V
- Rated current: 25A
- Plastic Housing: PA6.6, UL94V-0, Black
- Terminal: Brass, 1.0t, Tin plated
- Screw: Steel, M4, Nickel plated

Part No.	Product No.	說明	Poles	U:長 mm	Pitch(mm)
22086	DT-65-B01W-05	柵板型端子台	5P	57	11
22085	DT-65-B01W-08	柵板型端子台	8P	89	11
21329	DT-65-B01W-09	柵板型端子台	9P	101	11



- Plastic Housing: PBT, UL94V-0, Black
- Terminal: Brass, 1.0t, Tin plated
- Screw: Steel, M4, Nickel plated
- Working Temperature: -40°C~+130°C
- Insulation withstand Voltage: AC2000V at 1 minute
- Insulation Resistance: 1000MΩ or more at DC500V
- Wire range: 18~10AWG

Part No.	Product No.	說明	Poles	U:長 mm	Pitch(mm)
23940	DT-7N-B01W-05	柵板型端子台	5	68.08mm	13mm



- Terminal: Brass, Tin plated, 0.8t
- Insulator body: PBT(UL94V-0), Black
- Screw: M3.0, steel, Ni plated
- Cover: PC
- Operation temperatures: -40°C to +120°C
- Rated current: 10Amp AC300V
- Insulation withstands volt: AC2000V min
- Insulation resistance: >5000MΩ at DC500V
- PCB hole Dia: Φ1.6mm~Φ1.8mm
- Wire range: 12lb-in
- Screw torque: 14kg-cm Screw with washer



Part No.	Product No.	製造廠商	說明	Poles	U:長 mm	Pitch(mm)
24570	T31BM11-06G	DECA	柵板型端子台	6P 鍍金	47.7	7.62
25121	T31BM11-09G	DECA	柵板型端子台	9P 鍍金	70	7.62



您可以通過以下訂貨方式與我們聯繫，訂購產品

電話訂購

傳真訂購

電郵訂購



電話：台灣：886-3-5753170
傳真：台灣：886-3-5753172
郵箱：台灣：sale@100y.com.tw

深圳：86-755-83298787
深圳：86-755-83640655
深圳：100y@vip.163.com

上海：86-21-34970699
上海：86-21-64605107
上海：100y-1@vip.163.com