




焊片, 接地片

詳細產品規格-請點擊www.100y.com.tw



Part No.	Product No.	說明	L(mm)	W1(mm)	材質
28691	PC187(5)LR	Male Terminal	12.7	6.3	鍍銅
6479	PC250-836LR	Male Terminal	14	7.9	鍍銅



Part No.	Product No.	說明	L(mm)	W1(mm)	材質
6494	PC1L25005LR	Male Terminal	17.5	8.0	Brass

- 用途：焊接於PC板上，另一端插接端子，牢固，不動搖




Part No.	Product No.	說明	L(mm)	W1(mm)	Parking	重量
51903	PCRS205	PC 板焊接端子	13.8	5.2	1000PCS/bag	0.45g/pc



	D1(mm)	L(mm)	W1(mm)
ST-2LT	2.2mm	11.1	5.0
ST-3.5LT	3.5mm	12.7	6.3
ST-3LT	3.2mm	12.7	6.3
ST-4LT	4.3mm	12.7	6.8

Part No.	Product No.	說明	螺絲口徑 d1(mm)	L(mm)	W1(mm)	材質
14071	ST-2LT	2.2mm 焊片	2.2mm	11.1mm	5.0mm	BRASS
14074	ST-3.5LT	3.5mm 焊片	3.5mm	12.7mm	6.3mm	BRASS
14072	ST-3LT	3.2mm 焊片	3.2mm	12.7mm	6.3mm	BRASS
19801	ST-4LT	4.3mm 焊片	4.3mm	12.7mm	6.8mm	BRASS



Part No.	Product No.	說明	L(mm)	W1(mm)	材質
6452	TWALR	Multi-Way Adapter	18	7.4	Brass Finish

中接管端子(全Nylon.Vinyl護套)

詳細產品規格-請點擊www.100y.com.tw



- Conn. Material: Brass
- 護套材質：Vinyl
- 耐溫°C: 75°C
- 電壓：300V

Part No.	Product No.	說明	護套顏色	尺寸 L*d1*D	壓接線徑	Conn. Material	耐溫°C/Volt/A	護套材質
52019	BB1V	Vinyl 雙母連接頭	紅色	26*1.7*4.1	22-16AWG(0.5-1.5mm ²)	Brass	75°C/300V/10A	Vinyl
51482	BB2V	Vinyl 雙母連接頭	藍色	26*2.3*4.5	16-14AWG(1.5-2.5mm ²)	Brass	75°C/300V/15A	Vinyl
51480	BB5V	Vinyl 雙母連接頭	黃色	26*3.4*6.5	12-10AWG(4-6mm ²)	Brass	75°C/300V/24A	Vinyl



- Conn. Material: Copper
- 護套材質：Nylon
- 耐溫°C: 105°C
- 電壓：600V

Part No.	Product No.	說明	護套顏色	尺寸 L*d1*D	壓接線徑	Conn. Material	耐溫°C /Volt/A	護套材質
51499	BCT0.5A	Nylon 中接管端子	黃色	20*1.2*2.0	26-22AWG(0.2~0.5mm ²)	Copper	105°C/600V/9A	Nylon
52021	BCT1A	Nylon 中接管端子	紅色	26*1.6*4.1	22-16AWG(0.5~1.5mm ²)	Copper	105°C/600V/19A	Nylon
51483	BCT2A	Nylon 中接管端子	藍色	26*2.3*4.5	16-14AWG(1.5~2.5mm ²)	Copper	105°C/600V/27A	Nylon
52020	BCT5A	Nylon 中接管端子	黃色	27*3.6*6.5	12-10AWG(4~6mm ²)	Copper	105°C/600V/48A	Nylon



- 壓接線徑：16-14AWG(1.5-2.5mm²)
- 尺寸：27.3*2.3*3.8
- 材質：Copper
- 耐溫：105°C
- 電壓/電流：600V/27A
- 護套材質：Nylon

Part No.	Product No.	製造廠商	說明	護套顏色	尺寸 L*d1*D	壓接線徑	Conn. Material	耐溫°C /Volt/A	護套材質
6458	BNY2	KST	Nylon 中接管端子	藍色	27.3*2.3*3.8	16-14AWG(1.5-2.5mm ²)	Copper	105°C/600V/27A	Nylon

KST.

