



網路連接線


[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)

Part No.	Product No.	說明	Length (M)	M/F,M/M,F/F
8424	RG58A/U-1M	RG58A/U 網路線	1M	M-M
5549	RG58A/U-2M	RG58A/U 網路線	2M	M-M
5547	RG58A/U-3M	RG58A/U 網路線	3M	M-M
8423	RG58A/U-5M	RG58A/U 網路線	5M	M-M
5561	RG58A/U-10M	RG58A/U 網路線	10M	M-M
10296	RG58A/U-15M	RG58A/U 網路線	15M	M-M
9637	RG58A/U-20M	RG58A/U 網路線	20M	M-M
20106	RG58A/U-30M	RG58A/U 網路線	30M	M-M

RJ45母插座


[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)

- IDC端子板可接22-26AWG單芯線徑
- 接點材質：100 μ "鍍後加錫50 μ "金
- 高密度延緩燃燒

- IDC端子板設計用於高效率應用
- 加大間距的IDC端子板改善每一對線的串音干擾
- IDC端子板可適用110型及KRONE的壓接工具

Part No.	Product No.	製造廠商	說明
50681	1305-04002	DINTEK	CAT.6 Keystone RJ45 JACK (Horizontal type)




- BOX: UL 94V-0 ABS
- Jack: RJ-45 8P8C, 50 micro inches gold plate [UL-94V-0 PBT]
- Terminal Block: UL 94V-0 ABS---Dual type NYLON-6-66---110 type
- PCB: FR-4
- Dual type Block can be punched down with Krone or AT&T tool
- 110 type Block can be punched down with AT&T tool only

Part No.	Product No.	製造廠商	說明
2588	21030188A4-01	DINTEK	桌上型插座單孔加防塵蓋 CAT.5



- BOX: UL94V-0 ABS
- Jack: RJ-45 8P8C, 50 micro inches gold plated [UL-94V-0 PBT]
- Terminal Block: UL94V-0 ABS---Dual type NYLON-6-66---110 type
- PCB: FR-4
- Dual type Block can be punched down with Krone or AT&T tool
- 110 type Block can be punched down with AT&T tool only

Part No.	Product No.	製造廠商	說明
2589	21030288A4-01	DINTEK	桌上型雙孔插座加防塵蓋



- HOUSING-PBT POLYESTER UL94V-0 MIXED GLASS FIBER, STANDARD COLOR-BLACK
- CONTACTS-0.45mm DIA. ROUND PHOS-BRONZE PLATED WITH HARD GOLD(6 μ ")

Part No.	Product No.	製造廠商	說明
20502	258-8P8C-RJ45	UNION	PCB JACK



Part No.	Product No.	製造廠商	說明
2582	2603588A9-01	DINTEK	CAT.5 KEYSTON RJ-45 JACK



Part No.	Product No.	製造廠商	說明
15398	2606266P9-01	DINTEK	6P6C Keystone Jack



- Case: UL-94V-0 ABS
- Jack: RJ-45 8P8C, 50 micro inches gold plated [UL-94V-0 PBT]
- PCB: FR-4

Part No.	Product No.	說明
18141	29165028812-01	RJ45 F-F 接頭 遮蔽



- Current Rating:1.5AMP
- Voltage Rating:150VAC
- Contact Resistance:20m MAX
- Insulation Resistance: 500m MIN
- Dielectric Withstanding Voltage: 1000VAC, 1min
- Housing: PBT Polyester UL94V-0
- Color: Black
- Contact: 0.35 thickness alloy selective gold plating
- Shield: 0.25mm thickness copper alloy with Tin/Nickel plated

Part No.	Product No.	說明
24568	330S-1822-11301	RJ45 8P8C 180°座

