



## RJ45母插座



- Housing: PBT Polyester UL94V0
- Color: Black
- Contacts: 0.45mm Diameter Phos-Bronze plated with hard gold
- Current Rating: 1.5 AMP MAX

- Voltage Rating: 150VAC MAX
- Contact Resistance: 20 milliohms MAX. Initial
- Insulation Resistance: 500 Megohms MIN
- Dielectric Withstanding Voltage: 1000VAC, 1min

Part No.	Product No.	說明
38902	370-1811-10001	RJ45 10P8C 90°座



- Housing Material: Glass filled polyester(UL94V-0)
- Contact Material: Phosphor bronze  $\Phi 0.46\text{mm}$ (C5100)
- Plating: Gold plating over nickel
- Voltage Rating: 125 VAC RMS

- Current Rating: 1.5AMP
- Contact Resistance: 50 MILLIOHMS MAX.
- Insulation Resistance: 500 MEGHOMS MIN @ 500V DC
- Dielectric Withstanding Resistance: 1000V AC RMS 50Hz. 1MIN

Part No.	Product No.	說明	Packing
52212	5224-011880113	RJ45 8P8C 180°座 (塑封)	10Pcs/bag



Part No.	Product No.	說明	Packing	重量
52293	5224-031881	RJ45 8P8C 180°座 (屏蔽)	10Pcs/bag	5.8g/pc



- Couplers
- Coupler Type-Modular UTP
- Coupler Style-In Line
- Position-8

- Conductors-None
- Color-Black
- Manufacturer Series- Workstation

Part No.	Product No.	製造廠商	說明
49437	555052-1	AMP	AMP 8PIN RJ45 接頭



- Material: HOUSTNG-PBT POLYESTER UL94V0
- COLOR-BLACK
- CONTACTS-0.35mm THICKNESS ALLOY
- SELECTIVE GOLD PLATING
- SHIELD-0.25mm THICKNESS COPPER
- ALLOY WITH NICKEL PLATED

Part No.	Product No.	說明
38702	610S-8811-13031	RJ45 90°座



- Type: CAT5e Snap-in Keystone Jack(8P8C)
- Termination: 110 Style 90 Degree punch down for 22-26 AWG solid wire
- Use With: Any Computer Cable Store Blank
- Wall Plate or Patch Panel T568A & T568B wiring compatible
- UL listed

Part No.	Product No.	說明
14238	9037	CAT.5e JACK(8P8C)



- 配線終端之連接，可用RJ-45跳線連接至電話或電腦
- 可選用藍色ICON標示電腦，或選用綠色ICON標示電話
- 附標示卡及雙面膠供使用，附防塵蓋以防止灰塵及濕氣
- 若以充膠線連接資訊插座，跳接線充膠部分須與RJ-45外尺寸切齊，以利跳接線接頭與資訊插座孔位相容

Part No.	Product No.	說明
14236	9038	CAT.5 單孔資訊盒
14237	9039	CAT.5 雙孔資訊盒



Part No.	Product No.	說明
17258	9636-8814	RJ45 8P8C 90°座
4013	SY-008	RJ45 8P8C 90°座



- Voltage Rating: 125VAC RMS
- Current Rating: 1.5AMP
- Contact Resistance: 42 MILLIOHMS MAX
- Insulation resistance: 1000 MEGOHMS MIN @ 500V
- Dielectric Strength: 1000 VDC RMS 60Hz. 1MIN
- Housing Material: Nylon 66, UL94V-0
- Contact Material: Phosphor Bronze  $\Phi 0.46\text{mm}$
- Plating: Gold Plating Over Nickel

Part No.	Product No.	製造廠商	說明
42287	RJ10-08F1-K000-04	E-Conn	RJ-45 網路 8P8C 黑 PCB 90°

