



RJ45母插座



- Shield Type-Unshielded
- Mount Style-Right Angle Mount
- Available in many housing colors
- LEDs-Available with and without LEDs

- Packaging-80 units per Tray, 640 units per box(carton)
- Carton Weight-5.5 kgs Gross Weight
- Carton Size-35x25x26cm

Part No.	Product No.	說明	Packing
54857	XRJK-U-01-8-8-0-7A4	RJ45 8P8C 90°座	10 個/包



- Shield Type-Shielded
- Mount Style-Thru-hole
- LEDs-No LEDs

- Packaging-70 units per Tray, 1260 units per box(carton)
- Carton Weight-8.3 kgs Gross Weight
- Carton Size-51.5x34x22cm

Part No.	Product No.	說明
52751	XRJM-S-01-8-8-0	RJ45 母插座 ,8P8C BLACK-90°



Part No.	Product No.	說明
22622	XRJM-S-01-8-8-4	PHONE-JACK CONN,8P8C BLACK-90° LED(左 綠,右 黃)



Part No.	Product No.	說明
52336	XRJV-S-01-8-8-1	RJ45 8P8C 1Port 180° (左 黃,右 綠)

RJ45接頭



- Housing: Polycarbonate
- Contact: Copper alloy 50u" gold over nickel plate
- Current Rated: 30VAC at 1.5Amps

- Contact Resistance: 10 milliohms max
- Dielectric Strength: 1000VAC(RMS)
- Insulation Resistance: 500 Megaohm min

Part No.	Product No.	製造廠商	說明	Parking
3792	2P38803-01	DINTEK	RJ45 PLUG 三叉 鍍金 50u", UL & CSA	100 個/包
2590	2P38823-01	DINTEK	RJ45 PLUG 三叉 鍍金 50u", UL & CSA	10 個/包



- Housing Material: Polycarbonate, UL 94V-2. No Poison
- Material Contact: Phosphor Bronze
- Housing Color: Transparence
- Operation Temperature: -40°C to 125°C

Part No.	Product No.	說明
18119	NC-0216-00	網路接頭 10P10C



- 容納最大絕緣直徑0.39英寸(0.99mm)24AWG
- 導體和纜線外披介於200到.215英寸之間
- 超越TIA/EIA-568-A要求於4對(RJ-45)UTP運用
- 為8 position設計
- 材質: Polycarbonate, UL94V-2
- 額定電壓及電流: 150V AC, 1.5A

- 絕緣耐壓: 1000Vac
- 絕緣電阻: 500 Megaohms
- 抗拉力: 17lbs軸方向
- 耐插拔數: 750次
- 接觸點: 鍍金50μ
- 通過CSA(LR7189A),UL(file NO.E81956)

Part No.	Product No.	製造廠商	說明	Parking
3334	NET-PLG-AMP100-5e	AMP	RJ45 三叉 PLUG 8P8C	100 個/包
2585	NET-PLG-AMP100-5e-10 個/包	AMP	RJ45 PLUG 三叉鍍金 50u"	10 個/包



Part No.	Product No.	說明	Parking
18017	NET-PLG-PRO-6/10	網路接頭 8P8C PLUG Cat.6	10 個/包



- 容納最大絕緣直徑0.39英寸(0.99mm)24AWG
- 導體和纜線外披介於200到.215英寸之間
- 超越TIA/EIA-568-A要求於4對(RJ-45)UTP運用
- 為8 position設計
- 材質: Polycarbonate, UL94V-2
- 額定電壓及電流: 150V AC, 1.5A

- 絕緣耐壓: 1000Vac
- 絕緣電阻: 500 Megaohms
- 抗拉力: 17lbs軸方向
- 耐插拔數: 750次
- 接觸點: 鍍金50μ
- 通過CSA(LR7189A),UL(file NO.E81956)

Part No.	Product No.	說明	Parking	重量
12480	NET-PLG-PRO10/5e	RJ45 PLUG-8P8C-3 叉-鍍金	10 個/包	22.95G
12481	NET-PLG-PRO100-5e	RJ45 PLUG-8P8C-3 叉-鍍金	100 個/包	197.45G

