



## RS232/RS422/RS485轉換器

[詳細產品規格請點擊www.100y.com.tw](http://www.100y.com.tw)


- 與USB v1.1規格完全兼容
- 支持RS-232/422/485端口
- 傳輸速率可達115.2Kbps
- 提供3000V Dc隔離保護
- 自動RS-485數據流控制

- 無需外部電壓，集線器即可從USB端口驅動
- 驅動程序支持：Windows 98/ME/2000, Linux
- 即插即用
- 無須額外的IRQ或I/O端口
- 支持熱插拔功能

Part No.	Product No.	製造廠商	說明
55896	ADAM-4561	ADVANTECH	RS-485 資料讀取模組



- I/O類型：8路熱電偶/8DO
- 支持多通道，多範圍
- 容錯與過壓保護
- 2500V的光隔離

Part No.	Product No.	製造廠商	說明
55897	ADAM-6018	ADVANTECH	以太網路資料讀取模組



- 接口特性：接口兼容EIA/TIA的RS-232C,RS-422/485標準
- 電氣接口：RS-232C接口DB25孔型連接器RS-422/485接口四位接線端子或RJ-11座
- 傳輸介質：雙絞線或屏蔽線
- 工作方式：異步半雙工或異步全雙工
- 信號顯示：一個信號雙色指示燈指示TD,RD數據
- 隔離度：隔離電壓3500VRMS 500VDC連續
- 供電方式：RS-232端串口竊電，RS-422/485端外接電源

Part No.	Product No.	說明	Connector	重量
55035	ATC-107	光隔離型接口轉換器(RS-232 to RS-422/RS485)	DB25 孔型連接器/4P 端子座	380g



- 資料傳送可依RTS(傳送要求)訊號控制
- DCE\*/DTE\*可切換
- point-to-point, Multidrop, simplex\*/duplex\*可連接選擇
- 支援Full duplex, Half duplex
- 輕巧尺寸
- Monitor configuration(IC-485S)

Part No.	Product No.	說明	Connector	重量
5315	RS232/HM485	雙向介面轉換器 RS232/485	DB25M/RJ11+端子台	340g



- Wide range input DC power supply
- Automatic data format configuration
- Auto direction flow control on RS-485
- Auto baud rate switching from 300bps to 115.2Kbps
- 3000V DC isolated protection
- Surge protection on RS-422/485 data lines
- Power/TX/RX mode LED indicator
- Support screw terminal and external DC power adaptor
- Din rail or panel mounts support

Part No.	Product No.	製造廠商	說明	Connector	重量
17883	TRP-C06	Trycom	工業規格 422/485 防止干擾轉換器	9F/10P 端子座	0.38Kg/pcs



- Wide range input DC power supply
- Automatic data format configuration
- Auto direction flow control on RS-485
- Auto baud rate switching from 300bps to 115.2Kbps
- 3000VDC isolated protection
- Surge protection on RS-422/485 data lines
- Power/TX/RX mode LED indicator
- Support screw terminal and external DC adaptor
- DIN rail or panel mounts support

Part No.	Product No.	製造廠商	說明	Connector	重量
55773	TRP-C06HA	Trycom	RS232 轉 RS422/485 光隔離轉換器(2 組獨立)	2 standard D-Sub 9 pin female connectors	375g



- Wide input range DC power supply
- Automatic data format configuration
- Auto direction flow control on RS-485
- Auto baud rate switching from 300bps to 115.2Kbps
- RS485 bi-directionally communication
- 3000 DC isolated protection
- Surge protection on RS-422/485 data lines
- Power/TX/RX mode LED indicator
- Support screw terminal and external DC adapter
- DIN rail or panel mount support

Part No.	Product No.	說明	Connector
17884	TRP-C07	RS422/485 光耦合隔離中繼器	10P 端子座/10P 端子座



- Full compliance with the USB V1.0 and 2.0 specification.
- System gets 1 COM port when the converter is connected.
- Auto data format detecting.
- Auto direction flow control on RS-485.
- Auto baud rate switching from 75bps to 1228800bps.
- 256 byte buffer for upstream and downstream data flow.
- Direct power from USB port, no external power necessary.
- 3000V DC isolated protection.
- Surge protection on RS422/485 data lines.
- Power/TX/RX mode LED indicator.
- DIN rail or panel mount support.
- Driver support: Windows 98/ME/2000/XP/CE3.0, and Linux, and Mac OS.

Part No.	Product No.	製造廠商	說明	Connector
58413	TRP-C08	Trycom	工業規格 USB TO 232/422/485 光耦合轉換器(不含傳輸線)	USB/10P 端子座
17885	TRP-C08	Trycom	工業規格 USB TO 232/422/485 光耦合轉換器(附線材:LI-USB-A/B 1.8 米)	USB/10P 端子座

