



RS232/RS422/RS485轉換器

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- USB-2.0 device controller.
- Allow user custom adjust baud-rates.
- Each Port can impendent set up the baud-rate and data format.
- On-Chip 512-Byte FIFO for upstream and downstream data transfers for serial Port.
- System gets four serial port when the converter plug in.
- Auto switching RS422/485 detecting.
- Auto direction flow control on Rs485.

- Auto baud rate switching from 300bps to 256 Kbps.
- Direct power from USB port , no need external power supply.
- 3000 VDC isolation protection on RS422/485.
- Surge protection on RS422/485 data line.
- Power and TXA/RXA/TXB/RXB communication LED indicator
- Din-Rail (option)or panel mount Driver support:
- Vista64/32,Windows 98/ME/2000/XP/CE3.0, and Linux, and Mac OS


Part No.	Product No.	製造廠商	說明	Connector	重量
56064	TRP-C08H	Trycom	USB 轉 2埠 RS232 和 2埠 RS422/485 光隔離轉換器 (4組獨立)	Screw terminal for maximum AWG #12-30 wire	395g



- USB-2.0 Device Controller
- Allow user custom adjust baud-rates.
- Each port can impendent set up the baud-rate and data format.
- OS. System get dual port UART serial (1*RS232 and 1*RS422/485).
- On-Chip 512-Byte FIFO for upstream and downstream data transfers for serial Port.
- Fully PLC support such as Mitsubishi Q,FX and FATEK serial....
- Auto direction flow control on RS-485.
- Auto baud rate switching from 75bps to 921.6 Kbps.

- 256 byte buffer for upstream and downstream data flow.
- Direct power from USB port , no external power necessary.
- 3000V DC isolated protection.
- Surge protection on RS422/485 data lines.
- Power and TXA/RXA/TXB/RXB communication LED indicator
- DIN rail or panel mount support.
- Driver support: Vista64/32,Windows 98/ME/2000/XP/CE3.0, and Linux, and Mac OS.


Part No.	Product No.	製造廠商	說明	Connector	重量
55993	TRP-C08S	Trycom	USB 2.0 轉 1個 RS232 和 1個 RS422/485 2埠轉換器	USB/4P 端子座	375g



- Wide input range DC power supply..
- Support ASCII and Modbus RTU protocol.
- Supports baud rates from 1.2Kbps to 115.2 Kbps.
- Digital output signal with 3750Vrms isolation protection.
- Dual watchdog: Module's firmware, host computer traffic.

- LED for each channels working status.
- DIN-Rail and panel mount support.
- Configured and self-test by external dip-switch.
- Support screw terminal and external DC power adaptor.


Part No.	Product No.	製造廠商	說明	Connector	重量
56103	TRP-C24	Trycom	16組通道數位隔離輸出(O.C)分散式 RS485 模組, 支援 ASCII and Modbus RTU	Screw terminal for maximum AWG 12 wire	395g



- Wide input range DC power supply..
- Support ASCII and Modbus RTU protocol.
- Supports baud rates from 1.2Kbps to 115.2 Kbps.
- All 16 channels digital input ca be used as counter.
- Digital output signal with 3750Vrms isolation protection.

- Dual watchdog: Module's firmware, host computer traffic.
- LED for each channels working status.
- DIN rail and panel mount support.
- Configured and self-test by outer dip-switch.
- Support screw terminal and external DC power adaptor.

Part No.	Product No.	製造廠商	說明	重量
56104	TRP-C26	Trycom	16組通道數位隔離輸入分散式 RS485 模組, 支援 ASCII and Modbus RTU	395g



- Wide input range DC power supply..
- Support ASCII and Modbus RTU protocol.
- Supports baud rates from 1.2Kbps to 115.2 Kbps.
- All 4 channels digital input ca be used as counter.
- Digital input signal with 3750Vrms isolation protection.

- Dual watchdog: Module's firmware, host computer traffic.
- LED for each channels working status.
- DIN rail and panel mount support.
- Configured and self-test by outer dip-switch.
- Support screw terminal and external DC power adaptor.

Part No.	Product No.	製造廠商	說明	重量
56105	TRP-C28	Trycom	4組數位隔離輸入及4組繼電器分散式 RS485 模組, 支援 ASCII and Modbus RTU	400g



- DIN rail or Panel mount support.
- RS-232/422/485 all-in-one serial interface.
- Auto-detecting 10/100Mbps Ethernet interface.
- In Server mode supports individual client sessions for security.
- Virtual COM drivers for Windows NT/98/ME/2000/XP/Vista/Window 2003/CE/Server x64.

- Auto direction flow control on RS-485.
- Provide with +/- 15KV ESD protection on RS-232/422/485 signals.
- Supported baud rate up to 230.4 Kbps.
- Power/Link/COM Flow LED indicators.
- Support intranet and internet system setting function.
- Support screw terminal and standard external DC power adaptor.

Part No.	Product No.	製造廠商	說明	重量
55995	TRP-C31	Trycom	網路 10/100MB 轉 RS232/422/485 轉換器	377g



- DIN rail or Panel mount support.
- 2 serial ports interface: 1 RS-232, 1 RS-232/422/485.
- Auto-detecting 10/100Mbps Ethernet interface.
- In Server mode supports individual client sessions for security.
- Virtual COM drivers for Windows NT/98/ME/2000/XP/Vista/Window 2003/CE/Server x64.
- Auto direction flow control on RS-485.

- Provide with +/- 15KV ESD protection on RS-232/422/485 signals.
- Supported baud rate up to 230.4 Kbps.
- Power/Link/COMA/COMB Flow LED indicators.
- Support intranet and internet system setting function.
- Support screw terminal and standard external DC power adaptor.

Part No.	Product No.	製造廠商	說明	重量
55996	TRP-C32	Trycom	網路 10/100MB 轉 1埠 RS232 和 1埠 RS232/422/485 轉換器(2組獨立)	379g

