



RS232/RS422/RS485轉換器

[詳細產品規格-請點擊www.100y.com.tw](http://www.100y.com.tw)


- DIN rail or Panel mount support
- 4 X RS-232/422/485 all-in-one serial interface.
- Auto-detecting 10/100Mbps Ethernet interface.
- In Server mode supports individual client sessions for security.
- Virtual COM drivers for Windows98/Me/NT/2000/XP/Vista/Window 2003/CE/Server x64.

- Auto direction flow control on RS-485.
- Provide with +/- 15KV ESD protection on RS-232/422/485 signals.
- Supported baud rate up to 230.4 Kbps.
- Power/Link/COMA/COMB/COMC/COMD flow mode LED indicators..
- Support intranet and internet system setting function.
- Support screw terminal and standard external DC power adaptor.

Part No.	Product No.	製造廠商	說明	Connector	重量
56065	TRP-C34	Trycom	網路 10/100MB 轉 4埠 RS232/422/485 轉換器(4組獨立)	RJ-45 connection	638g



- 所有RS422/485/232 訊號提供3000V直流隔離和MRS422/485端提供過電流及過電壓保護。
- RS-232端提供RTS & CTS 交握訊號介面。
- RS485訊號提供自動雙向控制,連接任何RS485裝置皆相容)
- 自動選擇RS-232/RS-422/485訊號。
- 線上更新版本。
- RS422/485可接至1.2KM如需延長可另加TRP-C07中繼器。
- 面板燈號指示電源(PWR), 流量(RX, TX)及網路連接(LINK)。

- 可直接瀏覽器進入設定TRP-C36韌體功能選項。
- 網路通訊採用相容性高的RealTek8019AS晶片。
- 支援通訊協定ARP, UDP, TCP, ICMP, HTTP, DHCP, IP
- 電源消耗瓦數電流: 1.2W/500mA
- 可使用一般市售12V變壓器。(DC插入孔規格請使用5.5*2.1mm/500mA即可)
- 訊號及電源連接座採用歐規工業用公母分離式端子
- 電源輸入範圍從10V-30V,提供多樣電源供應器選擇。
- 支援全系列工業軌道裝置。
- 儲存溫度: -25~75°C.
- 操作溫度: -20~60°C.

Part No.	Product No.	製造廠商	說明	Connector	重量
56067	TRP-C36	Trycom	網路 To RS232/422/485 光隔離轉換器	Standard RJ45 LAN port	375g



- DIN rail or Panel mount support
- Supports 8 RS-232 serial interface
- Auto-detecting 10/100Mbps Ethernet interface
- In Server mode supports individual client sessions for security
- Virtual COM drivers for Windows NT/98/ME/2000/XP/Vista/Window 2003/CE/Server x64

- Provide with +/-15KV ESD protection on RS-232 signals
- Supported baud rate up to 230.4Kbps
- Power/Link/All COM port flow mode LED indicator
- Support intranet and internet system setting function
- Support screw terminal and standard external DC adaptor

Part No.	Product No.	製造廠商	說明	Connector	重量
56068	TRP-C38	Trycom	網路 10/100MB 轉 8埠 RS232 轉換器(8組獨立)	RJ-45	638g



- Wide range power input voltage
- ST Multi-mode fiber port
- Auto direction flow control on RS-485
- Automatically switch signal RS-232, RS-422 and Rs485
- Support 3000V DC isolation protection

- All RS-422/485 signals provide surge and overcurrent protection
- Power/TX/RX mode LED indicator
- Fiber transmission distance up to 2KM
- Auto baud rate switching from 300bps to 115.2Kbps
- Support Din-Rail and panel mount

Part No.	Product No.	製造廠商	說明	Connector
29431	TRP-C39	Trycom	ST 多模光纖轉 RS232/422/485 隔離	RS232



- Wide input range DC power supply
- SC single mode fiber port
- Auto direction flow control on RS-485
- Auto RS-232/422/485 signals switching
- Auto data format detecting

- Auto baud rate switching from 300bps to 115.2Kbps.
- Support 3000V DC isolation protection
- Support surge protection on RS-422/485 data lines
- Power/TX/RX mode LED indicator
- Fiber transmission distance up to 40KM
- DIN rail or panel mount support

Part No.	Product No.	製造廠商	說明	Connector	重量
55994	TRP-C39S	Trycom	SC 單模光纖轉 RS232/422/485 光隔離轉換器	RS232	388g



- Wide input range DC power supply
- Plug-and-Play design for the installation withinseconds
- Compact and Rugged Metal case capable ofwithstanding harsh environment
- Data rate: 10/100Mbps auto-negotiation and half-/Full-duplex mode on TX port
- Auto MDI-X/MDI-II for 10/100Base-TX port
- Provides media conversion from UTP to Fiber Optic media types

- Supports link fault pass through function
- Supports far end fault function
- LED display to indicate the whole working status 3 power input types: Direct USB power, external
- DC adapter and screw terminal
- Support IEEE Standard:802.3u 100Base TX & 100Base FX

Part No.	Product No.	製造廠商	說明	重量
56101	TRP-C41	Trycom	SC 單模光纖轉 Ethernet 10/100 MB 轉換器	400g



- Bluetooth V1.2 Class 1 compliance.(2.5mW/4dBm)
- Bluetooth interface compatible with PDA and PC-Base system
- Transmission range open filed 100M
- Using the outdoor direction antenna can up to 1KM
- Fully PLC support such as Mitsubishi Q, FX and FATEK serial...

- Bi-directionally RS-485 signals communication
- Support all common baud rate from 1.2K to 256Kbps
- Comfortable TRP-BT configuration software(Windows version)
- RS-232/422 and Rs485 signal auto switching
- Master/Slave connection mode selectable
- LED indicators for Power/Link(Active)/TX/RX

Part No.	Product No.	製造廠商	說明	重量
56102	TRP-C51	Trycom	RS232/422/485 無線藍芽轉換器(100公尺)可擴充至 1KM	400g

可通過下列資料尋找我們目錄內的产品

🔍 100y編號

🔍 廠商編號

🔍 產品關鍵字

🔍 製造廠商名稱



電話：台灣：886-3-5753170
 傳真：台灣：886-3-5753172
 郵箱：台灣：sale@100y.com.tw

深圳：86-755-83298787
 深圳：86-755-83640655
 深圳：100y@vip.163.com

上海：86-21-34970699
 上海：86-21-64605107
 上海：100y-1@vip.163.com

15-14