



RS-232轉RJ11/RJ45轉接頭

詳細產品規格請點擊www.100y.com.tw



Part No.	Product No.	說明
51205	DCT-T-S	CRIMP 金色母端子 (FOR:GC-9FT4 用)



GC-15FT8

GC-15MT8

Part No.	Function	Description
15MT8	DB 15 Male; RJ-45 8-wire	DB 15 to RJ-45 Adapter
15FT8	DB 15 Female; RJ-45 8-wire	DB 15 to RJ-45 Adapter

Part No.	Product No.	說明
49784	GC-15FT8	連接器
3400	GC-15MT8	RS-232 15M/RJ45 8P8C 連接器



Part No.	Function	Description
GC-25FT6	DB 25 Female; RJ-12 6 wire	DB 25 to RJ-12 Adapter
GC-25FT8	DB 25 Female; RJ-45 8 wire	DB 25 to RJ-45 Adapter
GC-25MT8	DB 25 Male; RJ-45 8 wire	DB 25 to RJ-45 Adapter

Part No.	Product No.	說明
3401	GC-25FT6	組合連接器外殼母座 6P
6347	GC-25FT8	RS-232 25F/RJ45 8P8C 連接器
3839	GC-25MT8	RS232-25M/RJ45 8P8C 連接器



Part No.	Function	Description
GC-9FT4	DB 9 Female; RJ-11 4 wire	DB 9 to RJ-11 Adapter
GC-9FT6	DB 9 Female; RJ-12 6 wire	DB 9 to RJ-12 Adapter
GC-9FT8	DB 9 Female; RJ-45 8 wire	DB 9 to RJ-45 Adapter
GC-9MT6	DB 9 Male; RJ-12 6 wire	DB 9 to RJ-12 Adapter
GC-9MT8	DB 9 Male; RJ-45 8 wire	DB 9 to RJ-45 Adapter

Part No.	Product No.	說明
3398	GC-9FT4	RS232-9F/RJ11 6P4C 連接器
16467	GC-9FT6	RS-232 9 母轉 6C JACK
3838	GC-9FT8	RS232 9F-RJ45 8P8C 連接器
16844	GC-9MT6	RS-232 9M/RJ45 8P4C 連接器
3399	GC-9MT8	RS-232 9M/RJ45 8P8C 連接器

藍牙RS-232系列產品

詳細產品規格請點擊www.100y.com.tw

藍牙RS-232系列產品



- 傳輸速率：Supports 1.2/2.4/4.8/9.6/19.2/38.4/57.6/115.2 Kbps 5.2/230.4/460.8 Kbps
- 覆蓋範圍：達到100m
- 連接：點對點 (微型網路)
- RS-232接口：D SUB 9-pin Female
- 傳輸功率：Max. 18 dBm (Class 1)
- 電源：5-6V DC
- 尺寸：35mm (W) x 45 mm (H)x 15 mm (D)

Part No.	Product No.	說明	重量
57299	BT-232B	藍牙 RS-232 轉接器	37.42g



Part No.	Product No.	說明	範圍	RS-232 接口	傳輸功率	電源	尺寸	重量
57334	BTM-4C1	CSR Chip BC04 藍牙模組	達到 100m	USB, UART&PCM(for voice codec)	up to +18dBm ,Cclass1	2.7~3.6VDC	28.2*15	1.3g



- Bluetooth Specification V2.0
- Support up to 7 CAL connection and 3 SCO connection
- Support Faster connection, Flush timeout, Synchronisation, LMP improvements, AFH, Parameter range and LMP SCO Handle
- 13 bit PCM interface
- UART interface with programmable baud rate
- Compact size(25.0x14.9x2.5mm)

Part No.	Product No.	說明	範圍	RS-232 接口	傳輸功率	電源	尺寸
57335	BTM-4C2	藍牙 CSR Chip BC04 模組	達到 10m	USB,PCM,SPI,UART	-6 dBm to+3 dBm	VDD: 3.3V(1.8V)+/-0.1V Regulated supply voltage	25*14.9

